



STL24N60DM2 Information



For Reference Only

Part Number STL24N60DM2

Manufacturer STMicroelectronics

Category Discrete Semiconductor Products
Transistors - FETs, MOSFETs - Single

Description N-CHANNEL 600 V, 0.195 OHM TYP.,

Package 8-PowerVDFN

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









STL24N60DM2 Specifications

Manufacturer Part NumberSTL24N60DM2ManufacturerSTMicroelectronicsCategoryDiscrete Semiconductor ProductsTransistors - FETs, MOSFETs - SinglePackage8-PowerVDFNSeriesMDmesh?FET TypeN-ChannelTechnologyMOSFET (Metal Oxide)Drain to Source Voltage (Vdss)600VCurrent - Continuous Drain (Id) @ 25°C15A (Tc)Drive Voltage (Max Rds On, Min Rds On)10VVgs(th) (Max) @ Id5V @ 250μA	
Category Discrete Semiconductor Products Transistors - FETs, MOSFETs - Single 8-PowerVDFN Series MDmesh? FET Type N-Channel Technology MOSFET (Metal Oxide) Drain to Source Voltage (Vdss) Current - Continuous Drain (Id) @ 25°C Drive Voltage (Max Rds On, Min Rds On) Vgs(th) (Max) @ Id Discrete Semiconductor Products Transistors - FETs, MOSFETs - Single 8-PowerVDFN MDmesh? FET Type N-Channel 10V 10V 15A (Tc) 15A (Tc) 5V @ 250µA	
Transistors - FETs, MOSFETs - Single Package 8-PowerVDFN Series MDmesh? FET Type N-Channel Technology MOSFET (Metal Oxide) Drain to Source Voltage (Vdss) 600V Current - Continuous Drain (Id) @ 25°C 15A (Tc) Drive Voltage (Max Rds On, Min Rds On) 10V Vgs(th) (Max) @ Id 5V @ 250μA	
Package8-PowerVDFNSeriesMDmesh?FET TypeN-ChannelTechnologyMOSFET (Metal Oxide)Drain to Source Voltage (Vdss)600VCurrent - Continuous Drain (Id) @ 25°C15A (Tc)Drive Voltage (Max Rds On, Min Rds On)10VVgs(th) (Max) @ Id5V @ 250μA	
SeriesMDmesh?FET TypeN-ChannelTechnologyMOSFET (Metal Oxide)Drain to Source Voltage (Vdss)600VCurrent - Continuous Drain (Id) @ 25°C15A (Tc)Drive Voltage (Max Rds On, Min Rds On)10VVgs(th) (Max) @ Id5V @ 250μA	
FET Type N-Channel Technology MOSFET (Metal Oxide) Drain to Source Voltage (Vdss) Current - Continuous Drain (Id) @ 25°C Drive Voltage (Max Rds On, Min Rds On) Vgs(th) (Max) @ Id N-Channel MOSFET (Metal Oxide) 100V 15A (Tc) 5V @ 250μA	
Technology Drain to Source Voltage (Vdss) Current - Continuous Drain (Id) @ 25°C Drive Voltage (Max Rds On, Min Rds On) Vgs(th) (Max) @ Id MOSFET (Metal Oxide) 600V 15A (Tc) 15V 5V @ 250μA	
Drain to Source Voltage (Vdss) Current - Continuous Drain (Id) @ 25°C Drive Voltage (Max Rds On, Min Rds On) Vgs(th) (Max) @ Id 600V 15A (Tc) 10V 5V @ 250μA	
Current - Continuous Drain (Id) @ 25°C15A (Tc)Drive Voltage (Max Rds On, Min Rds On)10VVgs(th) (Max) @ Id5V @ 250μA	
Drive Voltage (Max Rds On, Min Rds On) 10V Vgs(th) (Max) @ Id 5V @ 250μA	
Vgs(th) (Max) @ Id 5V @ 250μA	
Gate Charge (Qg) (Max) @ Vgs 29nC @ 10V	
Input Capacitance (Ciss) (Max) @ Vds 1055pF @ 100V	
Vgs (Max) ±25V	
FET Feature -	
Power Dissipation (Max) 125W (Tc)	
Rds On (Max) @ Id, Vgs 220 mOhm @ 9A, 10V	
Operating Temperature $-55^{\circ}\text{C} \sim 150^{\circ}\text{C} \text{ (TJ)}$	
Mounting Type Surface Mount	
Supplier Device Package PowerFlat? (8x8) HV	
Package / Case 8-PowerVDFN	
Repor	t errors?

STL24N60DM2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

STL24N60DM2 Payment Methods





















STL24N60DM2 Shipping Methods













If you have any question about STL24N60DM2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com