



STM32L031F6P6 Information

Part Number STM32L031F6P6

Manufacturer STMicroelectronics

Category Integrated Circuits (ICs)
Embedded - Microcontrollers

Description IC MCU 32BIT 32KB FLASH 20TSSOP **Package** 20-TSSOP (0.173", 4.40mm Width)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









STM32L031F6P6 Specifications

| Manufacturer Part Number Manufacturer STMicroelectronics Category Integrated Circuits (ICs) Embedded - Microcontrollers Package 20-TSSOP (0.173", 4.40mm Width) Series STM32 L0 Core Processor ARM? Cortex?-M0+ Core Size 32-Bit Speed 32MHz Connectivity I2C, IrDA, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 15 Page 20 MB 22 MB 23 MB 22 MB 23 MB 24 MB 24 MB 24 MB 24 MB 25 MB 26 MB |
|--|
| Category Integrated Circuits (ICs) Embedded - Microcontrollers Package 20-TSSOP (0.173", 4.40mm Width) Series STM32 L0 Core Processor ARM? Cortex?-M0+ Core Size 32-Bit Speed 32MHz Connectivity I2C, IrDA, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 15 |
| Embedded - Microcontrollers Package 20-TSSOP (0.173", 4.40mm Width) Series STM32 L0 Core Processor ARM? Cortex?-M0+ Core Size 32-Bit Speed 32MHz Connectivity I2C, IrDA, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 15 |
| Package 20-TSSOP (0.173", 4.40mm Width) Series STM32 L0 Core Processor ARM? Cortex?-M0+ Core Size 32-Bit Speed 32MHz Connectivity I2C, IrDA, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 15 |
| SeriesSTM32 L0Core ProcessorARM? Cortex?-M0+Core Size32-BitSpeed32MHzConnectivityI2C, IrDA, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, DMA, POR, PWM, WDTNumber of I/O15 |
| Core Processor ARM? Cortex?-M0+ 32-Bit Speed 32MHz Connectivity I2C, IrDA, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 15 |
| Core Size 32-Bit Speed 32MHz Connectivity I2C, IrDA, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 15 |
| Speed 32MHz Connectivity I2C, IrDA, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 15 |
| Connectivity I2C, IrDA, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 15 |
| Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 15 |
| Number of I/O 15 |
| |
| D |
| Program Memory Size 32KB (32K x 8) |
| Program Memory Type FLASH |
| EEPROM Size 1K x 8 |
| RAM Size 8K x 8 |
| Voltage - Supply (Vcc/Vdd) $1.8 \text{ V} \sim 3.6 \text{ V}$ |
| Data Converters A/D 10x12b |
| Oscillator Type Internal |
| Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C} \text{ (TA)}$ |
| Mounting Type - |
| Package / Case 20-TSSOP (0.173", 4.40mm Width) |
| Supplier Device Package 20-TSSOP |
| Report errors |

STM32L031F6P6 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

STM32L031F6P6 Payment Methods



















STM32L031F6P6 Shipping Methods













If you have any question about STM32L031F6P6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com