



STM8AL3148TCY Information



For Reference Only

Part Number STM8AL3148TCY

Manufacturer STMicroelectronics

Category Integrated Circuits (ICs)
Embedded - Microcontrollers

Description IC MCU 8BIT 16KB FLASH 48LQFP

Package 48-LQFP

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









STM8AL3148TCY Specifications

Manufacturer Part NumberSTM8AL3148TCYManufacturerSTMicroelectronicsCategoryIntegrated Circuits (ICs)Embedded - MicrocontrollersPackage48-LQFPSeriesAutomotive, AEC-Q100, STM8ACore ProcessorSTM8Core Size8-BitSpeed16MHzConnectivityI2C, IrDA, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, DMA, POR, PWM, WDTNumber of I/O41Program Memory Size16KB (16K x 8)Program Memory TypeFLASHEEPROM Size1K x 8RAM Size2K x 8Voltage - Supply (Vcc/Vdd)1.65 V ~ 3.6 V
Category Integrated Circuits (ICs) Embedded - Microcontrollers Package 48-LQFP Series Automotive, AEC-Q100, STM8A Core Processor STM8 Core Size 8-Bit Speed 16MHz Connectivity I2C, IrDA, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 41 Program Memory Size 16KB (16K x 8) Program Memory Type FLASH EEPROM Size 1K x 8 RAM Size 2K x 8 Voltage - Supply (Vcc/Vdd) 1.65 V ~ 3.6 V
Embedded - Microcontrollers Package 48-LQFP Series Automotive, AEC-Q100, STM8A Core Processor STM8 Core Size 8-Bit Speed 16MHz Connectivity I2C, IrDA, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 41 Program Memory Size 16KB (16K x 8) Program Memory Type FLASH EEPROM Size 1K x 8 RAM Size 2K x 8 Voltage - Supply (Vcc/Vdd) 1.65 V ~ 3.6 V
Package 48-LQFP Series Automotive, AEC-Q100, STM8A Core Processor STM8 Core Size 8-Bit Speed 16MHz Connectivity I2C, IrDA, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 41 Program Memory Size 16KB (16K x 8) Program Memory Type FLASH EEPROM Size 1K x 8 RAM Size 2K x 8 Voltage - Supply (Vcc/Vdd) 1.65 V ~ 3.6 V
Series Automotive, AEC-Q100, STM8A Core Processor STM8 Core Size 8-Bit Speed 16MHz Connectivity I2C, IrDA, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 41 Program Memory Size 16KB (16K x 8) Program Memory Type FLASH EEPROM Size 1K x 8 RAM Size 2K x 8 Voltage - Supply (Vcc/Vdd) 1.65 V ~ 3.6 V
Core Processor Core Size 8-Bit Speed 16MHz Connectivity I2C, IrDA, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 41 Program Memory Size 16KB (16K x 8) Program Memory Type FLASH EEPROM Size 1K x 8 RAM Size Voltage - Supply (Vcc/Vdd) 1.65 V ~ 3.6 V
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$
Speed 16MHz Connectivity I2C, IrDA, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 41 Program Memory Size 16KB (16K x 8) Program Memory Type FLASH EEPROM Size 1K x 8 RAM Size 2K x 8 Voltage - Supply (Vcc/Vdd) 1.65 V ~ 3.6 V
Connectivity I2C, IrDA, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 41 Program Memory Size $16KB (16K \times 8)$ Program Memory Type $FLASH$ EEPROM Size $1K \times 8$ RAM Size $2K \times 8$ Voltage - Supply (Vcc/Vdd) $1.65 \text{ V} \sim 3.6 \text{ V}$
Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 41 Program Memory Size 16KB (16K x 8) Program Memory Type FLASH EEPROM Size 1K x 8 RAM Size 2K x 8 Voltage - Supply (Vcc/Vdd) 1.65 V \sim 3.6 V
Number of I/O 41 Program Memory Size 16KB (16K x 8) Program Memory Type FLASH EEPROM Size 1K x 8 RAM Size 2K x 8 Voltage - Supply (Vcc/Vdd) 1.65 V ~ 3.6 V
Program Memory Size $16KB (16K \times 8)$ Program Memory Type $FLASH$ EEPROM Size $1K \times 8$ RAM Size $2K \times 8$ Voltage - Supply (Vcc/Vdd) $1.65 \text{ V} \sim 3.6 \text{ V}$
Program Memory Type FLASH EEPROM Size $1K \times 8$ RAM Size $2K \times 8$ Voltage - Supply (Vcc/Vdd) $1.65 \text{ V} \sim 3.6 \text{ V}$
EEPROM Size $1K \times 8$ RAM Size $2K \times 8$ Voltage - Supply (Vcc/Vdd) $1.65 \text{ V} \sim 3.6 \text{ V}$
RAM Size 2K x 8 Voltage - Supply (Vcc/Vdd) 1.65 V ~ 3.6 V
Voltage - Supply (Vcc/Vdd) 1.65 V ~ 3.6 V
Data Converters A/D 25x12b, D/A 1x12b
Oscillator Type Internal
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C} \text{ (TA)}$
Mounting Type -
Package / Case 48-LQFP
Supplier Device Package 48-LQFP (7x7)
Report erro

STM8AL3148TCY Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

STM8AL3148TCY Payment Methods



















STM8AL3148TCY Shipping Methods













If you have any question about STM8AL3148TCY, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com