

STPS30L120CFP

STPS30L120CFP Information

	Part Number	STPS30L120CFP
	Manufacturer	STMicroelectronics
www.heisenen.com	Category	Discrete Semiconductor Products Diodes - Rectifiers - Arrays
	Description	DIODE ARRAY SCHOTTKY 120V TO220F
	Package	TO-220-3 Full Pack
		For the pricing/inventory/lead time, please contact us
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



STPS30L120CFP Specifications

ManufacturerSTMicroelectronicsCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - ArraysPackageTO-220-3 Full PackSeries-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)120VCurrent - Average Rectified (Io) (per Diode)15AVoltage - Forward (Vf) (Max) @ If880mV @ 15ASpeedFast Recovery =< 500ms, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200µA @ 120VOperating Temperature - Junction150°C (Max)Mounting TypeThrough HolePackage / CaseTO-220-3 Full Pack		
CategoryDiscrete Semiconductor ProductsCategoryDiodes - Rectifiers - ArraysPackageTO-220-3 Full PackSeries-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)120VCurrent - Average Rectified (Io) (per Diode)15AVoltage - Forward (Vf) (Max) @ If880mV @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200µA @ 120VOperating Temperature - Junction150°C (Max)Mounting TypeThrough HolePackage / CaseTO-220-3 Full PackSupplier Device PackageTO-220FP	Manufacturer Part Number	STPS30L120CFP
Diodes - Rectifiers - ArraysPackageTO-220-3 Full PackSeries-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)120VCurrent - Average Rectified (Io) (per Diode)15AVoltage - Forward (Vf) (Max) @ If880mV @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200μA @ 120VOperating Temperature - Junction150°C (Max)Mounting TypeThrough HolePackage / CaseTO-220-F Full PackSupplier Device PackageTO-220FP	Manufacturer	STMicroelectronics
PackageTO-220-3 Full PackSeries-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)120VCurrent - Average Rectified (Io) (per Diode)15AVoltage - Forward (Vf) (Max) @ If880mV @ 15ASpeedFast Recovery =< 500ms, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200µA @ 120VOperating Temperature - Junction150°C (Max)Mounting TypeThrough HolePackage / CaseTO-220-3 Full PackSupplier Device PackageTO-220FP	Category	Discrete Semiconductor Products
Series-Series-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)120VCurrent - Average Rectified (Io) (per Diode)15AVoltage - Forward (Vf) (Max) @ If880mV @ 15ASpeedFast Recovery = < 500ms, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200µA @ 120VOperating Temperature - Junction150°C (Max)Mounting TypeThrough HolePackage / CaseTO-220-3 Full PackSupplier Device PackageTO-220FP		Diodes - Rectifiers - Arrays
Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)120VCurrent - Average Rectified (Io) (per Diode)15AVoltage - Forward (Vf) (Max) @ If880mV @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200µA @ 120VOperating Temperature - Junction150°C (Max)Mounting TypeThrough HolePackage / CaseTO-220-3 Full PackSupplier Device PackageTO-220FP	Package	TO-220-3 Full Pack
Diode TypeSchottkyDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)120VCurrent - Average Rectified (Io) (per Diode)15AVoltage - Forward (Vf) (Max) @ If880mV @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200µA @ 120VOperating Temperature - Junction150°C (Max)Mounting TypeThrough HolePackage / CaseTO-220-3 Full PackSupplier Device PackageTO-220FP	Series	-
Voltage - DC Reverse (Vr) (Max)120VCurrent - Average Rectified (Io) (per Diode)15AVoltage - Forward (Vf) (Max) @ If880mV @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200µA @ 120VOperating Temperature - Junction150°C (Max)Mounting TypeThrough HolePackage / CaseTO-220-3 Full PackSupplier Device PackageTO-220FP	Diode Configuration	1 Pair Common Cathode
Current - Average Rectified (Io) (per Diode)15AVoltage - Forward (Vf) (Max) @ If880mV @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200µA @ 120VOperating Temperature - Junction150°C (Max)Mounting TypeThrough HolePackage / CaseTO-220-3 Full PackSupplier Device PackageTO-220FP	Diode Type	Schottky
Voltage - Forward (Vf) (Max) @ If880mV @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200µA @ 120VOperating Temperature - Junction150°C (Max)Mounting TypeThrough HolePackage / CaseTO-220-3 Full PackSupplier Device PackageTO-220FP	Voltage - DC Reverse (Vr) (Max)	120V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200µA @ 120VOperating Temperature - Junction150°C (Max)Mounting TypeThrough HolePackage / CaseTO-220-3 Full PackSupplier Device PackageTO-220FP	Current - Average Rectified (Io) (per Diode)	15A
Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200μA @ 120VOperating Temperature - Junction150°C (Max)Mounting TypeThrough HolePackage / CaseTO-220-3 Full PackSupplier Device PackageTO-220FP	Voltage - Forward (Vf) (Max) @ If	880mV @ 15A
Current - Reverse Leakage @ Vr200µA @ 120VOperating Temperature - Junction150°C (Max)Mounting TypeThrough HolePackage / CaseTO-220-3 Full PackSupplier Device PackageTO-220FP	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Operating Temperature - Junction150°C (Max)Mounting TypeThrough HolePackage / CaseTO-220-3 Full PackSupplier Device PackageTO-220FP	Reverse Recovery Time (trr)	-
Mounting TypeThrough HolePackage / CaseTO-220-3 Full PackSupplier Device PackageTO-220FP	Current - Reverse Leakage @ Vr	200µA @ 120V
Package / CaseTO-220-3 Full PackSupplier Device PackageTO-220FP	Operating Temperature - Junction	150°C (Max)
Supplier Device Package TO-220FP	Mounting Type	Through Hole
	Package / Case	TO-220-3 Full Pack
Report errors?	Supplier Device Package	TO-220FP
		Report errors?

STPS30L120CFP Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

STPS30L120CFP Payment Methods



STPS30L120CFP Shipping Methods



If you have any question about STPS30L120CFP, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com