



STSR2PMCD-TR Information



For Reference Only

Part Number STSR2PMCD-TR

Manufacturer STMicroelectronics

Category Integrated Circuits (ICs)
PMIC - Gate Drivers

DescriptionIC SMART DRIVER SYNC 8-SOIC**Package**8-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









STSR2PMCD-TR Specifications

Manufacturer Part NumberSTSR2PMCD-TRManufacturerSTMicroelectronicsCategoryIntegrated Circuits (ICs)Package8-SOIC (0.154", 3.90mm Width)Series-Driven ConfigurationLow-SideChannel TypeSynchronousNumber of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply4.5 V ~ 5.5 VLogic Voltage - VIL, VIH-Current - Peak Output (Source, Sink)2A, 3.5AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)40ns, 30nsOperating Temperature-40°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC (0.154", 3.90mm Width)		
CategoryIntegrated Circuits (ICs)Package8-SOIC (0.154", 3.90mm Width)Series-Driven ConfigurationLow-SideChannel TypeSynchronousNumber of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply4.5 V ~ 5.5 VLogic Voltage - VIL, VIH-Current - Peak Output (Source, Sink)2A, 3.5AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)40ns, 30nsOperating Temperature-40°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Manufacturer Part Number	STSR2PMCD-TR
Package 8-SOIC (0.154", 3.90mm Width) Series - Driven Configuration Low-Side Channel Type Synchronous Number of Drivers 2 Gate Type N-Channel MOSFET Voltage - Supply 4.5 V ~ 5.5 V Logic Voltage - VIL, VIH - Current - Peak Output (Source, Sink) 2A, 3.5A Input Type Non-Inverting High Side Voltage - Max (Bootstrap) - Rise / Fall Time (Typ) 40ns, 30ns Operating Temperature 40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Manufacturer	STMicroelectronics
Package8-SOIC (0.154", 3.90mm Width)Series-Driven ConfigurationLow-SideChannel TypeSynchronousNumber of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply4.5 V ~ 5.5 VLogic Voltage - VIL, VIH-Current - Peak Output (Source, Sink)2A, 3.5AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)40ns, 30nsOperating Temperature-40°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SO	Category	Integrated Circuits (ICs)
Series-Driven ConfigurationLow-SideChannel TypeSynchronousNumber of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply4.5 V ~ 5.5 VLogic Voltage - VIL, VIH-Current - Peak Output (Source, Sink)2A, 3.5AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)40ns, 30nsOperating Temperature-40°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SO		PMIC - Gate Drivers
Driven Configuration Channel Type Synchronous Number of Drivers 2 Gate Type N-Channel MOSFET Voltage - Supply 4.5 V ~ 5.5 V Logic Voltage - VIL, VIH - Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) 40ns, 30ns Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Package	8-SOIC (0.154", 3.90mm Width)
Channel Type Number of Drivers 2 Gate Type N-Channel MOSFET Voltage - Supply 4.5 V ~ 5.5 V Logic Voltage - VIL, VIH - Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) 40ns, 30ns Operating Temperature 40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Series	-
Number of Drivers Gate Type N-Channel MOSFET Voltage - Supply 4.5 V ~ 5.5 V Logic Voltage - VIL, VIH Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature 40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Driven Configuration	Low-Side
Gate Type N-Channel MOSFET Voltage - Supply 4.5 V ~ 5.5 V Logic Voltage - VIL, VIH - Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature 40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Channel Type	Synchronous
Voltage - Supply Logic Voltage - VIL, VIH - Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Number of Drivers	2
Logic Voltage - VIL, VIH-Current - Peak Output (Source, Sink)2A, 3.5AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)40ns, 30nsOperating Temperature-40°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SO	Gate Type	N-Channel MOSFET
Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Voltage - Supply	4.5 V ~ 5.5 V
Input Type High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Logic Voltage - VIL, VIH	-
High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) 40ns, 30ns Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SO	Current - Peak Output (Source, Sink)	2A, 3.5A
Rise / Fall Time (Typ) Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Input Type	Non-Inverting
Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SO	High Side Voltage - Max (Bootstrap)	-
Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SO	Rise / Fall Time (Typ)	40ns, 30ns
Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SO	Operating Temperature	-40°C ~ 125°C (TJ)
Supplier Device Package 8-SO	Mounting Type	Surface Mount
	Package / Case	8-SOIC (0.154", 3.90mm Width)
Report errors?	Supplier Device Package	8-SO
Report crists:		Report errors?

STSR2PMCD-TR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

STSR2PMCD-TR Payment Methods



















STSR2PMCD-TR Shipping Methods













If you have any question about STSR2PMCD-TR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com