



STTH3L06B Information



For Reference Only

Part Number STTH3L06B

Manufacturer STMicroelectronics

Category Discrete Semiconductor Products

Diodes - Rectifiers - Single

DescriptionDIODE GEN PURP 600V 3A DPAK**Package**TO-252-3, DPak (2 Leads + Tab), SC-63

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









STTH3L06B Specifications

Manufacturer Part NumberSTTH3L06BManufacturerSTMicroelectronicsCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageTO-252-3, DPak (2 Leads + Tab), SC-63Series-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io)3AVoltage - Forward (Vf) (Max) @ If1.3V @ 3ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)85nsCurrent - Reverse Leakage @ Vr3μA @ 600V
CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageTO-252-3, DPak (2 Leads + Tab), SC-63Series-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io)3AVoltage - Forward (Vf) (Max) @ If1.3V @ 3ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)85nsCurrent - Reverse Leakage @ Vr3μA @ 600V
Diodes - Rectifiers - Single Package TO-252-3, DPak (2 Leads + Tab), SC-63 Series - Diode Type Standard Voltage - DC Reverse (Vr) (Max) 600V Current - Average Rectified (Io) 3A Voltage - Forward (Vf) (Max) @ If 1.3V @ 3A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 85ns Current - Reverse Leakage @ Vr 3μA @ 600V
Package TO-252-3, DPak (2 Leads + Tab), SC-63 Series - Diode Type Standard Voltage - DC Reverse (Vr) (Max) 600V Current - Average Rectified (Io) 3A Voltage - Forward (Vf) (Max) @ If 1.3V @ 3A Speed Fast Recovery =< 500 ns, > 200 mA (Io) Reverse Recovery Time (trr) 85ns Current - Reverse Leakage @ Vr 3μ A @ 600 V
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$
Diode Type Standard Voltage - DC Reverse (Vr) (Max) 600V Current - Average Rectified (Io) 3A Voltage - Forward (Vf) (Max) @ If 1.3V @ 3A Speed Fast Recovery =< 500 ns, > 200 mA (Io) Reverse Recovery Time (trr) 85ns Current - Reverse Leakage @ Vr 3 μ A @ 600 V
Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 85ns Current - Reverse Leakage @ Vr 3μA @ 600V
Current - Average Rectified (Io) 3A Voltage - Forward (Vf) (Max) @ If 1.3V @ 3A Speed Fast Recovery =< 500 ns, > 200 mA (Io) Reverse Recovery Time (trr) 85ns Current - Reverse Leakage @ Vr 3 μ A @ 600 V
Voltage - Forward (Vf) (Max) @ If
$Speed \\ Reverse Recovery = < 500ns, > 200mA (Io) \\ Reverse Recovery Time (trr) \\ S5ns \\ Current - Reverse Leakage @ Vr \\ 3\mu A @ 600V$
Reverse Recovery Time (trr) 85ns Current - Reverse Leakage @ Vr 3µA @ 600V
Current - Reverse Leakage @ Vr 3µA @ 600V
,
Capacitance @ Vr, F
Mounting Type Surface Mount
Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63
Supplier Device Package D-Pak
Operating Temperature - Junction 175°C (Max)
Report errors?

STTH3L06B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

STTH3L06B Payment Methods



















STTH3L06B Shipping Methods













If you have any question about STTH3L06B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com