



STW32NM50N Information



For Reference Only

Part Number STW32NM50N
Manufacturer STMicroelectronics

Category Discrete Semiconductor Products

Transistors - FETs, MOSFETs - Single

Description MOSFET N CH 500V 22A TO-247

Package TO-247-3

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









STW32NM50N Specifications

Manufacturer Part Number STW32NM50N Manufacturer STMicroelectronics Category Discrete Semiconductor Products Transistors - FETs, MOSFETs - Single Package TO-247-3 Series MDmesh? II FET Type N-Channel Technology MOSFET (Metal Oxide) Drain to Source Voltage (Vdss) 500V Current - Continuous Drain (Id) @ 25°C 22A (Tc) Drive Voltage (Max Rds On, Min Rds On) 10V Vgs(th) (Max) @ Id 4V @ 250µA Gate Charge (Qg) (Max) @ Vgs 1973pF @ 50V Vgs (Max) 190W (Tc) Rds On (Max) @ Id, Vgs 130 mOhm @ 11A, 10V Operating Temperature 150°C (TJ) Mounting Type Through Hole Supplier Device Package TO-247 Package / Case TO-247-3 Report errors?		
Category Discrete Semiconductor Products Transistors - FETs, MOSFETs - Single Package TO-247-3 Series MDmesh? II FET Type N-Channel Technology MOSFET (Metal Oxide) Drain to Source Voltage (Vdss) 500V Current - Continuous Drain (Id) @ 25°C 22A (Tc) Drive Voltage (Max Rds On, Min Rds On) 10V Vgs(th) (Max) @ Id 4V @ 250µA Gate Charge (Qg) (Max) @ Vgs 62.5nC @ 10V Input Capacitance (Ciss) (Max) @ Vds 1973pF @ 50V Vgs (Max) ±25V FET Feature - Power Dissipation (Max) 190W (Tc) Rds On (Max) @ Id, Vgs 130 mOhm @ 11A, 10V Operating Temperature 150°C (TJ) Mounting Type Through Hole Supplier Device Package TO-247- Package / Case TO-247-3	Manufacturer Part Number	STW32NM50N
Package TO-247-3 Series MDmesh? II FET Type N-Channel Technology MOSFET (Metal Oxide) Drain to Source Voltage (Vdss) 500V Current - Continuous Drain (Id) @ 25°C 22A (Tc) Drive Voltage (Max Rds On, Min Rds On) 10V Vgs(th) (Max) @ Id 4V @ 250μA Gate Charge (Qg) (Max) @ Vgs 62.5nC @ 10V Input Capacitance (Ciss) (Max) @ Vds 1973pF @ 50V Vgs (Max) ±25V FET Feature - Power Dissipation (Max) 190W (Tc) Rds On (Max) @ Id, Vgs 130 mOhm @ 11A, 10V Operating Temperature 150°C (TJ) Mounting Type Through Hole Supplier Device Package TO-247 Package / Case TO-247-3	Manufacturer	STMicroelectronics
Package TO-247-3 Series MDmesh? II FET Type N-Channel Technology MOSFET (Metal Oxide) Drain to Source Voltage (Vdss) 500V Current - Continuous Drain (Id) @ 25°C 22A (Tc) Drive Voltage (Max Rds On, Min Rds On) 10V Vgs(th) (Max) @ Id 4V @ 250μA Gate Charge (Qg) (Max) @ Vgs 62.5nC @ 10V Input Capacitance (Ciss) (Max) @ Vds 1973pF @ 50V Vgs (Max) ±25V FET Feature - Power Dissipation (Max) 190W (Tc) Rds On (Max) @ Id, Vgs 130 mOhm @ 11A, 10V Operating Temperature 150°C (TJ) Mounting Type Through Hole Supplier Device Package TO-247 Package / Case TO-247-3	Category	Discrete Semiconductor Products
Series MDmesh? II FET Type N-Channel Technology MOSFET (Metal Oxide) Tonin to Source Voltage (Vdss) Current - Continuous Drain (Id) @ 25°C 22A (Tc) Drive Voltage (Max Rds On, Min Rds On) 10V Vgs(th) (Max) @ Id 4V @ 250µA Gate Charge (Qg) (Max) @ Vgs 62.5nC @ 10V Input Capacitance (Ciss) (Max) @ Vds 1973pF @ 50V Vgs (Max) ±25V FET Feature - Power Dissipation (Max) 190W (Tc) Rds On (Max) @ Id, Vgs 130 mOhm @ 11A, 10V Operating Temperature 150°C (TJ) Mounting Type Through Hole Supplier Device Package 70-247 Package / Case		Transistors - FETs, MOSFETs - Single
FET TypeN-ChannelTechnologyMOSFET (Metal Oxide)Drain to Source Voltage (Vdss)500VCurrent - Continuous Drain (Id) @ 25°C22A (Tc)Drive Voltage (Max Rds On, Min Rds On)10VVgs(th) (Max) @ Id4V @ 250μAGate Charge (Qg) (Max) @ Vgs62.5nC @ 10VInput Capacitance (Ciss) (Max) @ Vds1973pF @ 50VVgs (Max)±25VFET Feature-Power Dissipation (Max)190W (Tc)Rds On (Max) @ Id, Vgs130 mOhm @ 11A, 10VOperating Temperature150°C (TJ)Mounting TypeThrough HoleSupplier Device PackageTO-247Package / CaseTO-247-3	Package	TO-247-3
TechnologyMOSFET (Metal Oxide)Drain to Source Voltage (Vdss)500VCurrent - Continuous Drain (Id) @ 25°C22A (Tc)Drive Voltage (Max Rds On, Min Rds On)10VVgs(th) (Max) @ Id4V @ 250μAGate Charge (Qg) (Max) @ Vgs62.5nC @ 10VInput Capacitance (Ciss) (Max) @ Vds1973pF @ 50VVgs (Max)±25VFET Feature-Power Dissipation (Max)190W (Tc)Rds On (Max) @ Id, Vgs130 mOhm @ 11A, 10VOperating Temperature150°C (TJ)Mounting TypeThrough HoleSupplier Device PackageTO-247Package / CaseTO-247-3	Series	MDmesh? II
Drain to Source Voltage (Vdss)500VCurrent - Continuous Drain (Id) @ 25°C22A (Tc)Drive Voltage (Max Rds On, Min Rds On)10VVgs(th) (Max) @ Id4V @ 250μAGate Charge (Qg) (Max) @ Vgs62.5nC @ 10VInput Capacitance (Ciss) (Max) @ Vds1973pF @ 50VVgs (Max)±25VFET Feature-Power Dissipation (Max)190W (Tc)Rds On (Max) @ Id, Vgs130 mOhm @ 11A, 10VOperating Temperature150°C (TJ)Mounting TypeThrough HoleSupplier Device PackageTO-247Package / CaseTO-247-3	FET Type	N-Channel
Current - Continuous Drain (Id) @ 25°C Drive Voltage (Max Rds On, Min Rds On) Vgs(th) (Max) @ Id Gate Charge (Qg) (Max) @ Vgs Input Capacitance (Ciss) (Max) @ Vds Vgs (Max) FET Feature Power Dissipation (Max) Rds On (Max) @ Id, Vgs 130 mOhm @ 11A, 10V Operating Temperature Mounting Type Through Hole Supplier Device Package Package / Case 22A (Tc) 4V @ 250μA 62.5nC @ 10V 1973pF @ 50V 25V FET Feature - Power Dissipation (Max) 190W (Tc) 130 mOhm @ 11A, 10V Through Hole	Technology	MOSFET (Metal Oxide)
Drive Voltage (Max Rds On, Min Rds On)10VVgs(th) (Max) @ Id4V @ 250μAGate Charge (Qg) (Max) @ Vgs62.5nC @ 10VInput Capacitance (Ciss) (Max) @ Vds1973pF @ 50VVgs (Max)±25VFET Feature-Power Dissipation (Max)190W (Tc)Rds On (Max) @ Id, Vgs130 mOhm @ 11A, 10VOperating Temperature150°C (TJ)Mounting TypeThrough HoleSupplier Device PackageTO-247Package / CaseTO-247-3	Drain to Source Voltage (Vdss)	500V
Vgs(th) (Max) @ Id Gate Charge (Qg) (Max) @ Vgs 62.5nC @ 10V Input Capacitance (Ciss) (Max) @ Vds 1973pF @ 50V Vgs (Max) ET Feature - Power Dissipation (Max) Rds On (Max) @ Id, Vgs 130 mOhm @ 11A, 10V Operating Temperature 150°C (TJ) Mounting Type Through Hole Supplier Device Package TO-247 Package / Case TO-247-3	Current - Continuous Drain (Id) @ 25°C	22A (Tc)
Gate Charge (Qg) (Max) @ Vgs Input Capacitance (Ciss) (Max) @ Vds 1973pF @ 50V Vgs (Max) ±25V FET Feature - Power Dissipation (Max) Rds On (Max) @ Id, Vgs 130 mOhm @ 11A, 10V Operating Temperature 150°C (TJ) Mounting Type Through Hole Supplier Device Package TO-247 Package / Case TO-247-3	Drive Voltage (Max Rds On, Min Rds On)	10V
Input Capacitance (Ciss) (Max) @ Vds Vgs (Max) ET Feature Power Dissipation (Max) Rds On (Max) @ Id, Vgs 130 mOhm @ 11A, 10V Operating Temperature 150°C (TJ) Mounting Type Through Hole Supplier Device Package TO-247 Package / Case TO-247-3	Vgs(th) (Max) @ Id	4V @ 250μA
Vgs (Max)±25VFET Feature-Power Dissipation (Max)190W (Tc)Rds On (Max) @ Id, Vgs130 mOhm @ 11A, 10VOperating Temperature150°C (TJ)Mounting TypeThrough HoleSupplier Device PackageTO-247Package / CaseTO-247-3	Gate Charge (Qg) (Max) @ Vgs	62.5nC @ 10V
FET Feature - Power Dissipation (Max) 190W (Tc) Rds On (Max) @ Id, Vgs 130 mOhm @ 11A, 10V Operating Temperature 150°C (TJ) Mounting Type Through Hole Supplier Device Package TO-247 Package / Case TO-247-3	Input Capacitance (Ciss) (Max) @ Vds	1973pF @ 50V
Power Dissipation (Max) Rds On (Max) @ Id, Vgs 130 mOhm @ 11A, 10V Operating Temperature 150°C (TJ) Mounting Type Through Hole Supplier Device Package TO-247 Package / Case TO-247-3	Vgs (Max)	±25V
Rds On (Max) @ Id, Vgs 130 mOhm @ 11A, 10V Operating Temperature 150°C (TJ) Mounting Type Through Hole Supplier Device Package TO-247 Package / Case TO-247-3	FET Feature	-
Operating Temperature 150°C (TJ) Mounting Type Through Hole Supplier Device Package TO-247 Package / Case TO-247-3	Power Dissipation (Max)	190W (Tc)
Mounting Type Through Hole Supplier Device Package TO-247 Package / Case TO-247-3	Rds On (Max) @ Id, Vgs	130 mOhm @ 11A, 10V
Supplier Device Package TO-247 Package / Case TO-247-3	Operating Temperature	150°C (TJ)
Package / Case TO-247-3	Mounting Type	Through Hole
	Supplier Device Package	TO-247
Report errors?	Package / Case	TO-247-3
		Report errors?

STW32NM50N Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

STW32NM50N Payment Methods



















STW32NM50N Shipping Methods













If you have any question about STW32NM50N, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com