

SWG030-05 Information



For Reference Only

Part Number SWG030-05 Manufacturer Sanken

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 5V 30W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









Manufacturer Sanken Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series SWG030 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -10°C ~ 71°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 4.06" L x 1.22" W x 3.08" H (103.0mm x 31.0mm x 78.0mm)			
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series SWG030 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -10°C ~ 71°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 4.06" L x 1.22" W x 3.08" H (103.0mm x 31.0mm x 78.0mm)	Manufacturer Part Number	SWG030-05	
AC DC Converters Package - Series SWG030 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -10°C ~ 71°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 4.06" L x 1.22" W x 3.08" H (103.0mm x 31.0mm x 78.0mm)	Manufacturer	Sanken	
Package - Series SWG030 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -10°C ~ 71°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 4.06" L x 1.22" W x 3.08" H (103.0mm x 31.0mm x 78.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series SWG030 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -10°C ~ 71°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 4.06" L x 1.22" W x 3.08" H (103.0mm x 31.0mm x 78.0mm)		AC DC Converters	
Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -10°C ~ 71°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 4.06" L x 1.22" W x 3.08" H (103.0mm x 31.0mm x 78.0mm)	Package	-	
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -10°C ~ 71°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 4.06" L x 1.22" W x 3.08" H (103.0mm x 31.0mm x 78.0mm)	Series	SWG030	
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -10°C ~ 71°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 4.06" L x 1.22" W x 3.08" H (103.0mm x 31.0mm x 78.0mm)	Туре	Open Frame	
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Applications Voltage - Isolation Size / Dimension 5V Voltage - Output 4 - Current - Output (Max) 6A A A A Bower (Watts) Applications ITE (Commercial) Avoltage - Isolation Size / Dimension 5V Chassis Mount 5V Applications Chassis Mount 5V Applications Applications Chassis Mount Applications Chassis Mount Applications Applications Chassis Mount Applications Appli	Number of Outputs	1	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature Features DC Input Capable, Universal Input Mounting Type Chassis Mount 4.06" L x 1.22" W x 3.08" H (103.0mm x 31.0mm x 78.0mm)	Voltage - Input	85 ~ 264 VAC	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature Features DC Input Capable, Universal Input Mounting Type Size / Dimension - Output 4 - Current - Output (Max) AR AR - Current - Output (Max) - Commercial) AkV (3000V) Six (3000V) - Civit Derating) Chassis Mount 4.06" L x 1.22" W x 3.08" H (103.0mm x 31.0mm x 78.0mm)	Voltage - Output 1	5V	
Voltage - Output 4 Current - Output (Max) 6A Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -10°C ~ 71°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension - Ux 1.22" Wx 3.08" H (103.0mm x 31.0mm x 78.0mm)	Voltage - Output 2	-	
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -10°C ~ 71°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 6A 100 100 100 100 100 100 100	Voltage - Output 3	-	
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -10°C ~ 71°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 4.06" L x 1.22" W x 3.08" H (103.0mm x 31.0mm x 78.0mm)	Voltage - Output 4	-	
Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -10°C ~ 71°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 4.06" L x 1.22" W x 3.08" H (103.0mm x 31.0mm x 78.0mm)	Current - Output (Max)	6A	
Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -10°C ~ 71°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 4.06" L x 1.22" W x 3.08" H (103.0mm x 31.0mm x 78.0mm)	Power (Watts)	30W	
Efficiency 77% Operating Temperature -10°C ~ 71°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 4.06" L x 1.22" W x 3.08" H (103.0mm x 31.0mm x 78.0mm)	Applications	ITE (Commercial)	
Operating Temperature -10°C ~ 71°C (With Derating) DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension -10°C ~ 71°C (With Derating) DC Input Capable, Universal Input Chassis Mount 4.06" L x 1.22" W x 3.08" H (103.0mm x 31.0mm x 78.0mm)	Voltage - Isolation	3kV (3000V)	
Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 4.06" L x 1.22" W x 3.08" H (103.0mm x 31.0mm x 78.0mm)	Efficiency	77%	
Mounting Type Chassis Mount Size / Dimension 4.06" L x 1.22" W x 3.08" H (103.0mm x 31.0mm x 78.0mm)	Operating Temperature	-10° C ~ 71° C (With Derating)	
Size / Dimension 4.06" L x 1.22" W x 3.08" H (103.0mm x 31.0mm x 78.0mm)	Features	DC Input Capable, Universal Input	
` '	Mounting Type	Chassis Mount	
Report errors?	Size / Dimension	4.06" L x 1.22" W x 3.08" H (103.0mm x 31.0mm x 78.0mm)	
report crois.			Report errors?

SWG030-05 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SWG030-05 Payment Methods



















SWG030-05 Shipping Methods













If you have any question about SWG030-05, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com