

SWG150-12 Information

(40)

Part Number SWG150-12 Manufacturer Sanken

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 12V 150W

Package -


For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CINCI	50 12	C	4
SWG15	5U-1 <i>Z</i>	Specii	ications

Manufacturer Part Number SWG150-12 Manufacturer Sanken Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series SWG150 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86% Operating Temperature -10°C ~ 71°C (With Derating)	•			
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series SWG150 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86%	facturer Part Number			
AC DC Converters	facturer	Sanken		
Package - Series SWG150 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86%	ory	Power Supplies - External/Internal (Off-Board)		
Series SWG150 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86%				
Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86%	ige			
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86%	S			
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86%				
Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86%	per of Outputs			
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86%	ge - Input			
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86%	ge - Output 1			
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86%	ge - Output 2			
Current - Output (Max) 13A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86%	ge - Output 3			
Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86%	ge - Output 4			
Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86%	nt - Output (Max)			
Voltage - Isolation 3kV (3000V) Efficiency 86%	r (Watts)			
Efficiency 86%	cations			
·	ge - Isolation			
Operating Temperature $-10^{\circ}\text{C} \sim 71^{\circ}\text{C}$ (With Derating)	ency			
	ating Temperature	-10°C ~ 71°C (With Derating)		
Features DC Input Capable, Universal Input	res	DC Input Capable, Universal Input		
Mounting Type Chassis Mount	nting Type			
Size / Dimension 6.61" L x 1.34" W x 3.66" H (168.0mm x 34.0mm x 93.0mm)	Dimension	6.66" H (168.0mm x 34.0mm x 93.0mm)		
Report er		Report errors?		

SWG150-12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SWG150-12 Payment Methods





















SWG150-12 Shipping Methods













If you have any question about SWG150-12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com