

### SWI10-12-E-P6 Information



For Reference Only

Part Number SWI10-12-E-P6

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC WALL MOUNT ADAPTER 12V 10W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **SWI10-12-E-P6 Specifications**

Manufacturer Part Number         SWI10-12-E-P6           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         SWI10-E           Region Utilized         Europe           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         90 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         1A           Power (Watts)         10W           No Load Power Consumption         75mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level VI, CoC Tier 2           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         2.72" L x 1.13" W x 3.06" H (69.0mm x 28.8mm x 77.7mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         SWI10-E           Region Utilized         Europe           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         90 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         1A           Power (Watts)         10W           No Load Power Consumption         75mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level VI, CoC Tier 2           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         2.72" L x 1.13" W x 3.06" H (69.0mm x 28.8mm x 77.7mm)	Manufacturer Part Number	SWI10-12-E-P6
Package         -           Series         SWI10-E           Region Utilized         Europe           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         90 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         1A           Power (Watts)         10W           No Load Power Consumption         75mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level VI, CoC Tier 2           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         2.72" L x 1.13" W x 3.06" H (69.0mm x 28.8mm x 77.7mm)	Manufacturer	CUI Inc.
Package         -           Series         SWI10-E           Region Utilized         Europe           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         90 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         1A           Power (Watts)         10W           No Load Power Consumption         75mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level VI, CoC Tier 2           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         2.72" L x 1.13" W x 3.06" H (69.0mm x 28.8mm x 77.7mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesSWI10-ERegion UtilizedEuropeFormWall MountInput TypeFixed BladeVoltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)1APower (Watts)10WNo Load Power Consumption75mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension2.72" L x 1.13" W x 3.06" H (69.0mm x 28.8mm x 77.7mm)		AC DC Desktop, Wall Adapters
Region UtilizedEuropeFormWall MountInput TypeFixed BladeVoltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)1APower (Watts)10WNo Load Power Consumption75mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension2.72" L x 1.13" W x 3.06" H (69.0mm x 28.8mm x 77.7mm)	Package	-
Form Wall Mount Input Type Fixed Blade  Voltage - Input 90 ~ 264 VAC  Voltage - Output 12V  Current - Output (Max) 1A  Power (Watts) 10W  No Load Power Consumption 75mW (Max)  Polarization Positive Center Applications ITE (Commercial)  Efficiency Level VI, CoC Tier 2  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.72" L x 1.13" W x 3.06" H (69.0mm x 28.8mm x 77.7mm)	Series	SWI10-E
Input Type Fixed Blade  Voltage - Input 90 ~ 264 VAC  Voltage - Output 12V  Current - Output (Max) 1A  Power (Watts) 10W  No Load Power Consumption 75mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level VI, CoC Tier 2  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.72" L x 1.13" W x 3.06" H (69.0mm x 28.8mm x 77.7mm)	Region Utilized	Europe
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $12\text{V}$ Current - Output (Max) $1A$ Power (Watts) $10\text{W}$ No Load Power Consumption $75\text{mW}$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.5\text{mm}$ I.D. $x \leq 5.5\text{mm}$ O.D. $x \leq 9.5\text{mm}$ Size / Dimension $2.72$ " L $x \leq 1.13$ " W $x \leq 3.06$ " H (69.0mm $x \leq 28.8\text{mm}$ x 77.7mm)	Form	Wall Mount
Voltage - Output  Current - Output (Max)  1A  Power (Watts)  No Load Power Consumption  Polarization  Polarization  Applications  ITE (Commercial)  Efficiency  Level VI, CoC Tier 2  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  12V  12V  12V  12V  12V  14  16  10  10  10  10  10  10  10  10  10	Input Type	Fixed Blade
Current - Output (Max)  Power (Watts)  No Load Power Consumption  Positive Center  Applications  ITE (Commercial)  Efficiency  Current - Output (Max)  Power (Watts)  ITE (Commercial)  Level VI, CoC Tier 2  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  2.72" L x 1.13" W x 3.06" H (69.0mm x 28.8mm x 77.7mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts)  No Load Power Consumption  75mW (Max)  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Level VI, CoC Tier 2  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  2.72" L x 1.13" W x 3.06" H (69.0mm x 28.8mm x 77.7mm)	Voltage - Output	12V
No Load Power Consumption $75 \text{mW}$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.5 \text{mm}$ I.D. $x 5.5 \text{mm}$ O.D. $x 9.5 \text{mm}$ Size / Dimension $2.72$ " L $x 1.13$ " W $x 3.06$ " H (69.0mm $x 28.8 \text{mm}$ $x 77.7 \text{mm}$ )	Current - Output (Max)	1A
Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level VI, CoC Tier 2  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.72" L x 1.13" W x 3.06" H (69.0mm x 28.8mm x 77.7mm)	Power (Watts)	10W
Applications ITE (Commercial)  Efficiency Level VI, CoC Tier 2  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.72" L x 1.13" W x 3.06" H (69.0mm x 28.8mm x 77.7mm)	No Load Power Consumption	75mW (Max)
Efficiency Level VI, CoC Tier 2  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.72" L x 1.13" W x 3.06" H (69.0mm x 28.8mm x 77.7mm)	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $2.72^{\circ}\text{L x } 1.13^{\circ}\text{W x } 3.06^{\circ}\text{H } (69.0\text{mm x } 28.8\text{mm x } 77.7\text{mm})$	Applications	ITE (Commercial)
Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         2.72" L x 1.13" W x 3.06" H (69.0mm x 28.8mm x 77.7mm)	Efficiency	Level VI, CoC Tier 2
Size / Dimension 2.72" L x 1.13" W x 3.06" H (69.0mm x 28.8mm x 77.7mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	2.72" L x 1.13" W x 3.06" H (69.0mm x 28.8mm x 77.7mm)
•		Report errors?

#### **SWI10-12-E-P6 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### SWI10-12-E-P6 Payment Methods



















### **SWI10-12-E-P6 Shipping Methods**













If you have any question about SWI10-12-E-P6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com