

SWI24-12-N-SC Information

Part Number SWI24-12-N-SC

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

AC/DC WALL MOUNT ADAPTER 12V 24W **Description**

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SWI24-12-N-SC Specifications

Manufacturer Part NumberSW124-12-N-SCManufacturerCUI Inc.CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesSW124-SCRegion UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)2APower (Watts)24WNo Load Power Consumption100mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VI		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package Series SWI24-SC Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) Power (Watts) 24W No Load Power Consumption 100mW (Max) Polarization - Applications ITE (Commercial)	Manufacturer Part Number	SWI24-12-N-SC
Package - Series SWI24-SC Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2A Power (Watts) 24W No Load Power Consumption 100mW (Max) Polarization - Applications ITE (Commercial)	Manufacturer	CUI Inc.
Package-SeriesSW124-SCRegion UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)2APower (Watts)24WNo Load Power Consumption100mW (Max)Polarization-ApplicationsITE (Commercial)	Category	Power Supplies - External/Internal (Off-Board)
Series SW124-SC Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2A Power (Watts) 24W No Load Power Consumption 100mW (Max) Polarization - Applications ITE (Commercial)		AC DC Desktop, Wall Adapters
Region Utilized Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output Current - Output (Max) Power (Watts) No Load Power Consumption Polarization Applications North America North America North America Andread North America North America Andread Nouth America North America Andread Nouth Application Fixed Blade 24 VAC 24 VAC 12V 12V 12V 12V 100mW (Max) 100mW (Max) Folarization - Applications ITE (Commercial)	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2A Power (Watts) 24W No Load Power Consumption 100mW (Max) Polarization - Applications ITE (Commercial)	Series	SWI24-SC
Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2A Power (Watts) 24W No Load Power Consumption 100mW (Max) Polarization - Applications ITE (Commercial)	Region Utilized	North America
Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) Power (Watts) No Load Power Consumption 100mW (Max) Polarization Applications ITE (Commercial)	Form	Wall Mount
Voltage - Output Current - Output (Max) Power (Watts) 24W No Load Power Consumption 100mW (Max) Polarization - Applications ITE (Commercial)	Input Type	Fixed Blade
Current - Output (Max) Power (Watts) No Load Power Consumption Polarization Applications 2A 100mW (Max) - ITE (Commercial)	Voltage - Input	90 ~ 264 VAC
Power (Watts) No Load Power Consumption 100mW (Max) Polarization Applications ITE (Commercial)	Voltage - Output	12V
No Load Power Consumption 100mW (Max) Polarization - Applications ITE (Commercial)	Current - Output (Max)	2A
Polarization - Applications ITE (Commercial)	Power (Watts)	24W
Applications ITE (Commercial)	No Load Power Consumption	100mW (Max)
	Polarization	-
Efficiency I evel VI	Applications	ITE (Commercial)
Enterency Level vi	Efficiency	Level VI
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$	Operating Temperature	0°C ~ 40°C
Output Connector Screw Terminal	Output Connector	Screw Terminal
Size / Dimension 3.86" L x 1.93" W x 1.28" H (98.0mm x 49.0mm x 32.5mm)	Size / Dimension	3.86" L x 1.93" W x 1.28" H (98.0mm x 49.0mm x 32.5mm)
Report errors?		Report errors?

SWI24-12-N-SC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SWI24-12-N-SC Payment Methods



















SWI24-12-N-SC Shipping Methods













If you have any question about SWI24-12-N-SC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com