

#### SWI6-5-E-P5R Information



For Reference Only

Part Number SWI6-5-E-P5R Manufacturer CUI Inc.

**Category** Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC WALL MOUNT ADAPTER 5V 16W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **SWI6-5-E-P5R Specifications**

Manufacturer Part NumberSWI6-5-E-P5RManufacturerCUI Inc.CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesSWI6-ERegion UtilizedEuropeFormWall MountInput TypeFixed BladeVoltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)1.5APower (Watts)6WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°C		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters  Package Series SWI6-E Region Utilized Europe Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC  Voltage - Output 5V Current - Output (Max) Power (Watts) No Load Power Consumption Polarization Applications ITE (Commercial) Efficiency Power (Watts) Level VI	Manufacturer Part Number	SWI6-5-E-P5R
Package - Series SWI6-E Region Utilized Europe Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 1.5A Power (Watts) 6W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI	Manufacturer	CUI Inc.
Package - SWI6-E  Region Utilized Europe  Form Wall Mount  Input Type Fixed Blade  Voltage - Input 90 ~ 264 VAC  Voltage - Output 5V  Current - Output (Max) 1.5A  Power (Watts) 6W  No Load Power Consumption 100mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level VI	Category	Power Supplies - External/Internal (Off-Board)
SeriesSWI6-ERegion UtilizedEuropeFormWall MountInput TypeFixed BladeVoltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)1.5APower (Watts)6WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI		AC DC Desktop, Wall Adapters
Region Utilized Europe Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 1.5A Power (Watts) 6W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 1.5A Power (Watts) 6W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI	Series	SWI6-E
Input Type Fixed Blade  Voltage - Input 90 ~ 264 VAC  Voltage - Output 5V  Current - Output (Max) 1.5A  Power (Watts) 6W  No Load Power Consumption 100mW (Max)  Polarization Applications ITE (Commercial)  Efficiency Level VI	Region Utilized	Europe
Voltage - Input  90 ~ 264 VAC  Voltage - Output  5V  Current - Output (Max)  1.5A  Power (Watts)  6W  No Load Power Consumption  100mW (Max)  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Level VI	Form	Wall Mount
Voltage - Output (Max) 1.5A  Power (Watts) 6W  No Load Power Consumption 100mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level VI	Input Type	Fixed Blade
Current - Output (Max)  Power (Watts)  No Load Power Consumption  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Level VI	Voltage - Input	90 ~ 264 VAC
Power (Watts) 6W  No Load Power Consumption 100mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level VI	Voltage - Output	5V
No Load Power Consumption 100mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level VI	Current - Output (Max)	1.5A
Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level VI	Power (Watts)	6W
Applications ITE (Commercial) Efficiency Level VI	No Load Power Consumption	100mW (Max)
Efficiency Level VI	Polarization	Positive Center
·	Applications	ITE (Commercial)
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$	Efficiency	Level VI
	Operating Temperature	$0^{\circ}\text{C} \sim 40^{\circ}\text{C}$
Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm	Output Connector	Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm
Size / Dimension 2.05" L x 1.10" W x 2.36" H (52.0mm x 28.0mm x 60.0mm)	Size / Dimension	2.05" L x 1.10" W x 2.36" H (52.0mm x 28.0mm x 60.0mm)
Report errors?		Report errors?

#### **SWI6-5-E-P5R Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **SWI6-5-E-P5R Payment Methods**





















### **SWI6-5-E-P5R Shipping Methods**













If you have any question about SWI6-5-E-P5R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com