

SWS600L-5 Information



For Reference Only

Part Number SWS600L-5

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 5V 600W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SWS600L-5 Specifications

Manufacturer Part Number SWS600L-5 Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series SWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 120A Power (Watts) 600W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -20°C ~ 74°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series SWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 120A Power (Watts) 600W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -20°C ~ 74°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Manufacturer Part Number	SWS600L-5
Package - Series SWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 120A Power (Watts) 600W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -20°C ~ 74°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Manufacturer	TDK-Lambda Americas Inc.
Package - Series SWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 120A Power (Watts) 600W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -20°C ~ 74°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series SWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 120A Power (Watts) 600W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -20°C ~ 74°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)		AC DC Converters
TypeEnclosedNumber of Outputs1Voltage - Input85 ~ 265 VACVoltage - Output 15VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)120APower (Watts)600WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency75%Operating Temperature-20°C ~ 74°C (With Derating)FeaturesAdjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Package	-
Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 120A Power (Watts) 600W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -20°C ~ 74°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Series	SWS
Voltage - Input85 ~ 265 VACVoltage - Output 15VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)120APower (Watts)600WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency75%Operating Temperature-20°C ~ 74°C (With Derating)FeaturesAdjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Type	Enclosed
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 120A Power (Watts) 600W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -20°C ~ 74°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature -20°C ~ 74°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Voltage - Input	85 ~ 265 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -20°C ~ 74°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Voltage - Output 1	5V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -20°C ~ 74°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) 600W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -20°C ~ 74°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Voltage - Output 3	-
Power (Watts) 600W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -20°C ~ 74°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation $3kV (3000V)$ Efficiency 75% Operating Temperature $-20^{\circ}\text{C} \sim 74^{\circ}\text{C}$ (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount $5ize / Dimension \qquad 7.48" \text{ L x } 4.72" \text{ W x } 2.40" \text{ H } (190.0 \text{mm x } 120.0 \text{mm x } 61.0 \text{mm})$	Current - Output (Max)	120A
Voltage - Isolation $3kV (3000V)$ Efficiency 75% Operating Temperature $-20^{\circ}\text{C} \sim 74^{\circ}\text{C}$ (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension $7.48''$ L x $4.72''$ W x $2.40''$ H (190.0mm x 120.0mm x 61.0mm)	Power (Watts)	600W
Efficiency 75% Operating Temperature -20°C ~ 74°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Applications	ITE (Commercial)
Operating Temperature -20°C ~ 74°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Voltage - Isolation	3kV (3000V)
Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Efficiency	75%
Mounting Type Chassis Mount Size / Dimension 7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Operating Temperature	-20°C ~ 74°C (With Derating)
Size / Dimension 7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Features	Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)
		Report errors?

SWS600L-5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SWS600L-5 Payment Methods





















SWS600L-5 Shipping Methods













If you have any question about SWS600L-5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com