

SWT30-5FF Information

Part Number SWT30-5FF

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 5V +/-15V 30W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SWT30-5FF Specifications

Manufacturer Part Number SWT30-5FF Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series SWT Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 15V Voltage - Output 3 -15V Voltage - Output 4 - Current - Output (Max) 2A, 1A, 300mA Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 70% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series SWT Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 15V Voltage - Output 3 -15V Voltage - Output 4 - Current - Output (Max) 2A, 1A, 300mA Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 70% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)	Manufacturer Part Number	SWT30-5FF
Package - Series SWT Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 15V Voltage - Output 3 -15V Voltage - Output 4 - Current - Output (Max) 2A, 1A, 300mA Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 70% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)	Manufacturer	TDK-Lambda Americas Inc.
Package - Series SWT Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 15V Voltage - Output 3 -15V Voltage - Output 4 - Current - Output (Max) 2A, 1A, 300mA Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 70% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)	Category	Power Supplies - External/Internal (Off-Board)
Series SWT Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 15V Voltage - Output 3 -15V Voltage - Output 4 - Current - Output (Max) 2A, 1A, 300mA Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 70% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)		AC DC Converters
Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 15V Voltage - Output 3 -15V Voltage - Output 4 - Current - Output (Max) 2A, 1A, 300mA Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 70% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)	Package	-
Number of Outputs 3 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 15V Voltage - Output 3 -15V Voltage - Output 4 - Current - Output (Max) 2A, 1A, 300mA Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 70% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)	Series	SWT
Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 15V Voltage - Output 3 -15V Voltage - Output 4 - Current - Output (Max) 2A, 1A, 300mA Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 70% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)	Туре	Open Frame
Voltage - Output 1 5V Voltage - Output 2 15V Voltage - Output 3 -15V Voltage - Output 4 - Current - Output (Max) 2A, 1A, 300mA Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 70% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)	Number of Outputs	3
Voltage - Output 2 Voltage - Output 3 -15V Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature Features DC Input Capable, Universal Input Mounting Type Size / Dimension 15V -15V -15V -15V -15V -15V -15V -15	Voltage - Input	85 ~ 265 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature O°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Size / Dimension -15V -15V	Voltage - Output 1	5V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 70% Operating Temperature O°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension	Voltage - Output 2	15V
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 70% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 2A, 1A, 300mA 30W Applications ITE (Commercial) 3kV (3000V) Commercial) Applications 3kV (3000V) Town 10 Commercial) 10 Commercial) 10 Commercial) 11 Commercial) 12 Commercial) 13 Commercial) 14 Commercial) 15 Commercial) 16 Commercial) 17 Commercial) 18 Commercial) 18 Commercial) 19 Commercial) 10 Commercial) 10 Commercial) 10 Commercial) 10 Commercial) 10 Commercial) 11 Commercial) 12 Commercial) 13 Commercial) 14 Commercial) 15 Commercial) 16 Commercial) 17 Commercial) 18 Co	Voltage - Output 3	-15V
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 70% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)	Voltage - Output 4	-
ApplicationsITE (Commercial)Voltage - Isolation $3kV (3000V)$ Efficiency 70% Operating Temperature $0^{\circ}C \sim 50^{\circ}C$ FeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension 5.00° L x 3.00° W x 1.20° H (127.0 mm x 76.2 mm x 30.5 mm)	Current - Output (Max)	2A, 1A, 300mA
Voltage - Isolation 3kV (3000V) Efficiency 70% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)	Power (Watts)	30W
Efficiency 70% Operating Temperature $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension $5.00^{\circ}\text{L x } 3.00^{\circ}\text{W x } 1.20^{\circ}\text{H } (127.0\text{mm x } 76.2\text{mm x } 30.5\text{mm})$	Applications	ITE (Commercial)
Operating Temperature0°C ~ 50°CFeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)	Voltage - Isolation	3kV (3000V)
Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)	Efficiency	70%
Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)	Operating Temperature	0°C ~ 50°C
Size / Dimension 5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)	Features	DC Input Capable, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)
		Report errors?

SWT30-5FF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SWT30-5FF Payment Methods



















SWT30-5FF Shipping Methods













If you have any question about SWT30-5FF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com