

SWT65-522 Information

Part Number SWT65-522

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 5V +/-12V 65W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SWT65-522	Casaifias	4:
3 W 103-344	Specifica	llions

Manufacturer Part Number SWT65-522 Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series SWT Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) 6A, 2.5A, 500mA Power (Watts) 65W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 6.00" L x 3.50" W x 1.77" H (152.4mm x 88.9mm x 45.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series SWT Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) 6A, 2.5A, 500mA Power (Watts) 65W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 6.00" L x 3.50" W x 1.77" H (152.4mm x 88.9mm x 45.0mm)	Manufacturer Part Number	SWT65-522
Package - Series SWT Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) 6A, 2.5A, 500mA Power (Watts) 65W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 6.00" L x 3.50" W x 1.77" H (152.4mm x 88.9mm x 45.0mm)	Manufacturer	TDK-Lambda Americas Inc.
Package - Series SWT Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) 6A, 2.5A, 500mA Power (Watts) 65W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 6.00" L x 3.50" W x 1.77" H (152.4mm x 88.9mm x 45.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series SWT Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) 6A, 2.5A, 500mA Power (Watts) 65W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 6.00" L x 3.50" W x 1.77" H (152.4mm x 88.9mm x 45.0mm)		AC DC Converters
Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) 6A, 2.5A, 500mA Power (Watts) 65W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 6.00" L x 3.50" W x 1.77" H (152.4mm x 88.9mm x 45.0mm)	Package	-
Number of Outputs 3 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) 6A, 2.5A, 500mA Power (Watts) 65W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 6.00" L x 3.50" W x 1.77" H (152.4mm x 88.9mm x 45.0mm)	Series	SWT
Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) 6A, 2.5A, 500mA Power (Watts) 65W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 6.00" L x 3.50" W x 1.77" H (152.4mm x 88.9mm x 45.0mm)	Туре	Open Frame
Voltage - Output 1 Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature O°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Size / Dimension 5V 12V Chassis Mount 6A, 2.5A, 500mA 6A, 2.5A, 500mA 65W ITE (Commercial) 3kV (3000V) 72% Operating Temperature O°C ~ 50°C Features DC Input Capable, Universal Input Chassis Mount Size / Dimension 6.00" L x 3.50" W x 1.77" H (152.4mm x 88.9mm x 45.0mm)	Number of Outputs	3
Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) 6A, 2.5A, 500mA Power (Watts) 65W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 6.00" L x 3.50" W x 1.77" H (152.4mm x 88.9mm x 45.0mm)	Voltage - Input	85 ~ 265 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) 6A, 2.5A, 500mA Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature O°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension -12V -1	Voltage - Output 1	5V
Voltage - Output 4 Current - Output (Max) 6A, 2.5A, 500mA Power (Watts) 65W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 6.00" L x 3.50" W x 1.77" H (152.4mm x 88.9mm x 45.0mm)	Voltage - Output 2	12V
Current - Output (Max) 6A, 2.5A, 500mA Power (Watts) 65W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 6.00" L x 3.50" W x 1.77" H (152.4mm x 88.9mm x 45.0mm)	Voltage - Output 3	-12V
Power (Watts) 65W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 6.00" L x 3.50" W x 1.77" H (152.4mm x 88.9mm x 45.0mm)	Voltage - Output 4	-
ApplicationsITE (Commercial)Voltage - Isolation $3kV (3000V)$ Efficiency 72% Operating Temperature $0^{\circ}C \sim 50^{\circ}C$ FeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension 6.00 " L x 3.50 " W x 1.77 " H (152.4 mm x 88.9 mm x 45.0 mm)	Current - Output (Max)	6A, 2.5A, 500mA
Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 6.00" L x 3.50" W x 1.77" H (152.4mm x 88.9mm x 45.0mm)	Power (Watts)	65W
Efficiency 72% Operating Temperature $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ FeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension $6.00^{\circ}\text{L x } 3.50^{\circ}\text{W x } 1.77^{\circ}\text{H } (152.4\text{mm x } 88.9\text{mm x } 45.0\text{mm})$	Applications	ITE (Commercial)
Operating Temperature0°C ~ 50°CFeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension6.00" L x 3.50" W x 1.77" H (152.4mm x 88.9mm x 45.0mm)	Voltage - Isolation	3kV (3000V)
Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 6.00" L x 3.50" W x 1.77" H (152.4mm x 88.9mm x 45.0mm)	Efficiency	72%
Mounting Type Chassis Mount Size / Dimension 6.00" L x 3.50" W x 1.77" H (152.4mm x 88.9mm x 45.0mm)	Operating Temperature	0°C ~ 50°C
Size / Dimension 6.00" L x 3.50" W x 1.77" H (152.4mm x 88.9mm x 45.0mm)	Features	DC Input Capable, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	6.00" L x 3.50" W x 1.77" H (152.4mm x 88.9mm x 45.0mm)
		Report errors?

SWT65-522 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SWT65-522 Payment Methods



















SWT65-522 Shipping Methods













If you have any question about SWT65-522, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com