



SZR-LY4-N1-AC220V Information



For Reference Only

Part Number SZR-LY4-N1-AC220V

Manufacturer Honeywell Sensing and Productivity Solutions

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 4PDT 10A 220V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SZR-LY4-N1-AC220V Specifications

Manufacturer Part Number SZR-LY4-N1-AC220V Manufacturer Honeywell Sensing and Productivity Solutions Category Relays Power Relays, Over 2 Amps Package - Series SZR-LY Relay Type General Purpose Coil Type Non Latching Coil Current 13.8mA Coil Voltage 220VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesSZR-LYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current13.8mACoil Voltage220VACContact Form4PDT (4 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)176 VACTurn Off Voltage (Min)66 VACOperate Time25msRelease Time25msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	SZR-LY4-N1-AC220V
Package-SeriesSZR-LYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current13.8mACoil Voltage220VACContact Form4PDT (4 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)176 VACTurn Off Voltage (Min)66 VACOperate Time25msRelease Time25msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Manufacturer	Honeywell Sensing and Productivity Solutions
Package - Series SZR-LY Relay Type General Purpose Coil Type Non Latching Coil Current 13.8mA Coil Voltage 220VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Category	Relays
SeriesSZR-LYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current13.8mACoil Voltage220VACContact Form4PDT (4 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)176 VACTurn Off Voltage (Min)66 VACOperate Time25msRelease Time25msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current13.8mACoil Voltage220VACContact Form4PDT (4 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)176 VACTurn Off Voltage (Min)66 VACOperate Time25msRelease Time25msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Package	-
Coil TypeNon LatchingCoil Current13.8mACoil Voltage220VACContact Form4PDT (4 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)176 VACTurn Off Voltage (Min)66 VACOperate Time25msRelease Time25msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Series	SZR-LY
Coil Current Coil Voltage 220VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style	Relay Type	General Purpose
Coil Voltage 220VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 25ms Release Time 25ms Release Time LED Indicator Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form 4PDT (4 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 25ms Release Time 25ms Release Time LED Indicator Mounting Type Socketable Termination Style Plug In	Coil Current	13.8mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style	Coil Voltage	220VAC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Contact Rating (Current)	10A
Turn Off Voltage (Min) 66 VAC Operate Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	176 VAC
Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	66 VAC
Features LED Indicator Mounting Type Socketable Termination Style Plug In	Operate Time	25ms
Mounting Type Socketable Termination Style Plug In	Release Time	25ms
Termination Style Plug In	Features	LED Indicator
•	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

SZR-LY4-N1-AC220V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SZR-LY4-N1-AC220V Payment Methods



















SZR-LY4-N1-AC220V Shipping Methods













If you have any question about SZR-LY4-N1-AC220V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com