



### SZR-LY4-N1-AC220V Information



For Reference Only

Part Number SZR-LY4-N1-AC220V

Manufacturer Honeywell Sensing and Productivity Solutions

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE 4PDT 10A 220V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## SZR-LY4-N1-AC220V Specifications

Manufacturer Part Number       SZR-LY4-N1-AC220V         Manufacturer       Honeywell Sensing and Productivity Solutions         Category       Relays         Power Relays, Over 2 Amps         Package       -         Series       SZR-LY         Relay Type       General Purpose         Coil Type       Non Latching         Coil Current       13.8mA         Coil Voltage       220VAC         Contact Form       4PDT (4 Form C)         Contact Rating (Current)       10A         Switching Voltage       250VAC, 125VDC - Max         Turn On Voltage (Max)       176 VAC         Turn Off Voltage (Min)       66 VAC         Operate Time       25ms         Release Time       25ms         Features       LED Indicator         Mounting Type       Socketable         Termination Style       Plug In		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesSZR-LYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current13.8mACoil Voltage220VACContact Form4PDT (4 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)176 VACTurn Off Voltage (Min)66 VACOperate Time25msRelease Time25msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	SZR-LY4-N1-AC220V
Package         -           Series         SZR-LY           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         13.8mA           Coil Voltage         220VAC           Contact Form         4PDT (4 Form C)           Contact Rating (Current)         10A           Switching Voltage         250VAC, 125VDC - Max           Turn On Voltage (Max)         176 VAC           Turn Off Voltage (Min)         66 VAC           Operate Time         25ms           Release Time         25ms           Features         LED Indicator           Mounting Type         Socketable           Termination Style         Plug In	Manufacturer	Honeywell Sensing and Productivity Solutions
Package         -           Series         SZR-LY           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         13.8mA           Coil Voltage         220VAC           Contact Form         4PDT (4 Form C)           Contact Rating (Current)         10A           Switching Voltage         250VAC, 125VDC - Max           Turn On Voltage (Max)         176 VAC           Turn Off Voltage (Min)         66 VAC           Operate Time         25ms           Release Time         25ms           Features         LED Indicator           Mounting Type         Socketable           Termination Style         Plug In	Category	Relays
SeriesSZR-LYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current13.8mACoil Voltage220VACContact Form4PDT (4 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)176 VACTurn Off Voltage (Min)66 VACOperate Time25msRelease Time25msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose  Coil Type Non Latching  Coil Current 13.8mA  Coil Voltage 220VAC  Contact Form 4PDT (4 Form C)  Contact Rating (Current) 10A  Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 176 VAC  Turn Off Voltage (Min) 66 VAC  Operate Time 25ms  Release Time 25ms  Release Time 25ms  Features LED Indicator  Mounting Type Socketable  Termination Style Plug In	Package	-
Coil Type Non Latching Coil Current 13.8mA Coil Voltage 220VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Series	SZR-LY
Coil Current Coil Voltage 220VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style	Relay Type	General Purpose
Coil Voltage 220VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 25ms Release Time 25ms Release Time LED Indicator Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form 4PDT (4 Form C)  Contact Rating (Current) 10A  Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 176 VAC  Turn Off Voltage (Min) 66 VAC  Operate Time 25ms  Release Time 25ms  Release Time LED Indicator  Mounting Type Socketable  Termination Style Plug In	Coil Current	13.8mA
Contact Rating (Current)  Switching Voltage  250VAC, 125VDC - Max  Turn On Voltage (Max)  176 VAC  Turn Off Voltage (Min)  66 VAC  Operate Time  25ms  Release Time  25ms  Features  LED Indicator  Mounting Type  Socketable  Termination Style	Coil Voltage	220VAC
Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 176 VAC  Turn Off Voltage (Min) 66 VAC  Operate Time 25ms  Release Time 25ms  Features LED Indicator  Mounting Type Socketable  Termination Style Plug In	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max)  176 VAC  Turn Off Voltage (Min)  66 VAC  Operate Time  25ms  Release Time  25ms  LED Indicator  Mounting Type  Socketable  Termination Style  Plug In	Contact Rating (Current)	10A
Turn Off Voltage (Min) 66 VAC Operate Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time25msRelease Time25msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Turn On Voltage (Max)	176 VAC
Release Time 25ms  Features LED Indicator  Mounting Type Socketable  Termination Style Plug In	Turn Off Voltage (Min)	66 VAC
Features LED Indicator  Mounting Type Socketable  Termination Style Plug In	Operate Time	25ms
Mounting Type Socketable Termination Style Plug In	Release Time	25ms
Termination Style Plug In	Features	LED Indicator
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

#### SZR-LY4-N1-AC220V Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## SZR-LY4-N1-AC220V Payment Methods



















## SZR-LY4-N1-AC220V Shipping Methods













If you have any question about SZR-LY4-N1-AC220V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com