



SZR-MY2-1-AC220V Information

Heisener.com

Part Number SZR-MY2-1-AC220V

Manufacturer Honeywell Sensing and Productivity Solutions

Category

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 5A 220V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SZR-MY2-1-AC220V Specifications

Manufacturer SZR-MY2-1-AC220V Manufacturer Honeywell Sensing and Productivity Solutions Category Relays Power Relays, Over 2 Amps Package - Series SZR-MY Relay Type General Purpose Coil Type Non Latching Coil Current 5.3mA Coil Voltage 220VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 165 VAC Turn Off Voltage (Min) 66 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesSZR-MYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current5.3mACoil Voltage220VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)165 VACTurn Off Voltage (Min)66 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	SZR-MY2-1-AC220V
Package - Series SZR-MY Relay Type General Purpose Coil Type Non Latching Coil Current 5.3mA Coil Voltage 220VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 165 VAC Turn Off Voltage (Min) 66 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Manufacturer	Honeywell Sensing and Productivity Solutions
Package - Series SZR-MY Relay Type General Purpose Coil Type Non Latching Coil Current 5.3mA Coil Voltage 220VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 165 VAC Turn Off Voltage (Min) 66 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Category	Relays
SeriesSZR-MYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current5.3mACoil Voltage220VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)165 VACTurn Off Voltage (Min)66 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 5.3mA Coil Voltage 220VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 165 VAC Turn Off Voltage (Min) 66 VAC Operate Time 20ms Release Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current5.3mACoil Voltage220VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)165 VACTurn Off Voltage (Min)66 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In	Series	SZR-MY
Coil Current Coil Voltage 220VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 165 VAC Turn Off Voltage (Min) 66 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style 5.3mA 5.3mA 5.3mA 5.3mA 5.3mA 6.6vAC 6.0vAC	Relay Type	General Purpose
Coil Voltage 220VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 165 VAC Turn Off Voltage (Min) 66 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 165 VAC Turn Off Voltage (Min) 66 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style	Coil Current	5.3mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 165 VAC Turn Off Voltage (Min) 66 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style	Coil Voltage	220VAC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 165 VAC Turn Off Voltage (Min) 66 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 165 VAC Turn Off Voltage (Min) 66 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style 165 VAC 20ms Plug In	Contact Rating (Current)	5A
Turn Off Voltage (Min) 66 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	165 VAC
Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	66 VAC
Features - Mounting Type Socketable Termination Style Plug In	Operate Time	20ms
Mounting Type Socketable Termination Style Plug In	Release Time	20ms
Termination Style Plug In	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
report chois.		Report errors?

SZR-MY2-1-AC220V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SZR-MY2-1-AC220V Payment Methods



















SZR-MY2-1-AC220V Shipping Methods













If you have any question about SZR-MY2-1-AC220V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com