



### SZR-MY2-1-AC220V Information

Heisener.com

Part Number SZR-MY2-1-AC220V

Manufacturer Honeywell Sensing and Productivity Solutions

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE DPDT 5A 220V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# SZR-MY2-1-AC220V Specifications

Manufacturer       SZR-MY2-1-AC220V         Manufacturer       Honeywell Sensing and Productivity Solutions         Category       Relays         Power Relays, Over 2 Amps         Package       -         Series       SZR-MY         Relay Type       General Purpose         Coil Type       Non Latching         Coil Current       5.3mA         Coil Voltage       220VAC         Contact Form       DPDT (2 Form C)         Contact Rating (Current)       5A         Switching Voltage       250VAC, 125VDC - Max         Turn On Voltage (Max)       165 VAC         Turn Off Voltage (Min)       66 VAC         Operate Time       20ms         Release Time       20ms         Features       -         Mounting Type       Socketable         Termination Style       Plug In		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesSZR-MYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current5.3mACoil Voltage220VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)165 VACTurn Off Voltage (Min)66 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	SZR-MY2-1-AC220V
Package - Series SZR-MY Relay Type General Purpose Coil Type Non Latching Coil Current 5.3mA Coil Voltage 220VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 165 VAC Turn Off Voltage (Min) 66 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Manufacturer	Honeywell Sensing and Productivity Solutions
Package         -           Series         SZR-MY           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         5.3mA           Coil Voltage         220VAC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         5A           Switching Voltage         250VAC, 125VDC - Max           Turn On Voltage (Max)         165 VAC           Turn Off Voltage (Min)         66 VAC           Operate Time         20ms           Release Time         20ms           Features         -           Mounting Type         Socketable           Termination Style         Plug In	Category	Relays
SeriesSZR-MYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current5.3mACoil Voltage220VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)165 VACTurn Off Voltage (Min)66 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose  Coil Type Non Latching  Coil Current 5.3mA  Coil Voltage 220VAC  Contact Form DPDT (2 Form C)  Contact Rating (Current) 5A  Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 165 VAC  Turn Off Voltage (Min) 66 VAC  Operate Time 20ms  Release Time 20ms  Release Time 20ms  Features -  Mounting Type Socketable  Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current5.3mACoil Voltage220VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)165 VACTurn Off Voltage (Min)66 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In	Series	SZR-MY
Coil Current Coil Voltage 220VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 165 VAC Turn Off Voltage (Min) 66 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style  5.3mA 5.3mA 5.3mA 5.3mA 5.3mA 6.6vAC 6.0vAC	Relay Type	General Purpose
Coil Voltage 220VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 165 VAC Turn Off Voltage (Min) 66 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  250VAC, 125VDC - Max  Turn On Voltage (Max)  165 VAC  Turn Off Voltage (Min)  66 VAC  Operate Time  20ms  Release Time  20ms  Features  -  Mounting Type  Socketable  Termination Style	Coil Current	5.3mA
Contact Rating (Current)  Switching Voltage  250VAC, 125VDC - Max  Turn On Voltage (Max)  165 VAC  Turn Off Voltage (Min)  66 VAC  Operate Time  20ms  Release Time  20ms  Features  -  Mounting Type  Socketable  Termination Style	Coil Voltage	220VAC
Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 165 VAC  Turn Off Voltage (Min) 66 VAC  Operate Time 20ms  Release Time 20ms  Features -  Mounting Type Socketable  Termination Style Plug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  165 VAC  Turn Off Voltage (Min)  66 VAC  Operate Time  20ms  Release Time  20ms  Features  -  Mounting Type  Socketable  Termination Style  165 VAC  20ms  Plug In	Contact Rating (Current)	5A
Turn Off Voltage (Min) 66 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	165 VAC
Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	66 VAC
Features - Mounting Type Socketable Termination Style Plug In	Operate Time	20ms
Mounting Type Socketable Termination Style Plug In	Release Time	20ms
Termination Style Plug In	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
report chois.		Report errors?

#### SZR-MY2-1-AC220V Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### SZR-MY2-1-AC220V Payment Methods



















## SZR-MY2-1-AC220V Shipping Methods













If you have any question about SZR-MY2-1-AC220V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com