

Heisener.com

SZR-MY2-D1-DC24V

SZR-MY2-D1-DC24V Information

Part Number SZR-MY2-D1-DC24V

Manufacturer Honeywell Sensing and Productivity Solutions

Category

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 5A 24V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SZR-MY2-D1-DC24V Specifications

Manufacturer Part NumberSZR-MY2-D1-DC24VManufacturerHoneywell Sensing and Productivity SolutionsCategoryRelaysPackage-SeriesSZR-MYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36.9mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time20msRelease Time20msFeaturesDiodeMounting TypeSocketableTermination StylePlug In		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesSZR-MYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36.9mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time20msRelease Time20msFeaturesDiodeMounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	SZR-MY2-D1-DC24V
Package - Series SZR-MY Relay Type General Purpose Coil Type Non Latching Coil Current 36.9mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms Release Time 20ms Features Diode Mounting Type Socketable Termination Style Plug In	Manufacturer	Honeywell Sensing and Productivity Solutions
Package-SeriesSZR-MYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36.9mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time20msRelease Time20msFeaturesDiodeMounting TypeSocketableTermination StylePlug In	Category	Relays
SeriesSZR-MYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36.9mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time20msRelease Time20msFeaturesDiodeMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 36.9mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms Release Time 20ms Features Diode Mounting Type Socketable Termination Style Plug In	Package	-
Coil Type Non Latching Coil Current 36.9mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms Release Time 20ms Features Diode Mounting Type Socketable Termination Style Plug In	Series	SZR-MY
Coil Current36.9mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time20msRelease Time20msFeaturesDiodeMounting TypeSocketableTermination StylePlug In	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms Release Time 20ms Features Diode Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms Release Time 20ms Features Diode Mounting Type Socketable Termination Style Plug In	Coil Current	36.9mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms Release Time 20ms Features Diode Mounting Type Socketable Termination Style	Coil Voltage	24VDC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms Release Time 20ms Features Diode Mounting Type Socketable Termination Style Plug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms Release Time 20ms Features Diode Mounting Type Socketable Termination Style 18 VDC 2.4 VDC 20ms Plug In	Contact Rating (Current)	5A
Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms Release Time 20ms Features Diode Mounting Type Socketable Termination Style Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time 20ms Release Time 20ms Features Diode Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	18 VDC
Release Time 20ms Features Diode Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	2.4 VDC
Features Diode Mounting Type Socketable Termination Style Plug In	Operate Time	20ms
Mounting Type Socketable Termination Style Plug In	Release Time	20ms
Termination Style Plug In	Features	Diode
	Mounting Type	Socketable
Doport orrors?	Termination Style	Plug In
Report errors?		Report errors?

SZR-MY2-D1-DC24V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SZR-MY2-D1-DC24V Payment Methods



















SZR-MY2-D1-DC24V Shipping Methods













If you have any question about SZR-MY2-D1-DC24V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com