

T 3361 018 Information

www.ho/senencom

For Reference Only

Part Number T 3361 018

Manufacturer Amphenol Sine Systems Corp
Category Connectors, Interconnects
Circular Connectors

Description CONN PLUG 5POS INLINE SKT

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









T 3361 018 Specifications

Manufacturer Part Number T 3361 018 Manufacturer Amphenol Sine Systems Corp Category Connectors, Interconnects Package - Series C 091 A Connector Type Plug, Female Sockets Number of Positions 5 Shell Size - Insert DIN (240 Degree) Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP40 Shell Material, Finish Die Cast, Nickel Plated Contact Finish Gold Features Shielded, Strain Relief Voltage - Rated 300V Current Rating 5A		
Category Connectors, Interconnects Circular Connectors Package - Series C 091 A Connector Type Plug, Female Sockets Number of Positions Shell Size - Insert DIN (240 Degree) Shell Size, MIL Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection Ip40 Shell Material, Finish Die Cast, Nickel Plated Contact Finish Gold Features Shielded, Strain Relief Voltage - Rated Current Rating Solder Cast Shielded, Strain Relief Solder Current Rating Solder Current Rating Solder	Manufacturer Part Number	T 3361 018
Circular Connectors Package - Series C 091 A Connector Type Plug, Female Sockets Number of Positions 5 Shell Size - Insert DIN (240 Degree) Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP40 Shell Material, Finish Die Cast, Nickel Plated Contact Finish Gold Features Shielded, Strain Relief Voltage - Rated Current Rating 5 A	Manufacturer	Amphenol Sine Systems Corp
Package - Connector Type Plug, Female Sockets Number of Positions 5 Shell Size - Insert DIN (240 Degree) Shell Size, MIL - Connector Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP40 Shell Material, Finish Die Cast, Nickel Plated Contact Finish Gold Features Shielded, Strain Relief Voltage - Rated 300V Current Rating 5A	Category	Connectors, Interconnects
SeriesC 091 AConnector TypePlug, Female SocketsNumber of Positions5Shell Size - InsertDIN (240 Degree)Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP40Shell Material, FinishDie Cast, Nickel PlatedContact FinishGoldFeaturesShielded, Strain ReliefVoltage - Rated300VCurrent Rating5A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions5Shell Size - InsertDIN (240 Degree)Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP40Shell Material, FinishDie Cast, Nickel PlatedContact FinishGoldFeaturesShielded, Strain ReliefVoltage - Rated300VCurrent Rating5A	Package	-
Number of Positions Shell Size - Insert DIN (240 Degree) Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP40 Shell Material, Finish Die Cast, Nickel Plated Contact Finish Gold Features Shielded, Strain Relief Voltage - Rated Current Rating 5A	Series	C 091 A
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Fastening Type Threaded Orientation Keyed Ingress Protection Shell Material, Finish Die Cast, Nickel Plated Contact Finish Gold Features Shielded, Strain Relief Voltage - Rated Ourent Rating 5A	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP40 Shell Material, Finish Die Cast, Nickel Plated Contact Finish Gold Features Shielded, Strain Relief Voltage - Rated Outrent Rating Shell Material Shell Material Shell Material Shell Material Shielded Shielded Shielded Strain Relief	Number of Positions	5
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP40Shell Material, FinishDie Cast, Nickel PlatedContact FinishGoldFeaturesShielded, Strain ReliefVoltage - Rated300VCurrent Rating5A	Shell Size - Insert	DIN (240 Degree)
Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP40 Shell Material, Finish Die Cast, Nickel Plated Contact Finish Gold Features Shielded, Strain Relief Voltage - Rated 300V Current Rating 5A	Shell Size, MIL	-
Fastening Type Orientation Keyed Ingress Protection IP40 Shell Material, Finish Die Cast, Nickel Plated Contact Finish Gold Features Shielded, Strain Relief Voltage - Rated Ourrent Rating Threaded Seyed Strain Relief Total Strain Relief Shielded, Strain Relief Shielded, Strain Relief	Mounting Type	Free Hanging (In-Line)
Orientation Keyed Ingress Protection IP40 Shell Material, Finish Die Cast, Nickel Plated Contact Finish Gold Features Shielded, Strain Relief Voltage - Rated 300V Current Rating 5A	Termination	Solder Cup
Ingress Protection IP40 Shell Material, Finish Die Cast, Nickel Plated Contact Finish Gold Features Shielded, Strain Relief Voltage - Rated 300V Current Rating 5A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Gold Features Shielded, Strain Relief Voltage - Rated Current Rating Die Cast, Nickel Plated Gold Shielded, Strain Relief 300V 5A	Orientation	Keyed
Contact Finish Gold Features Shielded, Strain Relief Voltage - Rated 300V Current Rating 5A	Ingress Protection	IP40
Features Shielded, Strain Relief Voltage - Rated 300V Current Rating 5A	Shell Material, Finish	Die Cast, Nickel Plated
Voltage - Rated 300V Current Rating 5A	Contact Finish	Gold
Current Rating 5A	Features	Shielded, Strain Relief
	Voltage - Rated	300V
D	Current Rating	5A
Report errors?		Report errors?

T 3361 018 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

T 3361 018 Payment Methods


































If you have any question about T 3361 018, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com