

## T540B107M003BH8710

#### T540B107M003BH8710 Information

Heisener.com	Part Number Manufacturer Category Description Package	T540B107M003BH8710 KEMET Capacitors Tantalum - Polymer Capacitors CAP TANT POLY 100UF 3V 1411 1411 (3528 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

#### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### T540B107M003BH8710 Specifications

Manufacturer Part Number T540B107M003BH8710   Manufacturer KEMET   Category Capacitors   Tantalum - Polymer Capacitors Tantalum - Polymer Capacitors   Package 1411 (3528 Metric)   Series KO-CAP? T540   Capacitance 100µF   Tolerance ±20%   Voltage - Rated 3V   Sype Molded   ESR (Equivalent Series Resistance) 80 mOhm @ 100kHz   Operating Temperature 55°C ~ 125°C   Lifetime @ Temp. 2000 Hrs @ 125°C   Mounting Type Surface Mount   Package / Case 1411 (3528 Metric)   Size / Dimension 0.038" (2.10mm)   Liedaf Spacing 0.038" (2.10mm)   Lead Spacing -   Features COTS (High Reliability)		
CategoryCapacitorsCategoryTantalum - Polymer CapacitorsPackage1411 (3528 Metric)PackageKO-CAP? T540Capacitance100µFTolerance±20%Voltage - Rated3VTypeMoldedESR (Equivalent Series Resistance)80 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case1411 (3528 Metric)Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.083" (2.10mm)Lead Spacing-FaturesCOTS (High Reliability)	Manufacturer Part Number	T540B107M003BH8710
Tantalum - Polymer CapacitorsPackage1411 (3528 Metric)SeriesKO-CAP? T540Capacitance100µFTolerance±20%Voltage - Rated3VTypeMoldedESR (Equivalent Series Resistance)80 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountSize / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max).083" (2.10mm)Lead Spacing-Manufacturer Size CodeBFeaturesCOTS (High Reliability)	Manufacturer	KEMET
Package1411 (3528 Metric)SeriesKO-CAP? T540Capacitance100μFTolerance±20%Voltage - Rated3VTypeMoldedESR (Equivalent Series Resistance)80 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case1411 (3528 Metric)Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.083" (2.10mm)Lead Spacing-FeaturesBFeaturesCOTS (High Reliability)	Category	Capacitors
Series KO-CAP? T540   Capacitance 100µF   Tolerance ±20%   Voltage - Rated 3V   Type Molded   ESR (Equivalent Series Resistance) 80 mOhm @ 100kHz   Operating Temperature -55°C ~ 125°C   Lifetime @ Temp. 2000 Hrs @ 125°C   Mounting Type Surface Mount   Package / Case 1411 (3528 Metric)   Size / Dimension 0.138" L x 0.110" W (3.50mm x 2.80mm)   Height - Seated (Max) 0.083" (2.10mm)   Lead Spacing -   Fatures B   Features COTS (High Reliability)		Tantalum - Polymer Capacitors
Capacitance 100μF   Tolerance ±20%   Voltage - Rated 3V   Type Molded   ESR (Equivalent Series Resistance) 80 mOhm @ 100kHz   Operating Temperature -55°C ~ 125°C   Lifetime @ Temp. 2000 Hrs @ 125°C   Mounting Type Surface Mount   Package / Case 1411 (3528 Metric)   Size / Dimension 0.083" (2.10mm)   Height - Seated (Max) 0.083" (2.10mm)   Lead Spacing -   Features COTS (High Reliability)	Package	1411 (3528 Metric)
Tolerance±20%Tolerance±20%Voltage - Rated3VTypeMoldedESR (Equivalent Series Resistance)80 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case1411 (3528 Metric)Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.083" (2.10mm)Lead Spacing-FeaturesBFeaturesCOTS (High Reliability)	Series	KO-CAP? T540
Voltage - Rated3VYopeMoldedESR (Equivalent Series Resistance)80 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case1411 (3528 Metric)Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)-Lead Spacing-FeaturesBFeaturesCOTS (High Reliability)	Capacitance	100µF
Type Molded   ESR (Equivalent Series Resistance) 80 mOhm @ 100kHz   Operating Temperature -55°C ~ 125°C   Lifetime @ Temp. 2000 Hrs @ 125°C   Mounting Type Surface Mount   Package / Case 1411 (3528 Metric)   Size / Dimension 0.138" L x 0.110" W (3.50mm x 2.80mm)   Height - Seated (Max) 0.083" (2.10mm)   Lead Spacing -   Manufacturer Size Code B   Features COTS (High Reliability)	Tolerance	±20%
A80 mOhm @ 100kHzESR (Equivalent Series Resistance)80 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case1411 (3528 Metric)Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.083" (2.10mm)Lead Spacing-Manufacturer Size CodeBFeaturesCOTS (High Reliability)	Voltage - Rated	3V
Operating Temperature -55°C ~ 125°C   Lifetime @ Temp. 2000 Hrs @ 125°C   Mounting Type Surface Mount   Package / Case 1411 (3528 Metric)   Size / Dimension 0.138" L x 0.110" W (3.50mm x 2.80mm)   Height - Seated (Max) 0.083" (2.10mm)   Lead Spacing -   Manufacturer Size Code B   Features COTS (High Reliability)	Туре	Molded
Lifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case1411 (3528 Metric)Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.083" (2.10mm)Lead Spacing-Manufacturer Size CodeBFeaturesCOTS (High Reliability)	ESR (Equivalent Series Resistance)	80 mOhm @ 100kHz
And the second	Operating Temperature	-55°C ~ 125°C
Package / Case1411 (3528 Metric)Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.083" (2.10mm)Lead Spacing-Manufacturer Size CodeBFeaturesCOTS (High Reliability)	Lifetime @ Temp.	2000 Hrs @ 125°C
Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.083" (2.10mm)Lead Spacing-Manufacturer Size CodeBFeaturesCOTS (High Reliability)	Mounting Type	Surface Mount
Height - Seated (Max)0.083" (2.10mm)Lead Spacing-Manufacturer Size CodeBFeaturesCOTS (High Reliability)	Package / Case	1411 (3528 Metric)
Lead Spacing-Manufacturer Size CodeBFeaturesCOTS (High Reliability)	Size / Dimension	0.138" L x 0.110" W (3.50mm x 2.80mm)
Manufacturer Size CodeBFeaturesCOTS (High Reliability)	Height - Seated (Max)	0.083" (2.10mm)
Features COTS (High Reliability)	Lead Spacing	-
	Manufacturer Size Code	В
Report errors?	Features	COTS (High Reliability)
		Report errors?

#### T540B107M003BH8710 Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

# T540B107M003BH8710 Payment Methods





If you have any question about T540B107M003BH8710, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com