

Heisener.com

# T540B226M010AH86107280

### T540B226M010AH86107280 Information

Part Number T540B226M010AH86107280

Manufacturer KEMET Category Capacitors

**Tantalum - Polymer Capacitors** 

**Description** CAP TANT POLY 22UF 10V 1411

Package 1411 (3528 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **T540B226M010AH86107280 Specifications**

Manufacturer Part Number         T540B226M010AH86107280           Manufacturer         KEMET           Category         Capacitors           Package         1411 (3528 Metric)           Series         KO-CAP? T540           Capacitance         22µF           Tolerance         ±20%           Voltage - Rated         10V           Type         Molded           ESR (Equivalent Series Resistance)         80 mOhm @ 100kHz           Operating Temperature         -55°C ~ 125°C           Lifetime @ Temp.         2000 Hrs @ 125°C           Mounting Type         Surface Mount           Package / Case         1411 (3528 Metric)           Size / Dimension         0.138" L x 0.110" W (3.50mm x 2.80mm)           Height - Seated (Max)         0.083" (2.10mm)           Lead Spacing         -		
Category         Capacitors           Package         1411 (3528 Metric)           Series         KO-CAP? T540           Capacitance         22µF           Tolerance         ±20%           Voltage - Rated         10V           Type         Molded           ESR (Equivalent Series Resistance)         80 mOhm @ 100kHz           Operating Temperature         -55°C ~ 125°C           Lifetime @ Temp.         2000 Hrs @ 125°C           Mounting Type         Surface Mount           Package / Case         1411 (3528 Metric)           Size / Dimension         0.138" L x 0.110" W (3.50mm x 2.80mm)           Height - Seated (Max)         0.083" (2.10mm)           Lead Spacing         -	Manufacturer Part Number	T540B226M010AH86107280
Tantalum - Polymer CapacitorsPackage1411 (3528 Metric)SeriesKO-CAP? T540Capacitance22μFTolerance±20%Voltage - Rated10VTypeMoldedESR (Equivalent Series Resistance)80 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case1411 (3528 Metric)Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.083" (2.10mm)Lead Spacing-	Manufacturer	KEMET
Package         1411 (3528 Metric)           Series         KO-CAP? T540           Capacitance         22μF           Tolerance         ±20%           Voltage - Rated         10V           Type         Molded           ESR (Equivalent Series Resistance)         80 mOhm @ 100kHz           Operating Temperature         -55°C ~ 125°C           Lifetime @ Temp.         2000 Hrs @ 125°C           Mounting Type         Surface Mount           Package / Case         1411 (3528 Metric)           Size / Dimension         0.138" L x 0.110" W (3.50mm x 2.80mm)           Height - Seated (Max)         0.083" (2.10mm)           Lead Spacing         -	Category	Capacitors
Series         KO-CAP? T540           Capacitance         22μF           Tolerance         ±20%           Voltage - Rated         10V           Type         Molded           ESR (Equivalent Series Resistance)         80 mOhm @ 100kHz           Operating Temperature         -55°C ~ 125°C           Lifetime @ Temp.         2000 Hrs @ 125°C           Mounting Type         Surface Mount           Package / Case         1411 (3528 Metric)           Size / Dimension         0.138" L x 0.110" W (3.50mm x 2.80mm)           Height - Seated (Max)         0.083" (2.10mm)           Lead Spacing         -		Tantalum - Polymer Capacitors
Capacitance $22\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $10V$ TypeMoldedESR (Equivalent Series Resistance) $80 \text{ mOhm } @ 100\text{kHz}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Lifetime @ Temp. $2000 \text{ Hrs } @ 125^{\circ}\text{C}$ Mounting TypeSurface MountPackage / Case $1411 (3528 \text{ Metric})$ Size / Dimension $0.138^{\circ}\text{ L x } 0.110^{\circ}\text{ W } (3.50 \text{mm x } 2.80 \text{mm})$ Height - Seated (Max) $0.083^{\circ}$ (2.10 mm)Lead Spacing-	Package	1411 (3528 Metric)
Tolerance ±20%  Voltage - Rated 10V  Type Molded  ESR (Equivalent Series Resistance) 80 mOhm @ 100kHz  Operating Temperature -55°C ~ 125°C  Lifetime @ Temp. 2000 Hrs @ 125°C  Mounting Type Surface Mount  Package / Case 1411 (3528 Metric)  Size / Dimension 0.138" L x 0.110" W (3.50mm x 2.80mm)  Height - Seated (Max) 0.083" (2.10mm)  Lead Spacing -	Series	KO-CAP? T540
Voltage - Rated  Type  Molded  ESR (Equivalent Series Resistance)  80 mOhm @ 100kHz  Operating Temperature  -55°C ~ 125°C  Lifetime @ Temp.  2000 Hrs @ 125°C  Mounting Type  Surface Mount  Package / Case  1411 (3528 Metric)  Size / Dimension  0.138" L x 0.110" W (3.50mm x 2.80mm)  Height - Seated (Max)  Lead Spacing  -	Capacitance	22μF
Type Molded  ESR (Equivalent Series Resistance) 80 mOhm @ 100kHz  Operating Temperature -55°C ~ 125°C  Lifetime @ Temp. 2000 Hrs @ 125°C  Mounting Type Surface Mount  Package / Case 1411 (3528 Metric)  Size / Dimension 0.138" L x 0.110" W (3.50mm x 2.80mm)  Height - Seated (Max) 0.083" (2.10mm)  Lead Spacing -	Tolerance	±20%
ESR (Equivalent Series Resistance)  80 mOhm @ 100kHz  -55°C ~ 125°C  Lifetime @ Temp.  2000 Hrs @ 125°C  Mounting Type  Surface Mount  Package / Case  1411 (3528 Metric)  Size / Dimension  0.138" L x 0.110" W (3.50mm x 2.80mm)  Height - Seated (Max)  0.083" (2.10mm)  Lead Spacing  -	Voltage - Rated	10V
Operating Temperature         -55°C ~ 125°C           Lifetime @ Temp.         2000 Hrs @ 125°C           Mounting Type         Surface Mount           Package / Case         1411 (3528 Metric)           Size / Dimension         0.138" L x 0.110" W (3.50mm x 2.80mm)           Height - Seated (Max)         0.083" (2.10mm)           Lead Spacing         -	Type	Molded
Lifetime @ Temp.       2000 Hrs @ 125°C         Mounting Type       Surface Mount         Package / Case       1411 (3528 Metric)         Size / Dimension       0.138" L x 0.110" W (3.50mm x 2.80mm)         Height - Seated (Max)       0.083" (2.10mm)         Lead Spacing       -	ESR (Equivalent Series Resistance)	80 mOhm @ 100kHz
Mounting Type       Surface Mount         Package / Case       1411 (3528 Metric)         Size / Dimension       0.138" L x 0.110" W (3.50mm x 2.80mm)         Height - Seated (Max)       0.083" (2.10mm)         Lead Spacing       -	Operating Temperature	-55°C ~ 125°C
Package / Case       1411 (3528 Metric)         Size / Dimension       0.138" L x 0.110" W (3.50mm x 2.80mm)         Height - Seated (Max)       0.083" (2.10mm)         Lead Spacing       -	Lifetime @ Temp.	2000 Hrs @ 125°C
Size / Dimension       0.138" L x 0.110" W (3.50mm x 2.80mm)         Height - Seated (Max)       0.083" (2.10mm)         Lead Spacing       -	Mounting Type	Surface Mount
Height - Seated (Max)  Lead Spacing  -  0.083" (2.10mm)  -	Package / Case	1411 (3528 Metric)
Lead Spacing -	Size / Dimension	0.138" L x 0.110" W (3.50mm x 2.80mm)
	Height - Seated (Max)	0.083" (2.10mm)
M C ( C )	Lead Spacing	-
Manufacturer Size Code B	Manufacturer Size Code	В
Features COTS (High Reliability)	Features	COTS (High Reliability)
Report errors?		Report errors?

#### T540B226M010AH86107280 Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **T540B226M010AH86107280 Payment Methods**



















## T540B226M010AH86107280 Shipping Methods













If you have any question about T540B226M010AH86107280, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com