

T540B226M010CH8710

T540B226M010CH8710 Information

Heisener.com	Part Number	T540B226M010CH8710	
	Manufacturer	KEMET	
	Category	Capacitors Tantalum - Polymer Capacitors	
	Description	CAP TANT POLY 22UF 10V 1411	
	Package	1411 (3528 Metric)	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Request a Quote

T540B226M010CH8710 Specifications

Manufacturer KEMET Category Capacitors Tantalum - Polymer Capacitors Tantalum - Polymer Capacitors Package 1411 (3528 Metric) Series KO-CAP? T540 Capacitance 22µF Tolerance ±20% Voltage - Rated 10V Type Molded ESR (Equivalent Series Resistance) 80 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 1411 (3528 Metric) Size / Dimension 0.083" (2.10mm) Height - Seated (Max) 0.083" (2.10mm) Lead Spacing -		
Catagory Capacitors Tantalum - Polymer Capacitors Package 1411 (3528 Metric) Series KO-CAP? T540 Capacitance 22μF Tolerance ±20% Voltage - Rated 10V Type Molded ESR (Equivalent Series Resistance) 80 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 1411 (3528 Metric) Size / Dimension 0.138" L x 0.110" W (3.50mm x 2.80mm) Height - Seated (Max) 0.083" (2.10mm) Lead Spacing - Features COTS (High Reliability)	Manufacturer Part Number	T540B226M010CH8710
Tantalum - Polymer CapacitorsPackage1411 (3528 Metric)SeriesKO-CAP? T540Capacitance22µFTolerance±20%Voltage - Rated10VTypeMoldedESR (Equivalent Series Resistance)80 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case1411 (3528 Metric)Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.083" (2.10mm)Lead Spacing-FeaturesCOTS (High Reliability)	Manufacturer	KEMET
Package1411 (3528 Metric)SeriesKO-CAP? T540Capacitance22µFTolerance±20%Voltage - Rated10VTypeMoldedESR (Equivalent Series Resistance)80 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case1411 (3528 Metric)Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.083" (2.10mm)Lead Spacing-FeaturesCOTS (High Reliability)	Category	Capacitors
Series KO-CAP? T540 Capacitance 22μF Tolerance ±20% Voltage - Rated 10V Type Molded ESR (Equivalent Series Resistance) 80 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 1411 (3528 Metric) Size / Dimension 0.083" (2.10mm) Height - Seated (Max) 0.083" (2.10mm) Lead Spacing - Features COTS (High Reliability)		Tantalum - Polymer Capacitors
Capacitance22μFColerance±20%Voltage - Rated10VTypeMoldedESR (Equivalent Series Resistance)80 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case1411 (3528 Metric)Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.083" (2.10mm)Lead Spacing-FeaturesCOTS (High Reliability)	Package	1411 (3528 Metric)
Tolerance±20%Yoltage - Rated10VTypeMoldedESR (Equivalent Series Resistance)80 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case1411 (3528 Metric)Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.083" (2.10mm)Lead Spacing-FeaturesCOTS (High Reliability)	Series	KO-CAP? T540
Voltage - RatedIOVTypeMoldedESR (Equivalent Series Resistance)80 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case1411 (3528 Metric)Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.083" (2.10mm)Lead Spacing-Manufacturer Size CodeBFeaturesCOTS (High Reliability)	Capacitance	22µF
TypeMoldedESR (Equivalent Series Resistance)80 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case1411 (3528 Metric)Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.083" (2.10mm)Lead Spacing-Manufacturer Size CodeBFeaturesCOTS (High Reliability)	Tolerance	±20%
Final80 mOhm @ 100kHzESR (Equivalent Series Resistance)80 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case1411 (3528 Metric)Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.083" (2.10mm)Lead Spacing-Manufacturer Size CodeBFeaturesCOTS (High Reliability)	Voltage - Rated	10V
Operating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case1411 (3528 Metric)Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.083" (2.10mm)Lead Spacing-Manufacturer Size CodeBFeaturesCOTS (High Reliability)	Туре	Molded
Lifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case1411 (3528 Metric)Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.083" (2.10mm)Lead Spacing-Manufacturer Size CodeBFeaturesCOTS (High Reliability)	ESR (Equivalent Series Resistance)	80 mOhm @ 100kHz
Nounting TypeSurface MountPackage / Case1411 (3528 Metric)Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.083" (2.10mm)Lead Spacing-Manufacturer Size CodeBFeaturesCOTS (High Reliability)	Operating Temperature	-55°C ~ 125°C
Package / Case1411 (3528 Metric)Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.083" (2.10mm)Lead Spacing-Manufacturer Size CodeBFeaturesCOTS (High Reliability)	Lifetime @ Temp.	2000 Hrs @ 125°C
Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.083" (2.10mm)Lead Spacing-Manufacturer Size CodeBFeaturesCOTS (High Reliability)	Mounting Type	Surface Mount
Height - Seated (Max)0.083" (2.10mm)Lead Spacing-Manufacturer Size CodeBFeaturesCOTS (High Reliability)	Package / Case	1411 (3528 Metric)
Lead Spacing-Manufacturer Size CodeBFeaturesCOTS (High Reliability)	Size / Dimension	0.138" L x 0.110" W (3.50mm x 2.80mm)
Manufacturer Size CodeBFeaturesCOTS (High Reliability)	Height - Seated (Max)	0.083" (2.10mm)
Features COTS (High Reliability)	Lead Spacing	-
	Manufacturer Size Code	В
Report errors?	Features	COTS (High Reliability)
		Report errors?

T540B226M010CH8710 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

T540B226M010CH8710 Payment Methods



If you have any question about T540B226M010CH8710, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com