

Heisener.com

T540D227K004AH8705

T540D227K004AH8705 Information

Part Number T540D227K004AH8705

Manufacturer KEMET Category Capacitors

Tantalum - Polymer Capacitors

Description CAP TANT POLY 220UF 4V 2917

Package 2917 (7343 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









T540D227K004AH8705 Specifications

Manufacturer Part Number T540D227K004AH8705 Manufacturer KEMET Category Capacitors Package 2917 (7343 Metric) Series KO-CAP? T540 Capacitance 220μF Tolerance ±10% Voltage - Rated 4V Type Molded ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing D		
Category Capacitors Package 2917 (7343 Metric) Series KO-CAP? T540 Capacitance 220μF Tolerance ±10% Voltage - Rated 4V Type Molded ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing -	Manufacturer Part Number	T540D227K004AH8705
Tantalum - Polymer CapacitorsPackage2917 (7343 Metric)SeriesKO-CAP? T540Capacitance220μFTolerance±10%Voltage - Rated4VTypeMoldedESR (Equivalent Series Resistance)40 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-	Manufacturer	KEMET
Package 2917 (7343 Metric) Series KO-CAP? T540 Capacitance 220μF Tolerance ±10% Voltage - Rated 4V Type Molded ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing -	Category	Capacitors
SeriesKO-CAP? T540Capacitance $220\mu F$ Tolerance $\pm 10\%$ Voltage - Rated $4V$ TypeMoldedESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55° C ~ 125° CLifetime @ Temp. 2000 Hrs @ 125°C Mounting TypeSurface MountPackage / Case $2917 (7343 \text{ Metric})$ Size / Dimension 0.287° L x 0.169° W $(7.30 \text{mm x } 4.30 \text{mm})$ Height - Seated (Max) 0.122° (3.10mm)Lead Spacing-		Tantalum - Polymer Capacitors
Capacitance $220\mu F$ Tolerance $\pm 10\%$ Voltage - Rated $4V$ Type $Molded$ ESR (Equivalent Series Resistance) $40 \text{ mOhm } @ 100\text{kHz}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Lifetime @ Temp. $2000 \text{ Hrs } @ 125^{\circ}\text{C}$ Mounting Type $Surface Mount$ Package / Case $2917 (7343 \text{ Metric})$ Size / Dimension $0.287^{\circ}\text{L x } 0.169^{\circ}\text{W } (7.30 \text{mm x } 4.30 \text{mm})$ Height - Seated (Max) $0.122^{\circ}\text{W } (3.10 \text{mm})$ Lead Spacing $-$	Package	2917 (7343 Metric)
Tolerance ±10% Voltage - Rated 4V Type Molded ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing -	Series	KO-CAP? T540
Voltage - Rated Type Molded ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing	Capacitance	220μF
Type Molded ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing -	Tolerance	$\pm 10\%$
ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing -	Voltage - Rated	4V
Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing -	Type	Molded
Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing	ESR (Equivalent Series Resistance)	40 mOhm @ 100kHz
Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing -	Operating Temperature	-55°C ~ 125°C
Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing -	Lifetime @ Temp.	2000 Hrs @ 125°C
Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing -	Mounting Type	Surface Mount
Height - Seated (Max) Lead Spacing 0.122" (3.10mm) -	Package / Case	2917 (7343 Metric)
Lead Spacing -	Size / Dimension	0.287" L x 0.169" W (7.30mm x 4.30mm)
	Height - Seated (Max)	0.122" (3.10mm)
Manufacturer Size Code	Lead Spacing	-
Manufacturer Dize Code	Manufacturer Size Code	D
Features COTS (High Reliability)	Features	COTS (High Reliability)
Report errors?		Report errors?

T540D227K004AH8705 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

T540D227K004AH8705 Payment Methods



















T540D227K004AH8705 Shipping Methods













If you have any question about T540D227K004AH8705, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com