

Heisener.com

T540D337K006CH8710WAFL

T540D337K006CH8710WAFL Information

Part Number T540D337K006CH8710WAFL

Manufacturer KEMET Category Capacitors

Tantalum - Polymer Capacitors

CAP TANT POLY 330UF 6.3V 2917 **Description**

Package 2917 (7343 Metric)

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









T540D337K006CH8710WAFL Specifications

Manufacturer Part NumberT540D337K006CH8710WAFLManufacturerKEMETCategoryCapacitorsPackage2917 (7343 Metric)SeriesKO-CAP? T540Capacitance330μFTolerance±10%Voltage - Rated6.3VTypeMoldedESR (Equivalent Series Resistance)40 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface Mount
Category Capacitors Package 2917 (7343 Metric) Series KO-CAP? T540 Capacitance 330μF Tolerance ±10% Voltage - Rated 6.3V Type Molded ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C
Tantalum - Polymer Capacitors Package 2917 (7343 Metric) Series KO-CAP? T540 Capacitance 330µF Tolerance ±10% Voltage - Rated 6.3V Type Molded ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C
Package2917 (7343 Metric)SeriesKO-CAP? T540Capacitance330μFTolerance $\pm 10\%$ Voltage - Rated $6.3V$ TypeMoldedESR (Equivalent Series Resistance) $40 \text{ mOhm } @ 100\text{kHz}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Lifetime @ Temp. $2000 \text{ Hrs } @ 125^{\circ}\text{C}$
Series KO-CAP? T540 Capacitance $330\mu F$ Tolerance $\pm 10\%$ Voltage - Rated $6.3V$ Type Molded ESR (Equivalent Series Resistance) $40 \text{ mOhm } @ 100kHz$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Lifetime @ Temp. $2000 \text{ Hrs } @ 125^{\circ}\text{C}$
Capacitance $330 \mu F$ Tolerance $\pm 10 \%$ Voltage - Rated $6.3 V$ TypeMoldedESR (Equivalent Series Resistance) $40 \text{ mOhm } @ 100 \text{kHz}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Lifetime @ Temp. $2000 \text{ Hrs } @ 125^{\circ}\text{C}$
Tolerance $\pm 10\%$ Voltage - Rated $6.3V$ Type Molded ESR (Equivalent Series Resistance) $40 \text{ mOhm } @ 100\text{kHz}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Lifetime @ Temp. $2000 \text{ Hrs } @ 125^{\circ}\text{C}$
Voltage - Rated 6.3V Type Molded ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C
Type Molded ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C
ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C
Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C
Lifetime @ Temp. 2000 Hrs @ 125°C
Mounting Type Surface Mount
Package / Case 2917 (7343 Metric)
Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm)
Height - Seated (Max) 0.122" (3.10mm)
Lead Spacing -
Manufacturer Size Code D
Features COTS (High Reliability)
Report errors?

T540D337K006CH8710WAFL Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

T540D337K006CH8710WAFL Payment Methods



















T540D337K006CH8710WAFL Shipping Methods













If you have any question about T540D337K006CH8710WAFL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com