

Heisener.com

T540D337K2R5DH85057280

T540D337K2R5DH85057280 Information

Part Number T540D337K2R5DH85057280

Manufacturer KEMET Category Capacitors

Tantalum - Polymer Capacitors

Description CAP TANT POLY 330UF 2.5V 2917

Package 2917 (7343 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









T540D337K2R5DH85057280 Specifications

Manufacturer Part NumberT540D337K2R5DH85057280ManufacturerKEMETCategoryCapacitorsPackage2917 (7343 Metric)SeriesKO-CAP? T540Capacitance330μFTolerance±10%Voltage - Rated2.5VTypeMoldedESR (Equivalent Series Resistance)40 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesCOTS (High Reliability)		
Category Capacitors Tantalum - Polymer Capacitors Package 2917 (7343 Metric) Series KO-CAP? T540 Capacitance 330µF Tolerance ±10% Voltage - Rated 2.5V Type Molded ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) Lead Spacing - Manufacturer Size Code D Features Capacitors Tantalum - Polymer Capacitors Ta	Manufacturer Part Number	T540D337K2R5DH85057280
Package 2917 (7343 Metric) Series KO-CAP? T540 Capacitance 330μF Tolerance ±10% Voltage - Rated 2.5V Type Molded ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing - Manufacturer Size Code D Features COTS (High Reliability)	Manufacturer	KEMET
Package 2917 (7343 Metric) Series KO-CAP? T540 Capacitance 330μF Tolerance ±10% Voltage - Rated 2.5 V Type Molded ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing - Manufacturer Size Code D Features COTS (High Reliability)	Category	Capacitors
Series KO-CAP? T540 Capacitance 330µF Tolerance ±10% Voltage - Rated 2.5V Type Molded ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing - Manufacturer Size Code D Features COTS (High Reliability)		Tantalum - Polymer Capacitors
Capacitance330μFTolerance±10%Voltage - Rated2.5VTypeMoldedESR (Equivalent Series Resistance)40 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesCOTS (High Reliability)	Package	2917 (7343 Metric)
Tolerance ±10% Voltage - Rated 2.5V Type Molded ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing - Manufacturer Size Code D Features COTS (High Reliability)	Series	KO-CAP? T540
Voltage - Rated 2.5V Type Molded ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) Lead Spacing Manufacturer Size Code Features COTS (High Reliability)	Capacitance	330µF
Type Molded ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing - Manufacturer Size Code D Features COTS (High Reliability)	Tolerance	±10%
ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) Lead Spacing - Manufacturer Size Code D Features COTS (High Reliability)	Voltage - Rated	2.5V
Operating Temperature Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing Manufacturer Size Code D Features COTS (High Reliability)	Type	Molded
Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing Manufacturer Size Code D COTS (High Reliability)	ESR (Equivalent Series Resistance)	40 mOhm @ 100kHz
Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing - Manufacturer Size Code D Features COTS (High Reliability)	Operating Temperature	-55°C ~ 125°C
Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing - Manufacturer Size Code D Features COTS (High Reliability)	Lifetime @ Temp.	2000 Hrs @ 125°C
Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing - Manufacturer Size Code D Features COTS (High Reliability)	Mounting Type	Surface Mount
Height - Seated (Max) Lead Spacing Manufacturer Size Code Features O.122" (3.10mm) COTS (High Reliability)	Package / Case	2917 (7343 Metric)
Lead Spacing - Manufacturer Size Code D Features COTS (High Reliability)	Size / Dimension	0.287" L x 0.169" W (7.30mm x 4.30mm)
Manufacturer Size Code D Features COTS (High Reliability)	Height - Seated (Max)	0.122" (3.10mm)
Features COTS (High Reliability)	Lead Spacing	-
	Manufacturer Size Code	D
Report errors?	Features	COTS (High Reliability)
		Report errors?

T540D337K2R5DH85057280 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

T540D337K2R5DH85057280 Payment Methods



















T540D337K2R5DH85057280 Shipping Methods













If you have any question about T540D337K2R5DH85057280, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com