

T540D337M003DH8505

T540D337M003DH8505 Information

Heisener.com	Part Number	T540D337M003DH8505
	Manufacturer	KEMET
	Category	Capacitors Tantalum - Polymer Capacitors
	Description	CAP TANT POLY 330UF 3V 2917
	Package	2917 (7343 Metric)
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Request a Quote

T540D337M003DH8505 Specifications

Manufacturer Part Number T540D337M003DH8505 Manufacturer KEMET Category Capacitors Tantalum - Polymer Capacitors Tantalum - Polymer Capacitors Package 2917 (7343 Metric) Series KO-CAP? T540 Capacitance 330µF Tolerance ±20% Voltage - Rated 3V Type Molded ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature 55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing - Manufacturer Size Code D		
Category Capacitors Tantalum - Polymer Capacitors Package 2917 (7343 Metric) Series KO-CAP? T540 Capacitance 330µF Tolerance ±20% Voltage - Rated 3V Type Molded ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing - Facturers D	Manufacturer Part Number	T540D337M003DH8505
Tantalum - Polymer CapacitorsPackage2917 (7343 Metric)SeriesKO-CAP? T540Capacitance330µFTolerance±20%Voltage - Rated3VTypeMoldedESR (Equivalent Series Resistance)40 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesCOTS (High Reliability)	Manufacturer	KEMET
Package2917 (7343 Metric)SeriesKO-CAP? T540Capacitance330µFTolerance±20%Voltage - Rated3VTypeMoldedESR (Equivalent Series Resistance)40 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-FeaturesCOTS (High Reliability)	Category	Capacitors
Series KO-CAP? T540 Capacitance 330µF Tolerance ±20% Voltage - Rated 3V Type Molded ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing - Manufacturer Size Code D Features COTS (High Reliability)		Tantalum - Polymer Capacitors
Capacitance330µFCopacitance±20%Yoltage - Rated3VTypeMoldedESR (Equivalent Series Resistance)40 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-FeaturesCOTS (High Reliability)	Package	2917 (7343 Metric)
Tolerance±20%Yoltage - Rated3VYopeMoldedESR (Equivalent Series Resistance)40 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-FeaturesDFeaturesCOTS (High Reliability)	Series	KO-CAP? T540
Voltage - Rated3VYopeMoldedESR (Equivalent Series Resistance)40 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-FeaturesDFeaturesCOTS (High Reliability)	Capacitance	330µF
Type Molded ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing - Manufacturer Size Code D Features COTS (High Reliability)	Tolerance	±20%
Fraction40 mOhm @ 100kHzESR (Equivalent Series Resistance)40 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesCOTS (High Reliability)	Voltage - Rated	3V
Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing - Manufacturer Size Code D Features COTS (High Reliability)	Туре	Molded
Lifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesCOTS (High Reliability)	ESR (Equivalent Series Resistance)	40 mOhm @ 100kHz
Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing - Manufacturer Size Code D Features COTS (High Reliability)	Operating Temperature	-55°C ~ 125°C
Package / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesCOTS (High Reliability)	Lifetime @ Temp.	2000 Hrs @ 125°C
Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing - Manufacturer Size Code D Features COTS (High Reliability)	Mounting Type	Surface Mount
Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesCOTS (High Reliability)	Package / Case	2917 (7343 Metric)
Lead Spacing-Manufacturer Size CodeDFeaturesCOTS (High Reliability)	Size / Dimension	0.287" L x 0.169" W (7.30mm x 4.30mm)
Manufacturer Size CodeDFeaturesCOTS (High Reliability)	Height - Seated (Max)	0.122" (3.10mm)
Features COTS (High Reliability)	Lead Spacing	-
	Manufacturer Size Code	D
Report errors?	Features	COTS (High Reliability)
Report chois.		Report errors?

T540D337M003DH8505 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

T540D337M003DH8505 Payment Methods



If you have any question about T540D337M003DH8505, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com