

Heisener.com

T540D477M003BH86057610

T540D477M003BH86057610 Information

Part Number T540D477M003BH86057610

Manufacturer KEMET Category Capacitors

Tantalum - Polymer Capacitors

Description CAP TANT POLY 470UF 3V 2917

Package 2917 (7343 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









T540D477M003BH86057610 Specifications

Manufacturer T540D477M003BH86057610 Manufacturer KEMET Category Capacitors Package 2917 (7343 Metric) Series KO-CAP? T540 Capacitance 470µF Tolerance ±20% Voltage - Rated 3V Type Molded ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing - Manufacturer Size Code D Features COTS (High Reliability)		
Category Capacitors Tantalum - Polymer Capacitors Package 2917 (7343 Metric) Series KO-CAP? T540 Capacitance 470µF Tolerance ±20% Voltage - Rated 3V Type Molded ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) Lead Spacing - Manufacturer Size Code D Features Capacitors Tantalum - Polymer Capacitors Tant	Manufacturer Part Number	T540D477M003BH86057610
Package 2917 (7343 Metric) Series KO-CAP? T540 Capacitance 470μF Tolerance ±20% Voltage - Rated 3V Type Molded ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing - Manufacturer Size Code D Features COTS (High Reliability)	Manufacturer	KEMET
Package 2917 (7343 Metric) Series KO-CAP? T540 Capacitance 470μF Tolerance ±20% Voltage - Rated 3V Type Molded ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing - Manufacturer Size Code D Features COTS (High Reliability)	Category	Capacitors
Series KO-CAP? T540 Capacitance 470µF Tolerance ±20% Voltage - Rated 3V Type Molded ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing - Manufacturer Size Code D Features COTS (High Reliability)		Tantalum - Polymer Capacitors
Capacitance $470 \mu F$ Tolerance $\pm 20\%$ Voltage - Rated $3V$ TypeMoldedESR (Equivalent Series Resistance) $40 \text{ mOhm } @ 100 \text{kHz}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Lifetime @ Temp. $2000 \text{ Hrs } @ 125^{\circ}\text{C}$ Mounting TypeSurface MountPackage / Case $2917 (7343 \text{ Metric})$ Size / Dimension $0.287^{\circ}\text{L} \times 0.169^{\circ}\text{W} (7.30 \text{mm x } 4.30 \text{mm})$ Height - Seated (Max) $0.122^{\circ}\text{(}3.10 \text{mm})$ Lead Spacing-Manufacturer Size CodeDFeaturesCOTS (High Reliability)	Package	2917 (7343 Metric)
Tolerance ±20% Voltage - Rated 3V Type Molded ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing - Manufacturer Size Code D Features COTS (High Reliability)	Series	KO-CAP? T540
Voltage - Rated Type Molded ESR (Equivalent Series Resistance) Operating Temperature Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) Lead Spacing Manufacturer Size Code Features COTS (High Reliability)	Capacitance	470μF
Type Molded ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing - Manufacturer Size Code D Features COTS (High Reliability)	Tolerance	±20%
ESR (Equivalent Series Resistance) 40 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) Lead Spacing - Manufacturer Size Code Peatures COTS (High Reliability)	Voltage - Rated	3V
Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing - Manufacturer Size Code D Features COTS (High Reliability)	Туре	Molded
Lifetime @ Temp. 2000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing - Manufacturer Size Code D Features COTS (High Reliability)	ESR (Equivalent Series Resistance)	40 mOhm @ 100kHz
Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing - Manufacturer Size Code D Features COTS (High Reliability)	Operating Temperature	-55°C ~ 125°C
Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing - Manufacturer Size Code D Features COTS (High Reliability)	Lifetime @ Temp.	2000 Hrs @ 125°C
Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.122" (3.10mm) Lead Spacing - Manufacturer Size Code D Features COTS (High Reliability)	Mounting Type	Surface Mount
Height - Seated (Max) Lead Spacing Manufacturer Size Code Features 0.122" (3.10mm) - COTS (High Reliability)	Package / Case	2917 (7343 Metric)
Lead Spacing-Manufacturer Size CodeDFeaturesCOTS (High Reliability)	Size / Dimension	0.287" L x 0.169" W (7.30mm x 4.30mm)
Manufacturer Size Code D Features COTS (High Reliability)	Height - Seated (Max)	0.122" (3.10mm)
Features COTS (High Reliability)	Lead Spacing	-
	Manufacturer Size Code	D
D	Features	COTS (High Reliability)
Report errors?		Report errors?

T540D477M003BH86057610 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

T540D477M003BH86057610 Payment Methods



















T540D477M003BH86057610 Shipping Methods













If you have any question about T540D477M003BH86057610, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com