

# T540D687M003BH8505

## T540D687M003BH8505 Information

Heisener.com	Part Number Manufacturer Category Description Package	T540D687M003BH8505 KEMET Capacitors Tantalum - Polymer Capacitors CAP TANT POLY 680UF 3V 2917 2917 (7343 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# T540D687M003BH8505 Specifications

Manufacturer Part Number T540D687M003BH8505   Manufacturer KEMET   Category Capacitors   Tantalum - Polymer Capacitors Tantalum - Polymer Capacitors   Package 2917 (7343 Metric)   Series KO-CAP? T540   Capacitance 680µF   Tolerance ±20%   Voltage - Rated 3V   Type Molded   Series Resistance) 40 mOhm @ 100kHz   Operating Temperature 55°C ~ 125°C   Lifetime @ Temp. 2000 Hrs @ 125°C   Mounting Type Surface Mount   Package / Case 2917 (7343 Metric)   Size / Dimension 0.287 "L x 0.169" W (7.30mm x 4.30mm)   Height - Seated (Max) 0.122" (3.10mm)   Lead Spacing -   Manufacturer Size Code D   Features COTS (High Reliability)		
Category   Capacitors     Tantalum - Polymer Capacitors     Package   2917 (7343 Metric)     Series   KO-CAP? T540     Capacitance   680µF     Tolerance   ±20%     Voltage - Rated   3V     Type   Molded     ESR (Equivalent Series Resistance)   40 mOhm @ 100kHz     Operating Temperature   -55°C ~ 125°C     Lifetime @ Temp.   2000 Hrs @ 125°C     Mounting Type   Surface Mount     Package / Case   2917 (7343 Metric)     Size / Dimension   0.287" L x 0.169" W (7.30mm x 4.30mm)     Height - Seated (Max)   0.122" (3.10mm)     Lead Spacing   -     Facturers Size Code   D	Manufacturer Part Number	T540D687M003BH8505
Intalum - Polymer CapacitorsPackage2917 (7343 Metric)SeriesKO-CAP? T540Capacitance680µFTolerance±20%Voltage - Rated3VTypeMoldedESR (Equivalent Series Resistance)40 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-FeaturesCOTS (High Reliability)	Manufacturer	KEMET
Package2917 (7343 Metric)SeriesKO-CAP? T540Capacitance680µFTolerance±20%Voltage - Rated3VTypeMoldedESR (Equivalent Series Resistance)40 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-FeaturesCOTS (High Reliability)	Category	Capacitors
Series   KO-CAP? T540     Capacitance   680µF     Tolerance   ±20%     Voltage - Rated   3V     Type   Molded     ESR (Equivalent Series Resistance)   40 mOhm @ 100kHz     Operating Temperature   -55°C ~ 125°C     Lifetime @ Temp.   2000 Hrs @ 125°C     Mounting Type   Surface Mount     Package / Case   2917 (7343 Metric)     Size / Dimension   0.287" L x 0.169" W (7.30mm x 4.30mm)     Height - Seated (Max)   0.122" (3.10mm)     Lead Spacing   -     Manufacturer Size Code   D     Features   COTS (High Reliability)		Tantalum - Polymer Capacitors
Capacitance   680μF     Tolerance   ±20%     Voltage - Rated   3V     Type   Molded     ESR (Equivalent Series Resistance)   40 mOhm @ 100kHz     Operating Temperature   -55°C ~ 125°C     Lifetime @ Temp.   2000 Hrs @ 125°C     Mounting Type   Surface Mount     Package / Case   2917 (7343 Metric)     Size / Dimension   0.287" L x 0.169" W (7.30mm x 4.30mm)     Height - Seated (Max)   0.122" (3.10mm)     Lead Spacing   -     Features   COTS (High Reliability)	Package	2917 (7343 Metric)
Tolerance±20%Yoltage - Rated3VYopeMoldedESR (Equivalent Series Resistance)40 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-FeaturesCOTS (High Reliability)	Series	KO-CAP? T540
Voltage - Rated3VYopeMoldedESR (Equivalent Series Resistance)40 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-FeaturesDFeaturesCOTS (High Reliability)	Capacitance	680µF
Type   Molded     ESR (Equivalent Series Resistance)   40 mOhm @ 100kHz     Operating Temperature   -55°C ~ 125°C     Lifetime @ Temp.   2000 Hrs @ 125°C     Mounting Type   Surface Mount     Package / Case   2917 (7343 Metric)     Size / Dimension   0.287" L x 0.169" W (7.30mm x 4.30mm)     Height - Seated (Max)   0.122" (3.10mm)     Lead Spacing   -     Manufacturer Size Code   D     Features   COTS (High Reliability)	Tolerance	$\pm 20\%$
AT40 mOhm @ 100kHzESR (Equivalent Series Resistance)40 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesCOTS (High Reliability)	Voltage - Rated	3V
Operating Temperature   -55°C ~ 125°C     Lifetime @ Temp.   2000 Hrs @ 125°C     Mounting Type   Surface Mount     Package / Case   2917 (7343 Metric)     Size / Dimension   0.287" L x 0.169" W (7.30mm x 4.30mm)     Height - Seated (Max)   0.122" (3.10mm)     Lead Spacing   -     Manufacturer Size Code   D     Features   COTS (High Reliability)	Туре	Molded
Lifetime @ Temp.2000 Hrs @ 125°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesCOTS (High Reliability)	ESR (Equivalent Series Resistance)	40 mOhm @ 100kHz
Anomaly and a strain of the	Operating Temperature	-55°C ~ 125°C
Package / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesCOTS (High Reliability)	Lifetime @ Temp.	2000 Hrs @ 125°C
Size / Dimension   0.287" L x 0.169" W (7.30mm x 4.30mm)     Height - Seated (Max)   0.122" (3.10mm)     Lead Spacing   -     Manufacturer Size Code   D     Features   COTS (High Reliability)	Mounting Type	Surface Mount
Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesCOTS (High Reliability)	Package / Case	2917 (7343 Metric)
Lead Spacing-Manufacturer Size CodeDFeaturesCOTS (High Reliability)	Size / Dimension	0.287" L x 0.169" W (7.30mm x 4.30mm)
Manufacturer Size CodeDFeaturesCOTS (High Reliability)	Height - Seated (Max)	0.122" (3.10mm)
Features COTS (High Reliability)	Lead Spacing	-
	Manufacturer Size Code	D
Report errors?	Features	COTS (High Reliability)
		Report errors?

## T540D687M003BH8505 Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### T540D687M003BH8505 Payment Methods



If you have any question about T540D687M003BH8505, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com