

Heisener.com

T543X226M063ATE0757280

T543X226M063ATE0757280 Information

Part Number T543X226M063ATE0757280

Manufacturer KEMET Category Capacitors

Tantalum - Polymer Capacitors

Description CAP POLY COTS SMD 22UF 63V 75MOH

Package 2917 (7343 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









T543X226M063ATE0757280 Specifications

Manufacturer T543X226M063ATE0757280 Manufacturer KEMET Category Capacitors Package 2917 (7343 Metric) Series KO-CAP? T543 Capacitance 22µF Tolerance ±20% Voltage - Rated 63V Type Molded ESR (Equivalent Series Resistance) 75 mOhm @ 100kHz Operating Temperature -55°C ~ 105°C Lifetime @ Temp. 2000 Hrs @ 105°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.168" (4.30mm) Lead Spacing - Manufacturer Size Code X Features COTS (High Reliability)		
Category Capacitors Tantalum - Polymer Capacitors Package 2917 (7343 Metric) Series KO-CAP? T543 Capacitance 22µF Tolerance ±20% Voltage - Rated 63V Type Molded ESR (Equivalent Series Resistance) 75 mOhm @ 100kHz Operating Temperature -55°C ~ 105°C Lifetime @ Temp. 2000 Hrs @ 105°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) Lead Spacing - Manufacturer Size Code X Features Capacitors Tantalum - Polymer Capacitors Tantalum - Polymer Capacitors Tomacitors Tomacito	Manufacturer Part Number	T543X226M063ATE0757280
Package 2917 (7343 Metric) Series KO-CAP? T543 Capacitance 22μF Tolerance ±20% Voltage - Rated 63V Type Molded ESR (Equivalent Series Resistance) 75 mOhm @ 100kHz Operating Temperature -55°C ~ 105°C Lifetime @ Temp. 2000 Hrs @ 105°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.168" (4.30mm) Lead Spacing - Manufacturer Size Code X Features COTS (High Reliability)	Manufacturer	KEMET
Package 2917 (7343 Metric) Series KO-CAP? T543 Capacitance 22μF Tolerance ±20% Voltage - Rated 63 V Type Molded ESR (Equivalent Series Resistance) 75 mOhm @ 100kHz Operating Temperature -55°C ~ 105°C Lifetime @ Temp. 2000 Hrs @ 105°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.168" (4.30mm) Lead Spacing - Manufacturer Size Code X Features COTS (High Reliability)	Category	Capacitors
Series KO-CAP? T543 Capacitance 22μF Tolerance ±20% Voltage - Rated 63V Type Molded ESR (Equivalent Series Resistance) 75 mOhm @ 100kHz Operating Temperature -55°C ~ 105°C Lifetime @ Temp. 2000 Hrs @ 105°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.168" (4.30mm) Lead Spacing - Manufacturer Size Code X Features COTS (High Reliability)		Tantalum - Polymer Capacitors
Capacitance 22μF Tolerance ±20% Voltage - Rated 63V Type Molded ESR (Equivalent Series Resistance) 75 mOhm @ 100kHz Operating Temperature -55°C ~ 105°C Lifetime @ Temp. 2000 Hrs @ 105°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.168" (4.30mm) Lead Spacing - Manufacturer Size Code X Features COTS (High Reliability)	Package	2917 (7343 Metric)
Tolerance ±20% Voltage - Rated 63V Type Molded ESR (Equivalent Series Resistance) 75 mOhm @ 100kHz Operating Temperature -55°C ~ 105°C Lifetime @ Temp. 2000 Hrs @ 105°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.168" (4.30mm) Lead Spacing - Manufacturer Size Code X Features COTS (High Reliability)	Series	KO-CAP? T543
Voltage - Rated Type Molded ESR (Equivalent Series Resistance) Operating Temperature Lifetime @ Temp. 2000 Hrs @ 105°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) Lead Spacing Manufacturer Size Code X Features COTS (High Reliability)	Capacitance	22μF
Type Molded ESR (Equivalent Series Resistance) 75 mOhm @ 100kHz Operating Temperature -55°C ~ 105°C Lifetime @ Temp. 2000 Hrs @ 105°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.168" (4.30mm) Lead Spacing - Manufacturer Size Code X Features COTS (High Reliability)	Tolerance	±20%
ESR (Equivalent Series Resistance) 75 mOhm @ 100kHz Operating Temperature -55°C ~ 105°C Lifetime @ Temp. 2000 Hrs @ 105°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) Lead Spacing - Manufacturer Size Code X Features COTS (High Reliability)	Voltage - Rated	63V
Operating Temperature Lifetime @ Temp. 2000 Hrs @ 105°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) Lead Spacing Manufacturer Size Code X Features COTS (High Reliability)	Type	Molded
Lifetime @ Temp. 2000 Hrs @ 105°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 1.24 Code Manufacturer Size Code X Features COTS (High Reliability)	ESR (Equivalent Series Resistance)	75 mOhm @ 100kHz
Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.168" (4.30mm) Lead Spacing - Manufacturer Size Code X Features COTS (High Reliability)	Operating Temperature	-55°C ~ 105°C
Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.168" (4.30mm) Lead Spacing - Manufacturer Size Code X Features COTS (High Reliability)	Lifetime @ Temp.	2000 Hrs @ 105°C
Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.168" (4.30mm) Lead Spacing - Manufacturer Size Code X Features COTS (High Reliability)	Mounting Type	Surface Mount
Height - Seated (Max) Lead Spacing - Manufacturer Size Code K Features O.168" (4.30mm) - X COTS (High Reliability)	Package / Case	2917 (7343 Metric)
Lead Spacing-Manufacturer Size CodeXFeaturesCOTS (High Reliability)	Size / Dimension	0.287" L x 0.169" W (7.30mm x 4.30mm)
Manufacturer Size Code X Features COTS (High Reliability)	Height - Seated (Max)	0.168" (4.30mm)
Features COTS (High Reliability)	Lead Spacing	-
	Manufacturer Size Code	X
Report errors?	Features	COTS (High Reliability)
		Report errors?

T543X226M063ATE0757280 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

T543X226M063ATE0757280 Payment Methods



















T543X226M063ATE0757280 Shipping Methods













If you have any question about T543X226M063ATE0757280, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com