

T73S5D15-24 Information



For Reference Only

Part Number T73S5D15-24

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 10A 24V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









T73S5D15-24 Specifications

Manufacturer Part NumberT73S5D15-24ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesT73Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current20.9mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage120VAC, 28VDC - MaxTurn On Voltage (Max)15.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time5msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesT73Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current20.9mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage120VAC, 28VDC - MaxTurn On Voltage (Max)15.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time5msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	T73S5D15-24
Package - Series T73 Relay Type General Purpose Coil Type Non Latching Coil Current 20.9mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 120VAC, 28VDC - Max Turn On Voltage (Max) 15.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - T73 Relay Type General Purpose Coil Type Non Latching Coil Current 20.9mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 120VAC, 28VDC - Max Turn On Voltage (Max) 15.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Category	Relays
SeriesT73Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current20.9mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage120VAC, 28VDC - MaxTurn On Voltage (Max)15.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time5msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 20.9mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 120VAC, 28VDC - Max Turn On Voltage (Max) 15.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil Type Non Latching Coil Current 20.9mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 120VAC, 28VDC - Max Turn On Voltage (Max) 15.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Series	T73
Coil Current Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 120VAC, 28VDC - Max Turn On Voltage (Max) 15.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 120VAC, 28VDC - Max Turn On Voltage (Max) 15.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage 120VAC, 28VDC - Max Turn On Voltage (Max) 15.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style	Coil Current	20.9mA
Contact Rating (Current) Switching Voltage 120VAC, 28VDC - Max Turn On Voltage (Max) 15.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Voltage	24VDC
Switching Voltage 120VAC, 28VDC - Max Turn On Voltage (Max) 15.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) 15.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	120VAC, 28VDC - Max
Operate Time10msRelease Time5msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	15.6 VDC
Release Time 5ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	1.2 VDC
Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	10ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	Insulation - Class F, Sealed - Fully
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

T73S5D15-24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

T73S5D15-24 Payment Methods



















T73S5D15-24 Shipping Methods













If you have any question about T73S5D15-24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com