

## **T7CS1D-24 Information**



For Reference Only

Part Number T7CS1D-24

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPST 12A 24V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **T7CS1D-24 Specifications**

Manufacturer Part NumberT7CS1D-24ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPackage-SeriesT7CRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current15mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)12ASwitching Voltage240VAC, 28VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time5msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough Hole		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesT7CRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current15mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)12ASwitching Voltage240VAC, 28VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time5msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough Hole	Manufacturer Part Number	T7CS1D-24
Package - Series T7C Relay Type General Purpose Coil Type Non Latching Coil Current 15mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 12A Switching Voltage 240VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully Mounting Type Trrough Hole	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - T7C  Relay Type General Purpose  Coil Type Non Latching  Coil Current 15mA  Coil Voltage 24VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 12A  Switching Voltage 240VAC, 28VDC - Max  Turn On Voltage (Max) 18 VDC  Turn Off Voltage (Min) 1.2 VDC  Operate Time 10ms  Release Time 5ms  Features Insulation - Class F, Sealed - Fully  Mounting Type Trhrough Hole	Category	Relays
Series         T7C           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         15mA           Coil Voltage         24VDC           Contact Form         SPST-NO (1 Form A)           Contact Rating (Current)         12A           Switching Voltage         240VAC, 28VDC - Max           Turn On Voltage (Max)         18 VDC           Turn Off Voltage (Min)         1.2 VDC           Operate Time         10ms           Release Time         5ms           Features         Insulation - Class F, Sealed - Fully           Mounting Type         Through Hole		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current15mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)12ASwitching Voltage240VAC, 28VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time5msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough Hole	Package	-
Coil Type Non Latching Coil Current 15mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 12A Switching Voltage 240VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Series	T7C
Coil Current Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 12A Switching Voltage 240VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 12A Switching Voltage 240VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 12A  Switching Voltage 240VAC, 28VDC - Max  Turn On Voltage (Max) 18 VDC  Turn Off Voltage (Min) 1.2 VDC  Operate Time 10ms  Release Time 5ms  Features Insulation - Class F, Sealed - Fully  Mounting Type Through Hole	Coil Current	15mA
Contact Rating (Current)  Switching Voltage  240VAC, 28VDC - Max  Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  1.2 VDC  Operate Time  10ms  Release Time  5ms  Features  Insulation - Class F, Sealed - Fully  Mounting Type  Through Hole	Coil Voltage	24VDC
Switching Voltage 240VAC, 28VDC - Max  Turn On Voltage (Max) 18 VDC  Turn Off Voltage (Min) 1.2 VDC  Operate Time 10ms  Release Time 5ms  Features Insulation - Class F, Sealed - Fully  Mounting Type Through Hole	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  1.2 VDC  Operate Time  10ms  Release Time  5ms  Features  Insulation - Class F, Sealed - Fully  Mounting Type  Through Hole	Contact Rating (Current)	12A
Turn Off Voltage (Min)  Operate Time  10ms  Release Time  5ms  Features  Insulation - Class F, Sealed - Fully  Mounting Type  Through Hole	Switching Voltage	240VAC, 28VDC - Max
Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Turn On Voltage (Max)	18 VDC
Release Time 5ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Turn Off Voltage (Min)	1.2 VDC
Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Operate Time	10ms
Mounting Type Through Hole	Release Time	5ms
	Features	Insulation - Class F, Sealed - Fully
The state of the s	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

### **T7CS1D-24 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **T7CS1D-24 Payment Methods**





















## **T7CS1D-24 Shipping Methods**













If you have any question about T7CS1D-24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com