

T86D476K016EBSS

T86D476K016EBSS Information

Heisener.com	Part Number Manufacturer Category Description Package	T86D476K016EBSS Vishay Sprague Capacitors Tantalum Capacitors CAP TANT 47UF 16V 10% 2917 2917 (7343 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



T86D476K016EBSS Specifications

ManufacturerVishay SpragueCategoryCapacitorsTantalum CapacitorsPackage2917 (7343 Metric)SeriesTANTAMOUNT?, T86Capacitance47µFTolerance±10%Voltage - Rated16VTypeMoldedESR (Equivalent Series Resistance)700 mOhmOperating Temperature-55°C ~ 125°CLifetime @ Temp.Surface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-FeaturesDCorts, Fail Safe with Built-in Fuse		
CategoryCapacitorsCategoryTantalum CapacitorsPackage2917 (7343 Metric)SeriesTANTAMOUNT?, T86Capacitance47µFTolerance±10%Voltage - Rated16VTypeMoldedESR (Equivalent Series Resistance)700 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lad Spacing-Manufacturer Size CodeDFeaturesCOTS, Fail Safe with Built-in FuseFailure Rate-	Manufacturer Part Number	T86D476K016EBSS
Tantalum CapacitorsPackage2917 (7343 Metric)SeriesTANTAMOUNT?, T86Capacitance47μFTolerance±10%Voltage - Rated16VTypeMoldedESR (Equivalent Series Resistance)700 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesCOTS, Fail Safe with Built-in FuseFailure Rate-	Manufacturer	Vishay Sprague
Package2917 (7343 Metric)SeriesTANTAMOUNT?, T86Capacitance47µFTolerance±10%Voltage - Rated16VTypeMoldedESR (Equivalent Series Resistance)700 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.122" (3.10mm)Height - Seated (Max)DLead SpacingDFeaturesCOTS, Fail Safe with Built-in FuseFailure Rate-	Category	Capacitors
ArrowTANTAMOUNT?, T86Capacitance47μFTolerance±10%Voltage - Rated16VVoltage - RatedMoldedTypeMoldedESR (Equivalent Series Resistance)700 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.122" (3.10mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-FeaturesCOTS, Fail Safe with Built-in FuseFailure Rate-		Tantalum Capacitors
Capacitance47μFTolerance±10%Voltage - Rated16VTypeMoldedESR (Equivalent Series Resistance)700 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.122" (3.10mm) x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-FeaturesCOTS, Fail Safe with Built-in FuseFailure Rate-	Package	2917 (7343 Metric)
Tolerance±10%Voltage - Rated16VTypeMoldedESR (Equivalent Series Resistance)700 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-FeaturesCOTS, Fail Safe with Built-in FuseFailure Rate-	Series	TANTAMOUNT?, T86
Voltage - Rated16VYopeMoldedESR (Equivalent Series Resistance)700 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesCOTS, Fail Safe with Built-in FuseFailure Rate-	Capacitance	47μF
TypeMoldedTypeMoldedESR (Equivalent Series Resistance)700 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesCOTS, Fail Safe with Built-in FuseFailure Rate-	Tolerance	±10%
AT700 mOhmESR (Equivalent Series Resistance)700 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesCOTS, Fail Safe with Built-in FuseFailure Rate-	Voltage - Rated	16V
Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesCOTS, Fail Safe with Built-in FuseFailure Rate-	Туре	Molded
Lifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesCOTS, Fail Safe with Built-in FuseFailure Rate-	ESR (Equivalent Series Resistance)	700 mOhm
Mounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesCOTS, Fail Safe with Built-in FuseFailure Rate-	Operating Temperature	-55°C ~ 125°C
Package / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesCOTS, Fail Safe with Built-in FuseFailure Rate-	Lifetime @ Temp.	-
Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesCOTS, Fail Safe with Built-in FuseFailure Rate-	Mounting Type	Surface Mount
Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesCOTS, Fail Safe with Built-in FuseFailure Rate-	Package / Case	2917 (7343 Metric)
Lead Spacing-Manufacturer Size CodeDFeaturesCOTS, Fail Safe with Built-in FuseFailure Rate-	Size / Dimension	0.287" L x 0.169" W (7.30mm x 4.30mm)
Manufacturer Size CodeDFeaturesCOTS, Fail Safe with Built-in FuseFailure Rate-	Height - Seated (Max)	0.122" (3.10mm)
FeaturesCOTS, Fail Safe with Built-in FuseFailure Rate-	Lead Spacing	-
Failure Rate -	Manufacturer Size Code	D
	Features	COTS, Fail Safe with Built-in Fuse
Report errors?	Failure Rate	-
		Report errors?

T86D476K016EBSS Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

T86D476K016EBSS Payment Methods



If you have any question about T86D476K016EBSS, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com