



T9AS1D12-18 Information



For Reference Only

Part Number T9AS1D12-18

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 30A 18V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









T9AS1D12-18 Specifications

Manufacturer Part Number T9ASID12-18 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series T9A Relay Type General Purpose Coil Type Non Latching Coil Current 55.6mA Coil Voltage 18VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 15ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPackage-SeriesT9ARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current55.6mACoil Voltage18VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage277VAC - MaxTurn On Voltage (Max)13.5 VDCTurn Off Voltage (Min)1.8 VDCOperate Time15msRelease Time15msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough Hole	Manufacturer Part Number	T9AS1D12-18
Package - Series T9A Relay Type General Purpose Coil Type Non Latching Coil Current 55.6mA Coil Voltage 18VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 15ms Features Insulation - Class F, Sealed - Fully Mounting Type Troods	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - T9A Relay Type General Purpose Coil Type Non Latching Coil Current 55.6mA Coil Voltage 18VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 15ms Release Time 15ms Resultation - Class F, Sealed - Fully Mounting Type Through Hole	Category	Relays
Series T9A Relay Type General Purpose Coil Type Non Latching Coil Current 55.6mA Coil Voltage 18VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 15ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 55.6mA Coil Voltage 18VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 15ms Release Time 15ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Package	-
Coil Type Non Latching Coil Current 55.6mA Coil Voltage 18VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 15ms Release Time 15ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Series	T9A
Coil Current Coil Voltage 18VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 15ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Relay Type	General Purpose
Coil Voltage 18VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 15ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 15ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Coil Current	55.6mA
Contact Rating (Current) Switching Voltage 277VAC - Max Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 15ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Coil Voltage	18VDC
Switching Voltage 277VAC - Max Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 15ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 15ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Contact Rating (Current)	30A
Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 15ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Switching Voltage	277VAC - Max
Operate Time 15ms Release Time 15ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Turn On Voltage (Max)	13.5 VDC
Release Time 15ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Turn Off Voltage (Min)	1.8 VDC
Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Operate Time	15ms
Mounting Type Through Hole	Release Time	15ms
	Features	Insulation - Class F, Sealed - Fully
Termination Style PC Pin	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

T9AS1D12-18 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

T9AS1D12-18 Payment Methods



















T9AS1D12-18 Shipping Methods













If you have any question about T9AS1D12-18, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com