

TACL226M003X

TACL226M003X Information



For Reference Only

Part Number	TACL226M003X		
Manufacturer	AVX Corporation		
Category	Capacitors Tantalum Capacitors		
Description	CAP TANT 22UF 3V 20% 0603		
Package	0603 (1608 Metric)		
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com		



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



TACL226M003X Specifications

ManufacturerAVX CorporationCapacitorsTantalum CapacitorsPackage0603 (1608 Metric)SeriesTACmicrochip?, TACCapacitance22µFTolerance20%Voltage - Rated3VSpreisSoldedSeries Resistance)7.5 OhmOperating Temperature-55°C ~ 125°CLifetime @ Temp.Surface MountPackage / Case0603 (1608 Metric)Siz / Dimension0.063° L x 0.033° W (1.60mm x 0.85mm)Height - Seated (Max)0.039° (1.00mm)Lead SpacingLFaturesLFeaturesLFeaturesL			
CategoryCapacitorsTantalum CapacitorsPackage0603 (1608 Metric)SeriesTACmicrochip?, TACCapacitance22µFTolerance±20%Voltage - Rated3VTypeMoldedESR (Equivalent Series Resistance)7.5 OhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting Type0603 (1608 Metric)Size / Dimension0.063° L x 0.033° W (1.60mm x 0.85mm)Height - Seated (Max)0.039° (1.00mm)Lead Spacing-Manufacturer Size CodeLFaturesGeneral PurposeFailure Rate-	Manufacturer Part Number	TACL226M003X	
Tantalum CapacitorsPackage0603 (1608 Metric)SeriesTACmicrochip?, TACCapacitance22μFTolerance±20%Voltage - Rated3VTypeMoldedESR (Equivalent Series Resistance)7.5 OhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.033" W (1.60mm x 0.85mm)Height - Seated (Max)0.039" (1.00mm)Lead Spacing-Manufacturer Size CodeLFaturesGeneral PurposeFailure Rate-	Manufacturer	AVX Corporation	
Package0603 (1608 Metric)SeriesTACmicrochip?, TACCapacitance22µFTolerance±20%Voltage - Rated3VTypeMoldedESR (Equivalent Series Resistance)7.5 OhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case0603 (1608 Metric)Size / Dimension0.039" (1.00mm)Height - Seated (Max)0.039" (1.00mm)Lead Spacing-Manufacturer Size CodeLFaturesGeneral PurposeFailure Rate-	Category	Capacitors	
Series TACmicrochip?, TAC Capacitance 22µF Tolerance ±20% Voltage - Rated 3V Type Molded ESR (Equivalent Series Resistance) 7.5 Ohm Operating Temperature -55°C ~ 125°C Lifetime @ Temp. - Mounting Type Surface Mount Package / Case 0603 (1608 Metric) Size / Dimension 0.039" (1.00mm) Height - Seated (Max) 0.399" (1.00mm) Lead Spacing - Manufacturer Size Code L Features General Purpose Failure Rate -		Tantalum Capacitors	
Capacitance22μFTolerance±20%Voltage - Rated3VTypeMoldedESR (Equivalent Series Resistance)7.5 OhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.033" W (1.60mm x 0.85mm)Height - Seated (Max)0.039" (1.00mm)Lead Spacing-Manufacturer Size CodeLFeaturesGeneral PurposeFailure Rate-	Package	0603 (1608 Metric)	
Tolerance±20%Voltage - Rated3VTypeMoldedESR (Equivalent Series Resistance)7.5 OhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.033" W (1.60mm x 0.85mm)Height - Seated (Max)0.039" (1.00mm)Lead Spacing-FaturesGeneral PurposeFatures-	Series	TACmicrochip?, TAC	
Voltage - Rated3VTypeMoldedESR (Equivalent Series Resistance)7.5 OhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.033" W (1.60mm x 0.85mm)Height - Seated (Max)0.039" (1.00mm)Lead SpacingLFeaturesGeneral PurposeFailure Rate-	Capacitance	22µF	
TypeMoldedESR (Equivalent Series Resistance)7.5 OhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.033" W (1.60mm x 0.85mm)Height - Seated (Max)0.039" (1.00mm)Lead Spacing-Manufacturer Size CodeLFeaturesGeneral PurposeFailure Rate-	Tolerance	±20%	
Fill7.5 OhmESR (Equivalent Series Resistance)7.5 OhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.033" W (1.60mm x 0.85mm)Height - Seated (Max)0.039" (1.00mm)Lead Spacing-Manufacturer Size CodeLFeaturesGeneral PurposeFailure Rate-	Voltage - Rated	3V	
Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.033" W (1.60mm x 0.85mm)Height - Seated (Max)0.039" (1.00mm)Lead Spacing-Manufacturer Size CodeLFeaturesGeneral PurposeFailure Rate-	Туре	Molded	
Lifetime @ TempMounting TypeSurface MountPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.033" W (1.60mm x 0.85mm)Height - Seated (Max)0.039" (1.00mm)Lead Spacing-Manufacturer Size CodeLFeaturesGeneral PurposeFailure Rate-	ESR (Equivalent Series Resistance)	7.5 Ohm	
Mounting TypeSurface MountPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.033" W (1.60mm x 0.85mm)Height - Seated (Max)0.039" (1.00mm)Lead Spacing-Manufacturer Size CodeLFeaturesGeneral PurposeFailure Rate-	Operating Temperature	-55°C ~ 125°C	
Package / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.033" W (1.60mm x 0.85mm)Height - Seated (Max)0.039" (1.00mm)Lead Spacing-Manufacturer Size CodeLFeaturesGeneral PurposeFailure Rate-	Lifetime @ Temp.	-	
Size / Dimension0.063" L x 0.033" W (1.60mm x 0.85mm)Height - Seated (Max)0.039" (1.00mm)Lead Spacing-Manufacturer Size CodeLFeaturesGeneral PurposeFailure Rate-	Mounting Type	Surface Mount	
Height - Seated (Max)0.039" (1.00mm)Lead Spacing-Manufacturer Size CodeLFeaturesGeneral PurposeFailure Rate-	Package / Case	0603 (1608 Metric)	
Lead Spacing-Manufacturer Size CodeLFeaturesGeneral PurposeFailure Rate-	Size / Dimension	0.063" L x 0.033" W (1.60mm x 0.85mm)	
Manufacturer Size CodeLFeaturesGeneral PurposeFailure Rate-	Height - Seated (Max)	0.039" (1.00mm)	
FeaturesGeneral PurposeFailure Rate-	Lead Spacing	-	
Failure Rate -	Manufacturer Size Code	L	
	Features	General Purpose	
Report errors?	Failure Rate	-	
			Report errors?

TACL226M003X Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

TACL226M003X Payment Methods



TACL226M003X Shipping Methods



If you have any question about TACL226M003X, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com