

TBPDLNN005PGUCV

TBPDLNN005PGUCV Information



For Reference Only

Part Number TBPDLNN005PGUCV

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

DescriptionSENSOR PRESSURE GAUGE**Package**4-DIP (0.453", 11.50mm), Top Port

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TBPDLNN005PGUCV Specifications

Manufacturer Part Number TBPDLNN005PGUCV Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package 4-DIP (0.453", 11.50mm), Top Port Series TBP Pressure Type Vented Gauge Operating Pressure 5 PSI (34.47 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 25 mV (5V) Accuracy ±0.15% Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package 4-DIP		
CategorySensors, TransducersPackage4-DIP (0.453", 11.50mm), Top PortSeriesTBPPressure TypeVented GaugeOperating Pressure5 PSI (34.47 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 25 mV (5V)Accuracy±0.15%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top PortSupplier Device Package4-DIP	Manufacturer Part Number	TBPDLNN005PGUCV
Package 4-DIP (0.453", 11.50mm), Top Port Series TBP Pressure Type Vented Gauge Operating Pressure Output Type Wheatstone Bridge Output 0 mV ~ 25 mV (5V) Accuracy ±0.15% Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature 40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions
Package4-DIP (0.453", 11.50mm), Top PortSeriesTBPPressure TypeVented GaugeOperating Pressure5 PSI (34.47 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 25 mV (5V)Accuracy±0.15%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top PortSupplier Device Package4-DIP	Category	Sensors, Transducers
SeriesTBPPressure TypeVented GaugeOperating Pressure5 PSI (34.47 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 25 mV (5V)Accuracy±0.15%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top PortSupplier Device Package4-DIP		Pressure Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure 5 PSI (34.47 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 25 mV (5V) Accuracy ±0.15% Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package	Package	4-DIP (0.453", 11.50mm), Top Port
Operating Pressure 5 PSI (34.47 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 25 mV (5V) Accuracy ±0.15% Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature - 40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package	Series	TBP
Output TypeWheatstone BridgeOutput0 mV ~ 25 mV (5V)Accuracy±0.15%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top PortSupplier Device Package4-DIP	Pressure Type	Vented Gauge
Output $0 \text{ mV} \sim 25 \text{ mV} (5\text{V})$ Accuracy $\pm 0.15\%$ Voltage - Supply $1.5 \text{ V} \sim 12 \text{ V}$ Port SizeMale - 0.13 " (3.18mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure $30 \text{ PSI} (206.84 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4-\text{DIP} (0.453", 11.50\text{mm}), \text{Top Port}$ Supplier Device Package $4-\text{DIP}$	Operating Pressure	5 PSI (34.47 kPa)
Accuracy ±0.15% Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package 4-DIP	Output Type	Wheatstone Bridge
Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package	Output	$0 \text{ mV} \sim 25 \text{ mV} (5\text{V})$
Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package 4-DIP	Accuracy	±0.15%
Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package 4-DIP	Voltage - Supply	1.5 V ~ 12 V
Features Temperature Compensated Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package 4-DIP	Port Size	Male - 0.13" (3.18mm) Tube
Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package 4-DIP	Port Style	Barbless
Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package 4-DIP	Features	Temperature Compensated
Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package 4-DIP	Termination Style	PC Pin
Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package 4-DIP	Maximum Pressure	30 PSI (206.84 kPa)
Supplier Device Package 4-DIP	Operating Temperature	-40°C ~ 125°C
	Package / Case	4-DIP (0.453", 11.50mm), Top Port
Report errors?	Supplier Device Package	4-DIP
Report crisis.		Report errors?

TBPDLNN005PGUCV Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TBPDLNN005PGUCV Payment Methods



















TBPDLNN005PGUCV Shipping Methods













If you have any question about TBPDLNN005PGUCV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com