

Heisener.com

TBPDLNS150PGUCV

TBPDLNS150PGUCV Information

Part Number TBPDLNS150PGUCV

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

DescriptionBASIC MODEL PRESSURE SENSOR**Package**4-DIP (0.453", 11.50mm), Top Port

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TBPDLNS150PGUCV Specifications

Manufacturer Part NumberTBPDLNS150PGUCVManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPackage4-DIP (0.453", 11.50mm), Top PortSeriesTBPPressure TypeVented GaugeOperating Pressure150 PSI (1034.21 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 45.75 mV (5V)Accuracy±0.15%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure245 PSI (1689.22 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top PortSupplier Device Package4-DIP		
CategorySensors, TransducersPackage4-DIP (0.453", 11.50mm), Top PortSeriesTBPPressure TypeVented GaugeOperating Pressure150 PSI (1034.21 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 45.75 mV (5V)Accuracy±0.15%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure245 PSI (1689.22 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top PortSupplier Device Package4-DIP	Manufacturer Part Number	TBPDLNS150PGUCV
Package 4-DIP (0.453", 11.50mm), Top Port Series TBP Pressure Type Vented Gauge Operating Pressure 150 PSI (1034.21 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 45.75 mV (5V) Accuracy ±0.15% Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure 40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions
Package4-DIP (0.453", 11.50mm), Top PortSeriesTBPPressure TypeVented GaugeOperating Pressure150 PSI (1034.21 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 45.75 mV (5V)Accuracy±0.15%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure245 PSI (1689.22 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top PortSupplier Device Package4-DIP	Category	Sensors, Transducers
SeriesTBPPressure TypeVented GaugeOperating Pressure150 PSI (1034.21 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 45.75 mV (5V)Accuracy±0.15%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure245 PSI (1689.22 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top PortSupplier Device Package4-DIP		Pressure Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure 150 PSI (1034.21 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 45.75 mV (5V) Accuracy ±0.15% Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure 245 PSI (1689.22 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package 4-DIP	Package	4-DIP (0.453", 11.50mm), Top Port
Operating Pressure Output Type Wheatstone Bridge Output 0 mV ~ 45.75 mV (5V) Accuracy ±0.15% Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure 245 PSI (1689.22 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package	Series	TBP
Output TypeWheatstone BridgeOutput0 mV ~ 45.75 mV (5V)Accuracy±0.15%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure245 PSI (1689.22 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top PortSupplier Device Package4-DIP	Pressure Type	Vented Gauge
Output 0 mV ~ 45.75 mV (5V) Accuracy ±0.15% Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure 245 PSI (1689.22 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package 4-DIP	Operating Pressure	150 PSI (1034.21 kPa)
Accuracy ±0.15% Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure 245 PSI (1689.22 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package 4-DIP	Output Type	Wheatstone Bridge
Voltage - Supply Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure 245 PSI (1689.22 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package	Output	$0 \text{ mV} \sim 45.75 \text{ mV} (5\text{V})$
Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure 245 PSI (1689.22 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package 4-DIP	Accuracy	±0.15%
Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure 245 PSI (1689.22 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package 4-DIP	Voltage - Supply	1.5 V ~ 12 V
Features Temperature Compensated Termination Style PC Pin Maximum Pressure 245 PSI (1689.22 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package 4-DIP	Port Size	Male - 0.13" (3.18mm) Tube
Termination Style PC Pin Maximum Pressure 245 PSI (1689.22 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package 4-DIP	Port Style	Barbless
Maximum Pressure 245 PSI (1689.22 kPa) Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package 4-DIP	Features	Temperature Compensated
Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package 4-DIP	Termination Style	PC Pin
Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package 4-DIP	Maximum Pressure	245 PSI (1689.22 kPa)
Supplier Device Package 4-DIP	Operating Temperature	-40°C ~ 125°C
	Package / Case	4-DIP (0.453", 11.50mm), Top Port
Donost among	Supplier Device Package	4-DIP
Report errors?		Report errors

TBPDLNS150PGUCV Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TBPDLNS150PGUCV Payment Methods



















TBPDLNS150PGUCV Shipping Methods













If you have any question about TBPDLNS150PGUCV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com