

TBPLANN100PGUCV

TBPLANN100PGUCV Information



For Reference Only

Part Number TBPLANN100PGUCV

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

DescriptionSENSOR PRESSURE GAUGE**Package**6-SMD, No Lead, Top Port

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TBPLANN100PGUCV Specifications

Manufacturer Part NumberTBPLANN100PGUCVManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPackage6-SMD, No Lead, Top PortSeriesTBPPressure TypeVented GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 25.5 mV (5V)Accuracy±0.15%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.11" (2.74mm) TubePort StyleBarbedFeaturesTemperature CompensatedTermination StyleSurface MountMaximum Pressure245 PSI (1689.22 kPa)Operating Temperature-40°C ~ 125°CPackage / Case6-SMD, No Lead, Top PortSupplier Device Package6-SMT		
CategorySensors, TransducersPressure Sensors, TransducersPackage6-SMD, No Lead, Top PortSeriesTBPPressure TypeVented GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 25.5 mV (5V)Accuracy±0.15%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.11" (2.74mm) TubePort StyleBarbedFeaturesTemperature CompensatedTermination StyleSurface MountMaximum Pressure245 PSI (1689.22 kPa)Operating Temperature-40°C ~ 125°CPackage / Case6-SMD, No Lead, Top PortSupplier Device Package6-SMT	Manufacturer Part Number	TBPLANN100PGUCV
Package 6-SMD, No Lead, Top Port Series TBP Pressure Type Vented Gauge Operating Pressure 100 PSI (689.48 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 25.5 mV (5V) Accuracy ±0.15% Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.11" (2.74mm) Tube Port Style Barbed Features Temperature Compensated Termination Style Surface Mount Maximum Pressure 245 PSI (1689.22 kPa) Operating Temperature - 40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Sure Port Small Pressure - 40°C ~ 125 POT Port Supplier Device Package 6-SMT	Manufacturer	Honeywell Sensing and Productivity Solutions
Package6-SMD, No Lead, Top PortSeriesTBPPressure TypeVented GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 25.5 mV (5V)Accuracy±0.15%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.11" (2.74mm) TubePort StyleBarbedFeaturesTemperature CompensatedTermination StyleSurface MountMaximum Pressure245 PSI (1689.22 kPa)Operating Temperature-40°C ~ 125°CPackage / Case6-SMD, No Lead, Top PortSupplier Device Package6-SMT	Category	Sensors, Transducers
SeriesTBPPressure TypeVented GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 25.5 mV (5V)Accuracy±0.15%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.11" (2.74mm) TubePort StyleBarbedFeaturesTemperature CompensatedTermination StyleSurface MountMaximum Pressure245 PSI (1689.22 kPa)Operating Temperature-40°C ~ 125°CPackage / Case6-SMD, No Lead, Top PortSupplier Device Package6-SMT		Pressure Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure 100 PSI (689.48 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 25.5 mV (5V) Accuracy ±0.15% Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.11" (2.74mm) Tube Port Style Barbed Features Temperature Compensated Termination Style Surface Mount Maximum Pressure 245 PSI (1689.22 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package 6-SMT	Package	6-SMD, No Lead, Top Port
Operating Pressure 100 PSI (689.48 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 25.5 mV (5V) Accuracy ±0.15% Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.11" (2.74mm) Tube Port Style Barbed Features Temperature Compensated Termination Style Surface Mount Maximum Pressure 245 PSI (1689.22 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package 6-SMT	Series	TBP
Output TypeWheatstone BridgeOutput0 mV ~ 25.5 mV (5V)Accuracy±0.15%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.11" (2.74mm) TubePort StyleBarbedFeaturesTemperature CompensatedTermination StyleSurface MountMaximum Pressure245 PSI (1689.22 kPa)Operating Temperature-40°C ~ 125°CPackage / Case6-SMD, No Lead, Top PortSupplier Device Package6-SMT	Pressure Type	Vented Gauge
Output $0 \text{ mV} \sim 25.5 \text{ mV} (5\text{V})$ Accuracy $\pm 0.15\%$ Voltage - Supply $1.5 \text{ V} \sim 12 \text{ V}$ Port SizeMale - $0.11''$ (2.74mm) TubePort StyleBarbedFeaturesTemperature CompensatedTermination StyleSurface MountMaximum Pressure $245 \text{ PSI} (1689.22 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case 6-SMD , No Lead, Top PortSupplier Device Package 6-SMT	Operating Pressure	100 PSI (689.48 kPa)
Accuracy ±0.15% Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.11" (2.74mm) Tube Port Style Barbed Features Temperature Compensated Termination Style Surface Mount Maximum Pressure 245 PSI (1689.22 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package 6-SMT	Output Type	Wheatstone Bridge
Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.11" (2.74mm) Tube Port Style Barbed Temperature Compensated Termination Style Surface Mount Maximum Pressure 245 PSI (1689.22 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package 6-SMT	Output	$0 \text{ mV} \sim 25.5 \text{ mV} (5\text{V})$
Port Size Male - 0.11" (2.74mm) Tube Port Style Barbed Features Temperature Compensated Termination Style Surface Mount Maximum Pressure 245 PSI (1689.22 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package 6-SMT	Accuracy	±0.15%
Port Style Features Temperature Compensated Termination Style Surface Mount Maximum Pressure 245 PSI (1689.22 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package 6-SMT	Voltage - Supply	1.5 V ~ 12 V
Features Temperature Compensated Termination Style Surface Mount Maximum Pressure 245 PSI (1689.22 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package 6-SMT	Port Size	Male - 0.11" (2.74mm) Tube
Termination Style Surface Mount Maximum Pressure 245 PSI (1689.22 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package 6-SMT	Port Style	Barbed
Maximum Pressure 245 PSI (1689.22 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package 6-SMT	Features	Temperature Compensated
Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package 6-SMT	Termination Style	Surface Mount
Package / Case 6-SMD, No Lead, Top Port Supplier Device Package 6-SMT	Maximum Pressure	245 PSI (1689.22 kPa)
Supplier Device Package 6-SMT	Operating Temperature	-40°C ~ 125°C
	Package / Case	6-SMD, No Lead, Top Port
Report errors?	Supplier Device Package	6-SMT
		Report errors?

TBPLANN100PGUCV Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TBPLANN100PGUCV Payment Methods





















TBPLANN100PGUCV Shipping Methods













If you have any question about TBPLANN100PGUCV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com