

TBPLLNS001PGUCV

TBPLLNS001PGUCV Information



For Reference Only

Part Number TBPLLNS001PGUCV

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

DescriptionSENSOR PRESSURE GAUGE**Package**6-SMD, No Lead, Top Port

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TBPLLNS001PGUCV Specifications

Manufacturer Part Number TBPLLNS001PGUCV Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package 6-SMD, No Lead, Top Port Series TBP Pressure Type Vented Gauge Operating Pressure 1 PSI (6.89 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 7.5 mV (5V) Accuracy ±0.2% Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features Temperature Compensated Termination Style Surface Mount Maximum Pressure 12.7 PSI (87.56 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package 6-SMT		
Category Sensors, Transducers Pressure Sensors, Transducers Package 6-SMD, No Lead, Top Port Series TBP Pressure Type Vented Gauge Operating Pressure 1 PSI (6.89 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 7.5 mV (5V) Accuracy ±0.2% Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features Tempination Style Maximum Pressure 12.7 PSI (87.56 kPa) Operating Temperature 40°C ~ 125°C Package / Case Supplier Device Package 6-SMT	Manufacturer Part Number	TBPLLNS001PGUCV
Package 6-SMD, No Lead, Top Port Series TBP Pressure Type Vented Gauge Operating Pressure 1 PSI (6.89 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 7.5 mV (5V) Accuracy ±0.2% Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features Temperature Compensated Termination Style Surface Mount Maximum Pressure 12.7 PSI (87.56 kPa) Operating Temperature — 40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Sure Port Small P	Manufacturer	Honeywell Sensing and Productivity Solutions
Package6-SMD, No Lead, Top PortSeriesTBPPressure TypeVented GaugeOperating Pressure1 PSI (6.89 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 7.5 mV (5V)Accuracy±0.2%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StyleSurface MountMaximum Pressure12.7 PSI (87.56 kPa)Operating Temperature-40°C ~ 125°CPackage / Case6-SMD, No Lead, Top PortSupplier Device Package6-SMT	Category	Sensors, Transducers
SeriesTBPPressure TypeVented GaugeOperating Pressure1 PSI (6.89 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 7.5 mV (5V)Accuracy±0.2%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StyleSurface MountMaximum Pressure12.7 PSI (87.56 kPa)Operating Temperature-40°C ~ 125°CPackage / Case6-SMD, No Lead, Top PortSupplier Device Package6-SMT		Pressure Sensors, Transducers
Pressure TypeVented GaugeOperating Pressure1 PSI (6.89 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 7.5 mV (5V)Accuracy±0.2%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StyleSurface MountMaximum Pressure12.7 PSI (87.56 kPa)Operating Temperature-40°C ~ 125°CPackage / Case6-SMD, No Lead, Top PortSupplier Device Package6-SMT	Package	6-SMD, No Lead, Top Port
Operating Pressure Output Type Wheatstone Bridge Output OmV ~ 7.5 mV (5V) Accuracy ±0.2% Voltage - Supply Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features Temperature Compensated Termination Style Surface Mount Maximum Pressure 12.7 PSI (87.56 kPa) Operating Temperature -40°C ~ 125°C Package / Case Supplier Device Package 6-SMT	Series	TBP
Output TypeWheatstone BridgeOutput0 mV ~ 7.5 mV (5V)Accuracy±0.2%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StyleSurface MountMaximum Pressure12.7 PSI (87.56 kPa)Operating Temperature-40°C ~ 125°CPackage / Case6-SMD, No Lead, Top PortSupplier Device Package6-SMT	Pressure Type	Vented Gauge
Output $0 \text{ mV} \sim 7.5 \text{ mV} (5\text{V})$ Accuracy $\pm 0.2\%$ Voltage - Supply $1.5 \text{ V} \sim 12 \text{ V}$ Port Size $Male - 0.13'' (3.18 \text{mm})$ Tube Port Style $Barbless$ Features $Temperature Compensated$ Termination Style $Surface Mount$ Maximum Pressure $12.7 \text{ PSI} (87.56 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case 6-SMD , No Lead, Top Port Supplier Device Package 6-SMT	Operating Pressure	1 PSI (6.89 kPa)
Accuracy $\pm 0.2\%$ Voltage - Supply $1.5 \text{ V} \sim 12 \text{ V}$ Port SizeMale - 0.13 " (3.18 mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StyleSurface MountMaximum Pressure $12.7 \text{ PSI } (87.56 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case 6-SMD , No Lead, Top PortSupplier Device Package 6-SMT	Output Type	Wheatstone Bridge
Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features Temperature Compensated Termination Style Surface Mount Maximum Pressure 12.7 PSI (87.56 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package 6-SMT	Output	$0 \text{ mV} \sim 7.5 \text{ mV} (5\text{V})$
Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features Temperature Compensated Termination Style Surface Mount Maximum Pressure 12.7 PSI (87.56 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package 6-SMT	Accuracy	±0.2%
Port Style Barbless Features Temperature Compensated Termination Style Surface Mount Maximum Pressure 12.7 PSI (87.56 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package 6-SMT	Voltage - Supply	1.5 V ~ 12 V
Features Temperature Compensated Termination Style Surface Mount Maximum Pressure 12.7 PSI (87.56 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package 6-SMT	Port Size	Male - 0.13" (3.18mm) Tube
Termination Style Surface Mount Maximum Pressure 12.7 PSI (87.56 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package 6-SMT	Port Style	Barbless
Maximum Pressure 12.7 PSI (87.56 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package 6-SMT	Features	Temperature Compensated
Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package 6-SMT	Termination Style	Surface Mount
Package / Case 6-SMD, No Lead, Top Port Supplier Device Package 6-SMT	Maximum Pressure	12.7 PSI (87.56 kPa)
Supplier Device Package 6-SMT	Operating Temperature	-40°C ~ 125°C
	Package / Case	6-SMD, No Lead, Top Port
Report errors?	Supplier Device Package	6-SMT
		Report errors?

TBPLLNS001PGUCV Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TBPLLNS001PGUCV Payment Methods



















TBPLLNS001PGUCV Shipping Methods













If you have any question about TBPLLNS001PGUCV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com