



#### TC122-JR-07470KL Information



For Reference Only

Part Number TC122-JR-07470KL

**Manufacturer** Yageo **Category** Resistors

Resistor Networks, Arrays

**Description** RES ARRAY 2 RES 470K OHM 0404

Package 0404 (1010 Metric), Concave

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## TC122-JR-07470KL Specifications

Manufacturer Part Number         TC122-IR-07470KL           Manufacturer         Yageo           Category         Resistors           Package         0404 (1010 Metric), Concave           Series         TC122           Circuit Type         Isolated           Resistance (Ohms)         470k           Tolerance         ±5%           Number of Resistors         2           Number of Pins         4           Power Per Element         62.5mW           Temperature Coefficient         ±200ppm/°C           Operating Temperature         -55°C ~ 125°C           Applications         DDRAM, SDRAM           Mounting Type         Surface Mount           Package / Case         0404 (1010 Metric), Concave           Supplier Device Package         -           Size / Dimension         0.039" L x 0.039" W (1.00mm x 1.00mm)           Height - Seated (Max)         0.016" (0.40mm)		
Category         Resistors           Resistor Networks, Arrays           Package         0404 (1010 Metric), Concave           Series         TC122           Circuit Type         Isolated           Resistance (Ohms)         470k           Tolerance         ±5%           Number of Resistors         2           Number of Pins         4           Power Per Element         62.5mW           Temperature Coefficient         ±200ppm/°C           Operating Temperature         -55°C ~ 125°C           Applications         DDRAM, SDRAM           Mounting Type         Surface Mount           Package / Case         0404 (1010 Metric), Concave           Supplier Device Package         -           Size / Dimension         0.039" L x 0.039" W (1.00mm x 1.00mm)           Height - Seated (Max)         0.016" (0.40mm)	Manufacturer Part Number	TC122-JR-07470KL
Resistor Networks, Arrays           Package         0404 (1010 Metric), Concave           Series         TC122           Circuit Type         Isolated           Resistance (Ohms)         470k           Tolerance         ±5%           Number of Resistors         2           Number of Pins         4           Power Per Element         62.5mW           Temperature Coefficient         ±200ppm/°C           Operating Temperature         -55°C ~ 125°C           Applications         DDRAM, SDRAM           Mounting Type         Surface Mount           Package / Case         0404 (1010 Metric), Concave           Supplier Device Package         -           Size / Dimension         0.039" L x 0.039" W (1.00mm x 1.00mm)           Height - Seated (Max)         0.016" (0.40mm)	Manufacturer	Yageo
Package         0404 (1010 Metric), Concave           Series         TC122           Circuit Type         Isolated           Resistance (Ohms)         470k           Tolerance         ±5%           Number of Resistors         2           Number of Pins         4           Power Per Element         62.5mW           Temperature Coefficient         ±200ppm/°C           Operating Temperature         -55°C ~ 125°C           Applications         DDRAM, SDRAM           Mounting Type         Surface Mount           Package / Case         0404 (1010 Metric), Concave           Supplier Device Package         -           Size / Dimension         0.039" L x 0.039" W (1.00mm x 1.00mm)           Height - Seated (Max)         0.016" (0.40mm)	Category	Resistors
Series         TC122           Circuit Type         Isolated           Resistance (Ohms)         470k           Tolerance         ±5%           Number of Resistors         2           Number of Pins         4           Power Per Element         62.5mW           Temperature Coefficient         ±200ppm/°C           Operating Temperature         -55°C ~ 125°C           Applications         DDRAM, SDRAM           Mounting Type         Surface Mount           Package / Case         0404 (1010 Metric), Concave           Supplier Device Package         -           Size / Dimension         0.039" L x 0.039" W (1.00mm x 1.00mm)           Height - Seated (Max)         0.016" (0.40mm)		Resistor Networks, Arrays
Circuit Type Isolated Resistance (Ohms) 470k  Tolerance ±5%  Number of Resistors 2  Number of Pins 4  Power Per Element 62.5mW  Temperature Coefficient ±200ppm/°C  Operating Temperature -55°C ~ 125°C  Applications DDRAM, SDRAM  Mounting Type Surface Mount  Package / Case 0404 (1010 Metric), Concave  Supplier Device Package  Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm)  Height - Seated (Max) 0.016" (0.40mm)	Package	0404 (1010 Metric), Concave
Resistance (Ohms)  Tolerance  ±5%  Number of Resistors  2  Number of Pins  4  Power Per Element  62.5mW  Temperature Coefficient  ±200ppm/°C  Operating Temperature  -55°C ~ 125°C  Applications  DDRAM, SDRAM  Mounting Type  Surface Mount  Package / Case  0404 (1010 Metric), Concave  Supplier Device Package  Size / Dimension  0.039" L x 0.039" W (1.00mm x 1.00mm)  Height - Seated (Max)  0.016" (0.40mm)	Series	TC122
Tolerance ±5%  Number of Resistors 2  Number of Pins 4  Power Per Element 62.5mW  Temperature Coefficient ±200ppm/°C  Operating Temperature -55°C ~ 125°C  Applications DDRAM, SDRAM  Mounting Type Surface Mount  Package / Case 0404 (1010 Metric), Concave  Supplier Device Package  Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm)  Height - Seated (Max) 0.016" (0.40mm)	Circuit Type	Isolated
Number of Resistors  2 Number of Pins  4 Power Per Element  62.5mW  Temperature Coefficient  200ppm/°C  Operating Temperature  -55°C ~ 125°C  Applications  DDRAM, SDRAM  Mounting Type  Surface Mount  Package / Case  0404 (1010 Metric), Concave  Supplier Device Package  - Size / Dimension  0.039" L x 0.039" W (1.00mm x 1.00mm)  Height - Seated (Max)  0.016" (0.40mm)	Resistance (Ohms)	470k
Number of Pins 4  Power Per Element 62.5mW  Temperature Coefficient ±200ppm/°C  Operating Temperature -55°C ~ 125°C  Applications DDRAM, SDRAM  Mounting Type Surface Mount  Package / Case 0404 (1010 Metric), Concave  Supplier Device Package -  Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm)  Height - Seated (Max) 0.016" (0.40mm)	Tolerance	±5%
Power Per Element  Emperature Coefficient  ±200ppm/°C  Operating Temperature  -55°C ~ 125°C  Applications  DDRAM, SDRAM  Mounting Type  Surface Mount  Package / Case  0404 (1010 Metric), Concave  Supplier Device Package  -  Size / Dimension  0.039" L x 0.039" W (1.00mm x 1.00mm)  Height - Seated (Max)  0.016" (0.40mm)	Number of Resistors	2
Temperature Coefficient ±200ppm/°C  Operating Temperature -55°C ~ 125°C  Applications DDRAM, SDRAM  Mounting Type Surface Mount  Package / Case 0404 (1010 Metric), Concave  Supplier Device Package  Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm)  Height - Seated (Max) 0.016" (0.40mm)	Number of Pins	4
Operating Temperature  -55°C ~ 125°C  Applications  DDRAM, SDRAM  Mounting Type  Surface Mount  Package / Case  0404 (1010 Metric), Concave  Supplier Device Package  - Size / Dimension  0.039" L x 0.039" W (1.00mm x 1.00mm)  Height - Seated (Max)  0.016" (0.40mm)	Power Per Element	62.5mW
Applications DDRAM, SDRAM  Mounting Type Surface Mount  Package / Case 0404 (1010 Metric), Concave  Supplier Device Package - Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm)  Height - Seated (Max) 0.016" (0.40mm)	Temperature Coefficient	±200ppm/°C
Mounting Type Surface Mount Package / Case 0404 (1010 Metric), Concave Supplier Device Package - Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm) Height - Seated (Max) 0.016" (0.40mm)	Operating Temperature	-55°C ~ 125°C
Package / Case       0404 (1010 Metric), Concave         Supplier Device Package       -         Size / Dimension       0.039" L x 0.039" W (1.00mm x 1.00mm)         Height - Seated (Max)       0.016" (0.40mm)	Applications	DDRAM, SDRAM
Supplier Device Package - Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm) Height - Seated (Max) 0.016" (0.40mm)	Mounting Type	Surface Mount
Size / Dimension       0.039" L x 0.039" W (1.00mm x 1.00mm)         Height - Seated (Max)       0.016" (0.40mm)	Package / Case	0404 (1010 Metric), Concave
Height - Seated (Max) 0.016" (0.40mm)	Supplier Device Package	-
	Size / Dimension	0.039" L x 0.039" W (1.00mm x 1.00mm)
Report errors?	Height - Seated (Max)	0.016" (0.40mm)
		Report errors?

#### TC122-JR-07470KL Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### TC122-JR-07470KL Payment Methods





















# TC122-JR-07470KL Shipping Methods













If you have any question about TC122-JR-07470KL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com