



TC164-FR-0712KL Information

Part Number TC164-FR-0712KL

Manufacturer Yageo **Category** Resistors

Resistor Networks, Arrays

Description RES ARRAY 4 RES 12K OHM 1206

Package 1206 (3216 Metric), Concave, Long Side Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TC164-FR-0712KL Specifications

Manufacturer Part Number TC164-FR-0712KL Manufacturer Yageo Category Resistors Package 1206 (3216 Metric), Concave, Long Side Terminals Series TC164 Circuit Type Isolated Resistance (Ohms) 12k Tolerance ±1% Number of Resistors 4 Number of Pins 8 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package - Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.028" (0.70mm)		
Category Resistors Resistor Networks, Arrays Package 1206 (3216 Metric), Concave, Long Side Terminals Series TC164 Circuit Type Isolated Resistance (Ohms) 12k Tolerance ±1% Number of Resistors 4 Number of Pins 8 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package - Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.028" (0.70mm)	Manufacturer Part Number	TC164-FR-0712KL
Resistor Networks, ArraysPackage1206 (3216 Metric), Concave, Long Side TerminalsSeriesTC164Circuit TypeIsolatedResistance (Ohms)12kTolerance±1%Number of Resistors4Number of Pins8Power Per Element62.5mWTemperature Coefficient±200ppm/°COperating Temperature-55°C ~ 155°CApplicationsDDRAM, SDRAMMounting TypeSurface MountPackage / Case1206 (3216 Metric), Concave, Long Side TerminalsSupplier Device Package-Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.028" (0.70mm)	Manufacturer	Yageo
Package 1206 (3216 Metric), Concave, Long Side Terminals Series TC164 Circuit Type Isolated Resistance (Ohms) 12k Tolerance ±1% Number of Resistors 4 Number of Pins 8 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package - Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.028" (0.70mm)	Category	Resistors
SeriesTC164Circuit TypeIsolatedResistance (Ohms)12kTolerance±1%Number of Resistors4Number of Pins8Power Per Element62.5mWTemperature Coefficient±200ppm/°COperating Temperature-55°C ~ 155°CApplicationsDDRAM, SDRAMMounting TypeSurface MountPackage / Case1206 (3216 Metric), Concave, Long Side TerminalsSupplier Device Package-Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.028" (0.70mm)		Resistor Networks, Arrays
Circuit Type Isolated Resistance (Ohms) 12k Tolerance ±1% Number of Resistors 4 Number of Pins 8 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.028" (0.70mm)	Package	1206 (3216 Metric), Concave, Long Side Terminals
Resistance (Ohms) 12k Tolerance ±1% Number of Resistors 4 Number of Pins 8 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.028" (0.70mm)	Series	TC164
Tolerance ±1% Number of Resistors 4 Number of Pins 8 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package - Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.028" (0.70mm)	Circuit Type	Isolated
Number of Resistors A Number of Pins B Rower Per Element 62.5mW Temperature Coefficient -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.028" (0.70mm)	Resistance (Ohms)	12k
Number of Pins Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package - Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.028" (0.70mm)	Tolerance	±1%
Power Per Element femperature Coefficient femperature Coefficient femperature f	Number of Resistors	4
Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package - Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.028" (0.70mm)	Number of Pins	8
Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package - Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.028" (0.70mm)	Power Per Element	62.5mW
Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package - Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.028" (0.70mm)	Temperature Coefficient	±200ppm/°C
Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package - Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.028" (0.70mm)	Operating Temperature	-55°C ~ 155°C
Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package - Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.028" (0.70mm)	Applications	DDRAM, SDRAM
Supplier Device Package - Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.028" (0.70mm)	Mounting Type	Surface Mount
Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.028" (0.70mm)	Package / Case	1206 (3216 Metric), Concave, Long Side Terminals
Height - Seated (Max) 0.028" (0.70mm)	Supplier Device Package	-
	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)
Report errors?	Height - Seated (Max)	0.028" (0.70mm)
		Report errors?

TC164-FR-0712KL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TC164-FR-0712KL Payment Methods



















TC164-FR-0712KL Shipping Methods













If you have any question about TC164-FR-0712KL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com