



#### TC4425AVMF713 Information



For Reference Only

Part Number TC4425AVMF713

Manufacturer Microchip Technology

Category Integrated Circuits (ICs)
PMIC - Gate Drivers

**Description** IC MOSFET DVR 3A DUAL HS 8DFN

Package 8-VDFN Exposed Pad

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **TC4425AVMF713 Specifications**

Manufacturer Part NumberTC4425AVMF713ManufacturerMicrochip TechnologyCategoryIntegrated Circuits (ICs)PMIC - Gate DriversPackage8-VDFN Exposed PadSeries-Driven ConfigurationLow-SideChannel TypeIndependentNumber of Drivers2Gate TypeN-Channel, P-Channel MOSFETVoltage - Supply4.5 V ~ 18 VLogic Voltage - VIL, VIH0.8V, 2.4VCurrent - Peak Output (Source, Sink)4.5A, 4.5AInput TypeInverting, Non-InvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)12ns, 12nsOperating Temperature-40°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-VDFN Exposed PadSupplier Device Package8-DFN-S (6x5)		
CategoryIntegrated Circuits (ICs)Package8-VDFN Exposed PadSeries-Driven ConfigurationLow-SideChannel TypeIndependentNumber of Drivers2Gate TypeN-Channel, P-Channel MOSFETVoltage - Supply4.5 V ~ 18 VLogic Voltage - VIL, VIH0.8V, 2.4VCurrent - Peak Output (Source, Sink)4.5A, 4.5AInput TypeInverting, Non-InvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)12ns, 12nsOperating Temperature-40°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-VDFN Exposed PadSupplier Device Package8-DFN-S (6x5)	Manufacturer Part Number	TC4425AVMF713
Package 8-VDFN Exposed Pad  Series - Driven Configuration Low-Side Channel Type Independent Number of Drivers 2 Gate Type N-Channel, P-Channel MOSFET  Voltage - Supply 4.5 V ~ 18 V  Logic Voltage - VIL, VIH 0.8V, 2.4V  Current - Peak Output (Source, Sink) 4.5A, 4.5A  Input Type Inverting, Non-Inverting  High Side Voltage - Max (Bootstrap) - Rise / Fall Time (Typ) 12ns, 12ns  Operating Temperature -40°C ~ 150°C (TJ)  Mounting Type Surface Mount  Mounting Type Surface Mount  Package / Case 8-VDFN Exposed Pad  Supplier Device Package 8-DFN-S (6x5)	Manufacturer	Microchip Technology
Package8-VDFN Exposed PadSeries-Driven ConfigurationLow-SideChannel TypeIndependentNumber of Drivers2Gate TypeN-Channel, P-Channel MOSFETVoltage - Supply4.5 V ~ 18 VLogic Voltage - VIL, VIH0.8V, 2.4VCurrent - Peak Output (Source, Sink)4.5A, 4.5AInput TypeInverting, Non-InvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)12ns, 12nsOperating Temperature-40°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-VDFN Exposed PadSupplier Device Package8-DFN-S (6x5)	Category	Integrated Circuits (ICs)
Series-Driven ConfigurationLow-SideChannel TypeIndependentNumber of Drivers2Gate TypeN-Channel, P-Channel MOSFETVoltage - Supply4.5 V ~ 18 VLogic Voltage - VIL, VIH0.8V, 2.4VCurrent - Peak Output (Source, Sink)4.5A, 4.5AInput TypeInverting, Non-InvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)12ns, 12nsOperating Temperature-40°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-VDFN Exposed PadSupplier Device Package8-DFN-S (6x5)		PMIC - Gate Drivers
Driven Configuration  Channel Type  Independent  Number of Drivers  2  Gate Type  N-Channel, P-Channel MOSFET  Voltage - Supply  Logic Voltage - VIL, VIH  Current - Peak Output (Source, Sink)  Input Type  Inverting, Non-Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  Operating Temperature  -40°C ~ 150°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-VDFN Exposed Pad  Supplier Device Package	Package	8-VDFN Exposed Pad
Channel Type Number of Drivers 2 Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4.5 V ~ 18 V Logic Voltage - VIL, VIH 0.8V, 2.4V Current - Peak Output (Source, Sink) Input Type Inverting, Non-Inverting High Side Voltage - Max (Bootstrap) -Rise / Fall Time (Typ) 12ns, 12ns Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-VDFN Exposed Pad Supplier Device Package 8-DFN-S (6x5)	Series	-
Number of Drivers  Gate Type  N-Channel, P-Channel MOSFET  Voltage - Supply  4.5 V ~ 18 V  Logic Voltage - VIL, VIH  0.8V, 2.4V  Current - Peak Output (Source, Sink)  Input Type  Inverting, Non-Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  Operating Temperature  -40°C ~ 150°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-VDFN Exposed Pad  Supplier Device Package	Driven Configuration	Low-Side
Gate Type  N-Channel, P-Channel MOSFET  Voltage - Supply  4.5 V ~ 18 V  Logic Voltage - VIL, VIH  0.8V, 2.4V  Current - Peak Output (Source, Sink)  Input Type  Inverting, Non-Inverting  High Side Voltage - Max (Bootstrap)	Channel Type	Independent
Voltage - Supply  Logic Voltage - VIL, VIH  0.8V, 2.4V  Current - Peak Output (Source, Sink)  Input Type  Inverting, Non-Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  12ns, 12ns  Operating Temperature  -40°C ~ 150°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-VDFN Exposed Pad  Supplier Device Package	Number of Drivers	2
Logic Voltage - VIL, VIH  O.8V, 2.4V  Current - Peak Output (Source, Sink)  Input Type  Inverting, Non-Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  Operating Temperature  -40°C ~ 150°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-VDFN Exposed Pad  Supplier Device Package  8-DFN-S (6x5)	Gate Type	N-Channel, P-Channel MOSFET
Current - Peak Output (Source, Sink)  Input Type  Inverting, Non-Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  Operating Temperature  -40°C ~ 150°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-VDFN Exposed Pad  Supplier Device Package  8-DFN-S (6x5)	Voltage - Supply	4.5 V ~ 18 V
Input Type  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  12ns, 12ns  Operating Temperature  -40°C ~ 150°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-VDFN Exposed Pad  Supplier Device Package  8-DFN-S (6x5)	Logic Voltage - VIL, VIH	0.8V, 2.4V
High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  12ns, 12ns  Operating Temperature  -40°C ~ 150°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-VDFN Exposed Pad  Supplier Device Package  8-DFN-S (6x5)	Current - Peak Output (Source, Sink)	4.5A, 4.5A
Rise / Fall Time (Typ)  12ns, 12ns  Operating Temperature  -40°C ~ 150°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-VDFN Exposed Pad  Supplier Device Package  8-DFN-S (6x5)	Input Type	Inverting, Non-Inverting
Operating Temperature  -40°C ~ 150°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-VDFN Exposed Pad  Supplier Device Package  8-DFN-S (6x5)	High Side Voltage - Max (Bootstrap)	-
Mounting Type Surface Mount Package / Case 8-VDFN Exposed Pad Supplier Device Package 8-DFN-S (6x5)	Rise / Fall Time (Typ)	12ns, 12ns
Package / Case 8-VDFN Exposed Pad Supplier Device Package 8-DFN-S (6x5)	Operating Temperature	-40°C ~ 150°C (TJ)
Supplier Device Package 8-DFN-S (6x5)	Mounting Type	Surface Mount
	Package / Case	8-VDFN Exposed Pad
Report errors?	Supplier Device Package	8-DFN-S (6x5)
		Report errors?

#### **TC4425AVMF713 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **TC4425AVMF713 Payment Methods**



















### **TC4425AVMF713 Shipping Methods**













If you have any question about TC4425AVMF713, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com