



TC4427ACOA Information



For Reference Only

Part Number TC4427ACOA

Manufacturer Microchip Technology

Category Integrated Circuits (ICs)
PMIC - Gate Drivers

Description IC MOSFET DVR 1.5A DUAL HS 8SOIC

Package 8-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TC4427ACOA Specifications

Manufacturer Part Number TC4427ACOA Manufacturer Microchip Technology Category Integrated Circuits (ICs) PACKAGE 8-SOIC (0.154", 3.90mm Width) Series - Driven Configuration Low-Side Channel Type Independent Number of Drivers 2 Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4.5 V ~ 18 V Logic Voltage - VIL, VIH 0.8V, 2.4V Current - Peak Output (Source, Sink) 1.5A, 1.5A Input Type Non-Inverting High Side Voltage - Max (Bootstrap) - Rise / Fall Time (Typ) 25ns, 25ns Operating Temperature 0°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC		
CategoryIntegrated Circuits (ICs)PMIC - Gate DriversPackage8-SOIC (0.154", 3.90mm Width)Series-Driven ConfigurationLow-SideChannel TypeIndependentNumber of Drivers2Gate TypeN-Channel, P-Channel MOSFETVoltage - Supply4.5 V ~ 18 VLogic Voltage - VIL, VIH0.8V, 2.4VCurrent - Peak Output (Source, Sink)1.5A, 1.5AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)25ns, 25nsOperating Temperature0°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Manufacturer Part Number	TC4427ACOA
Package 8-SOIC (0.154", 3.90mm Width) Series - Driven Configuration Low-Side Channel Type Independent Number of Drivers 2 Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4.5 V ~ 18 V Logic Voltage - VIL, VIH 0.8V, 2.4V Current - Peak Output (Source, Sink) 1.5A, 1.5A Input Type Non-Inverting High Side Voltage - Max (Bootstrap) - Rise / Fall Time (Typ) 25ns, 25ns Operating Temperature 0°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Manufacturer	Microchip Technology
Package8-SOIC (0.154", 3.90mm Width)Series-Driven ConfigurationLow-SideChannel TypeIndependentNumber of Drivers2Gate TypeN-Channel, P-Channel MOSFETVoltage - Supply4.5 V ~ 18 VLogic Voltage - VIL, VIH0.8V, 2.4VCurrent - Peak Output (Source, Sink)1.5A, 1.5AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)25ns, 25nsOperating Temperature0°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Category	Integrated Circuits (ICs)
Series-Driven ConfigurationLow-SideChannel TypeIndependentNumber of Drivers2Gate TypeN-Channel, P-Channel MOSFETVoltage - Supply4.5 V ~ 18 VLogic Voltage - VIL, VIH0.8V, 2.4VCurrent - Peak Output (Source, Sink)1.5A, 1.5AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)25ns, 25nsOperating Temperature0°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC		PMIC - Gate Drivers
Driven Configuration Channel Type Independent Number of Drivers 2 Gate Type N-Channel, P-Channel MOSFET Voltage - Supply Logic Voltage - VIL, VIH Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Package	8-SOIC (0.154", 3.90mm Width)
Channel Type Number of Drivers 2 Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4.5 V ~ 18 V Logic Voltage - VIL, VIH 0.8V, 2.4V Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) - Rise / Fall Time (Typ) 25ns, 25ns Operating Temperature 0°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Series	-
Number of Drivers Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4.5 V ~ 18 V Logic Voltage - VIL, VIH 0.8V, 2.4V Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature 0°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Driven Configuration	Low-Side
Gate TypeN-Channel, P-Channel MOSFETVoltage - Supply4.5 V ~ 18 VLogic Voltage - VIL, VIH0.8V, 2.4VCurrent - Peak Output (Source, Sink)1.5A, 1.5AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)25ns, 25nsOperating Temperature0°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Channel Type	Independent
Voltage - Supply Logic Voltage - VIL, VIH 0.8V, 2.4V Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature 0°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Number of Drivers	2
Logic Voltage - VIL, VIH Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature O°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Gate Type	N-Channel, P-Channel MOSFET
Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature O°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Voltage - Supply	4.5 V ~ 18 V
Input Type High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature O°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Logic Voltage - VIL, VIH	0.8V, 2.4V
High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) 25ns, 25ns Operating Temperature 0°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Current - Peak Output (Source, Sink)	1.5A, 1.5A
Rise / Fall Time (Typ) 25ns, 25ns Operating Temperature 0°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Input Type	Non-Inverting
Operating Temperature0°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	High Side Voltage - Max (Bootstrap)	-
Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Rise / Fall Time (Typ)	25ns, 25ns
Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Operating Temperature	0°C ~ 150°C (TJ)
Supplier Device Package 8-SOIC	Mounting Type	Surface Mount
	Package / Case	8-SOIC (0.154", 3.90mm Width)
Report errors?	Supplier Device Package	8-SOIC
		Report errors?

TC4427ACOA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TC4427ACOA Payment Methods



















TC4427ACOA Shipping Methods













If you have any question about TC4427ACOA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com