

TC74A0-5.0VAT

TC74A0-5.0VAT Information



Number	TC74A0-5.0VAT
ufacturer	Microchip Technology
gory	Sensors, Transducers Temperature Sensors, Transducers
ription	SENSOR TEMP I2C/SMBUS TO220-5
age	TO-220-5
	For the pricing/inventory/lead time, please contact us
	Website: https://www.heisener.com
	E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



TC74A0-5.0VAT Specifications

Manufacturer Part NumberTC74A0-5.0VATManufacturerMicrochip TechnologyCategorySensors, TransducersCategoryTemperature Sensors, TransducersPackageTO-220-5Series-Sensor TypeDigital, LocalSensing Temperature - Local-40°C ~ 125°CSensing Temperature - Remote-Output TypeI2C/SMBusVoltage - Supply2.7 V ~ 5.5 VResolution7bFeaturesStandby ModeAccuracy - Highest (Lowest)±2°C (±3°C)Test Condition25°C ~ 85°C (0°C ~ 125°C)Operating Temperature-40°C ~ 125°CMounting TypeThrough Hole	
CategorySensors, TransducersCategorySensors, TransducersTemperature Sensors, TransducersPackageTO-220-5Series-Sensor TypeDigital, LocalSensing Temperature - Local-40°C ~ 125°CSensing Temperature - Remote-Output TypeI2C/SMBusVoltage - Supply2.7 V ~ 5.5 VResolution7 bFeaturesStandby ModeAccuracy - Highest (Lowest)±2°C (±3°C)Test Condition25°C ~ 85°C (0°C ~ 125°C)Operating Temperature-40°C ~ 125°C	
Temperature Sensors, TransducersPackageTO-220-5Series-Sensor TypeDigital, LocalSensing Temperature - Local $-40^{\circ}C \sim 125^{\circ}C$ Sensing Temperature - Remote-Output TypeI2C/SMBusVoltage - Supply $2.7 V \sim 5.5 V$ Resolution $7 b$ FeaturesStandby ModeAccuracy - Highest (Lowest) $\pm 2^{\circ}C (\pm 3^{\circ}C)$ Test Condition $25^{\circ}C \sim 85^{\circ}C (0^{\circ}C \sim 125^{\circ}C)$ Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$	
PackageTO-220-5Series-Sensor TypeDigital, LocalSensing Temperature - Local-40°C ~ 125°CSensing Temperature - Remote-Output TypeI2C/SMBusVoltage - Supply2.7 V ~ 5.5 VResolution7 bFeaturesStandby ModeAccuracy - Highest (Lowest)±2°C (±3°C)Test Condition25°C ~ 85°C (0°C ~ 125°C)Operating Temperature-40°C ~ 125°C	
Series-Sensor TypeDigital, LocalSensing Temperature - Local-40°C ~ 125°CSensing Temperature - Remote-Output TypeI2C/SMBusVoltage - Supply2.7 V ~ 5.5 VResolution7 bFeaturesStandby ModeAccuracy - Highest (Lowest)±2°C (±3°C)Test Condition25°C ~ 85°C (0°C ~ 125°C)Operating Temperature-40°C ~ 125°C	
Sensor TypeDigital, LocalSensing Temperature - Local-40°C ~ 125°CSensing Temperature - Remote-Output TypeI2C/SMBusVoltage - Supply2.7 V ~ 5.5 VResolution7 bFeaturesStandby ModeAccuracy - Highest (Lowest)±2°C (±3°C)Test Condition25°C ~ 85°C (0°C ~ 125°C)Operating Temperature-40°C ~ 125°C	
Sensing Temperature - Local $-40^{\circ}C \sim 125^{\circ}C$ Sensing Temperature - Remote-Output TypeI2C/SMBusVoltage - Supply $2.7 V \sim 5.5 V$ Resolution $7 b$ FeaturesStandby ModeAccuracy - Highest (Lowest) $\pm 2^{\circ}C (\pm 3^{\circ}C)$ Test Condition $25^{\circ}C \sim 85^{\circ}C (0^{\circ}C \sim 125^{\circ}C)$ Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$	
Sensing Temperature - Remote-Output TypeI2C/SMBusVoltage - Supply2.7 V ~ 5.5 VResolution7 bFeaturesStandby ModeAccuracy - Highest (Lowest)±2°C (±3°C)Test Condition25°C ~ 85°C (0°C ~ 125°C)Operating Temperature-40°C ~ 125°C	
Output Type I2C/SMBus Voltage - Supply $2.7 V \sim 5.5 V$ Resolution $7 b$ Features Standby Mode Accuracy - Highest (Lowest) $\pm 2^{\circ}C (\pm 3^{\circ}C)$ Test Condition $25^{\circ}C \sim 85^{\circ}C (0^{\circ}C \sim 125^{\circ}C)$ Operating Temperature $40^{\circ}C \sim 125^{\circ}C$	
Voltage - Supply $2.7 V \sim 5.5 V$ Resolution $7 b$ Features Standby Mode Accuracy - Highest (Lowest) $\pm 2^{\circ}C (\pm 3^{\circ}C)$ Test Condition $25^{\circ}C \sim 85^{\circ}C (0^{\circ}C \sim 125^{\circ}C)$ Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$	
Resolution7 bFeaturesStandby ModeAccuracy - Highest (Lowest) $\pm 2^{\circ}C (\pm 3^{\circ}C)$ Test Condition $25^{\circ}C \sim 85^{\circ}C (0^{\circ}C \sim 125^{\circ}C)$ Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$	
FeaturesStandby ModeAccuracy - Highest (Lowest)±2°C (±3°C)Test Condition25°C ~ 85°C (0°C ~ 125°C)Operating Temperature-40°C ~ 125°C	
Accuracy - Highest (Lowest) $\pm 2^{\circ}C (\pm 3^{\circ}C)$ Test Condition $25^{\circ}C \sim 85^{\circ}C (0^{\circ}C \sim 125^{\circ}C)$ Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$	
Test Condition $25^{\circ}C \sim 85^{\circ}C (0^{\circ}C \sim 125^{\circ}C)$ Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$	
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	
Mounting Type Through Hole	
Package / Case TO-220-5	
Supplier Device Package TO-220-5	
Repo	rt errors?

TC74A0-5.0VAT Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE UARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

TC74A0-5.0VAT Payment Methods





If you have any question about TC74A0-5.0VAT, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com