

TCF40 Information



For Reference Only

Part Number TCF40 Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE RECT 40A 600VAC/300DC BLADE

Package Blade Type, Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TCF40 Specifications

Manufacturer Part Number TCF40 Manufacturer Eaton Category Circuit Protection Package Blade Type, Module Series CUBEFuse? TCF Fuse Type Rectangular Current Rating 40A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features Indicating Class - Approvals CE, CSA, UL Operating Temperature -40°C ~ 80°C Breaking Capacity @ Rated Voltage 300kA AC, 100kA DC Mounting Type Holder Package / Case Blade Type, Module Size / Dimension 1.880" L x 0.750" W x 1.270" H (47.75mm x 19.05mm x 32.26mm) Report errors?		
CategoryCircuit ProtectionPackageBlade Type, ModuleSeriesCUBEFuse? TCFFuse TypeRectangularCurrent Rating40AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, ULOperating Temperature-40°C ~ 80°CBreaking Capacity @ Rated Voltage300kA AC, 100kA DCMounting TypeHolderPackage / CaseBlade Type, ModuleSize / Dimension1.880" L x 0.750" W x 1.270" H (47.75mm x 19.05mm x 32.26mm)	Manufacturer Part Number	TCF40
PackageElectrical, Specialty FusesPackageBlade Type, ModuleSeriesCUBEFuse? TCFFuse TypeRectangularCurrent Rating40AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, ULOperating Temperature-40°C ~ 80°CBreaking Capacity @ Rated Voltage300kA AC, 100kA DCMounting TypeHolderPackage / CaseBlade Type, ModuleSize / Dimension1.880" L x 0.750" W x 1.270" H (47.75mm x 19.05mm x 32.26mm)	Manufacturer	Eaton
PackageBlade Type, ModuleSeriesCUBEFuse? TCFFuse TypeRectangularCurrent Rating40AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, ULOperating Temperature-40°C ~ 80°CBreaking Capacity @ Rated Voltage300kA AC, 100kA DCMounting TypeHolderPackage / CaseBlade Type, ModuleSize / Dimension1.880" L x 0.750" W x 1.270" H (47.75mm x 19.05mm x 32.26mm)	Category	Circuit Protection
SeriesCUBEFuse? TCFFuse TypeRectangularCurrent Rating40AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, ULOperating Temperature-40°C ~ 80°CBreaking Capacity @ Rated Voltage300kA AC, 100kA DCMounting TypeHolderPackage / CaseBlade Type, ModuleSize / Dimension1.880" L x 0.750" W x 1.270" H (47.75mm x 19.05mm x 32.26mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 40A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features Indicating Class - Approvals CE, CSA, UL Operating Temperature 40°C ~ 80°C Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Rectangular 40A ADA ADA HOLD HOLD HOLD ADA Beatangular 40A ADA Bov Blade Type, Module 1.880" L x 0.750" W x 1.270" H (47.75mm x 19.05mm x 32.26mm)	Package	Blade Type, Module
Current Rating 40A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features Indicating Class - Approvals CE, CSA, UL Operating Temperature -40°C ~ 80°C Breaking Capacity @ Rated Voltage 300kA AC, 100kA DC Mounting Type Holder Package / Case Blade Type, Module Size / Dimension 1.880" L x 0.750" W x 1.270" H (47.75mm x 19.05mm x 32.26mm)	Series	CUBEFuse? TCF
Voltage Rating - AC Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Indicating Class - Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 60	Fuse Type	Rectangular
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features Indicating Class - Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Blade Type, Module Size / Dimension 300V Electrical, Industrial Electrical, Industrial Electrical, Industrial CE, CSA, UL OC, CSA, UL OPERATION OF COMMON O	Current Rating	40A
Response Time Applications Electrical, Industrial Features Indicating Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Blade Type, Module Size / Dimension Slow Electrical, Industrial Indicating CE, CSA, UL - CE, CSA, UL -40°C ~ 80°C 300kA AC, 100kA DC Holder Holder Blade Type, Module 1.880" L x 0.750" W x 1.270" H (47.75mm x 19.05mm x 32.26mm)	Voltage Rating - AC	600V
Applications Electrical, Industrial Features Indicating Class - Approvals CE, CSA, UL Operating Temperature -40°C ~ 80°C Breaking Capacity @ Rated Voltage 300kA AC, 100kA DC Mounting Type Holder Package / Case Blade Type, Module Size / Dimension 1.880" L x 0.750" W x 1.270" H (47.75mm x 19.05mm x 32.26mm)	Voltage Rating - DC	300V
Features Indicating Class - Approvals CE, CSA, UL Operating Temperature -40°C ~ 80°C Breaking Capacity @ Rated Voltage 300kA AC, 100kA DC Mounting Type Holder Package / Case Blade Type, Module Size / Dimension 1.880" L x 0.750" W x 1.270" H (47.75mm x 19.05mm x 32.26mm)	Response Time	Slow
Class Approvals CE, CSA, UL Operating Temperature -40°C ~ 80°C Breaking Capacity @ Rated Voltage 300kA AC, 100kA DC Mounting Type Holder Package / Case Blade Type, Module Size / Dimension 1.880" L x 0.750" W x 1.270" H (47.75mm x 19.05mm x 32.26mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature -40°C ~ 80°C Breaking Capacity @ Rated Voltage 300kA AC, 100kA DC Mounting Type Holder Package / Case Blade Type, Module Size / Dimension CE, CSA, UL -40°C ~ 80°C Breaking Capacity @ Rated Voltage 300kA AC, 100kA DC Holder Holder 1.880" L x 0.750" W x 1.270" H (47.75mm x 19.05mm x 32.26mm)	Features	Indicating
Operating Temperature -40°C ~ 80°C Breaking Capacity @ Rated Voltage 300kA AC, 100kA DC Mounting Type Holder Package / Case Blade Type, Module Size / Dimension 1.880" L x 0.750" W x 1.270" H (47.75mm x 19.05mm x 32.26mm)	Class	-
Breaking Capacity @ Rated Voltage 300kA AC, 100kA DC Mounting Type Holder Package / Case Blade Type, Module Size / Dimension 1.880" L x 0.750" W x 1.270" H (47.75mm x 19.05mm x 32.26mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Blade Type, Module Size / Dimension 1.880" L x 0.750" W x 1.270" H (47.75mm x 19.05mm x 32.26mm)	Operating Temperature	-40°C ~ 80°C
Package / Case Blade Type, Module Size / Dimension 1.880" L x 0.750" W x 1.270" H (47.75mm x 19.05mm x 32.26mm)	Breaking Capacity @ Rated Voltage	300kA AC, 100kA DC
Size / Dimension 1.880" L x 0.750" W x 1.270" H (47.75mm x 19.05mm x 32.26mm)	Mounting Type	Holder
	Package / Case	Blade Type, Module
Report errors?	Size / Dimension	1.880" L x 0.750" W x 1.270" H (47.75mm x 19.05mm x 32.26mm)
		Report errors?

TCF40 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TCF40 Payment Methods



















TCF40 Shipping Methods













If you have any question about TCF40, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com