

# ТСТ40-08Е07АВ

#### **TCT40-08E07AB Information**

Heisener.com Detailseverstant tere	 TCT40-08E07AB Triad Magnetics Transformers Power Transformers CHASSIS MOUNT CONTROL TRANSFORME - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### **TCT40-08E07AB** Specifications

Manufacturer Part NumberTCT40-08E07ABManufacturerTriad MagneticsCategoryTransformersPackage-PackageClass 2, TCTStriesClass 2, TCTYotge - PrimaryLaminated CoreVoltage - Secondary (Full Load)12VCurrent - Output (Max)Single, Multiple TapsSecondary Winding(s)SingleNower - MaxOvaPower - MaxSolder, Quick ConnectNouting TypeSolder, Quick ConnectSize / Dimension92.46mm L x 59.44mm WVoltage - Isolation1500 VACWeightSingle, Solder, Quick ConnectSize / DimensionSingle, Solder, Quick ConnectSize /		
CategoryTransformersPower TransformersPackagePackageSeriesClass 2, TCTTypeLaminated CoreVoltage - Primary120V, 240VVoltage - Secondary (Full Load)12VCurrent - Output (Max)3.34APrimary Winding(s)Single, Multiple TapsSecondary Winding(s)SingleCenter TapNoPower - Max40 VAMounting TypeChasis MountSize / Dimension92.46mm L x 59.44mm WSize / Dimension56.39mmVoltage - Isolation1500VACWeight1.5 lbs (680.4g)	Manufacturer Part Number	TCT40-08E07AB
InterfactPower TransformersPackage-SeriesClass 2, TCTTypeLaminated CoreVoltage - Primary120V, 240VVoltage - Secondary (Full Load)12VCurrent - Output (Max)3.34APrimary Winding(s)Single, Multiple TapsSecondary Winding(s)SingleCenter TapNoPower - Max40 VAMounting TypeChasis MountSize / Dimension92.46mm L x 59.44mm WHeight - Seated (Max)56.39mmVoltage - Isolation1500VACWeight1.5 lbs (680.4g)	Manufacturer	Triad Magnetics
Package-SeriesClass 2, TCTTypeLaminated CoreVoltage - Primary120V, 240VVoltage - Secondary (Full Load)12VCurrent - Output (Max)3.34APrimary Winding(s)Single, Multiple TapsSecondary Winding(s)NoCenter TapNoPower - MaxGlassi MountMounting TypeSolder, Quick ConnectSter/ DimensionSolder, Quick ConnectSter/ Dimension5.39mmVoltage - Isolation1500VACWeightStoles (Soldeg)	Category	Transformers
SeriesClass 2, TCTTypeLaminated CoreVoltage - Primary120V, 240VVoltage - Secondary (Full Load)12VCurrent - Output (Max)3.34APrimary Winding(s)Single, Multiple TapsSecondary Winding(s)NoCenter TapNoPower - Max40 VAMounting TypeChasis MountTermination StyleSolder, Quick ConnectSize / Dimension92.46mm L x 59.44mm WHeight - Seated (Max)56.39mmVoltage - Isolation150VAC		Power Transformers
TypeLaminated CoreVoltage - Primary120V, 240VVoltage - Secondary (Full Load)12VCurrent - Output (Max)3.34APrimary Winding(s)Single, Multiple TapsSecondary Winding(s)SinglePower - Max40 VAPower - MaxChassis MountTermination StyleSolder, Quick ConnectSize / Dimension9.246mm L x 59.44mm WHeight - Seated (Max)56.39mmWoltage - Isolation1500VACWeight1.51bs (680.4g)	Package	-
TypeTime referVoltage - Primary120V, 240VVoltage - Secondary (Full Load)12VCurrent - Output (Max)3.34APrimary Winding(s)Single, Multiple TapsSecondary Winding(s)SingleCenter TapNoPower - Max40 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension92.46mm L x 59.44mm WHeight - Seated (Max)56.39mmVoltage - Isolation1500VACWeight1.5 lbs (680.4g)	Series	Class 2, TCT
Voltage - Secondary (Full Load)12VCurrent - Output (Max)3.34APrimary Winding(s)Single, Multiple TapsSecondary Winding(s)SingleCenter TapNoPower - Max40 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension92.46mm L x 59.44mm WHeight - Seated (Max)56.39mmVoltage - Isolation1500VACWeight1.5 lbs (680.4g)	Туре	Laminated Core
Current - Output (Max)3.34APrimary Winding(s)Single, Multiple TapsSecondary Winding(s)SingleCenter TapNoPower - Max40 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension92.46mm L x 59.44mm WHeight - Seated (Max)56.39mmVoltage - Isolation1500VACWeight1.5 lbs (680.4g)	Voltage - Primary	120V, 240V
Primary Winding(s)Single, Multiple TapsSecondary Winding(s)SingleCenter TapNoPower - Max40 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension92.46mm L x 59.44mm WHeight - Seated (Max)56.39mmVoltage - Isolation1500VACWeight1.5 lbs (680.4g)	Voltage - Secondary (Full Load)	12V
Secondary Winding(s)SingleCenter TapNoPower - Max40 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension92.46mm L x 59.44mm WHeight - Seated (Max)56.39mmVoltage - Isolation1500VACWeight1.5 lbs (680.4g)	Current - Output (Max)	3.34A
Center TapNoPower - Max40 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension92.46mm L x 59.44mm WHeight - Seated (Max)56.39mmVoltage - Isolation1500VACWeight1.5 lbs (680.4g)	Primary Winding(s)	Single, Multiple Taps
Power - Max40 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension92.46mm L x 59.44mm WHeight - Seated (Max)56.39mmVoltage - Isolation1500VACWeight1.5 lbs (680.4g)	Secondary Winding(s)	Single
Mounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension92.46mm L x 59.44mm WHeight - Seated (Max)56.39mmVoltage - Isolation1500VACWeight1.5 lbs (680.4g)	Center Tap	No
Termination StyleSolder, Quick ConnectSize / Dimension92.46mm L x 59.44mm WHeight - Seated (Max)56.39mmVoltage - Isolation1500VACWeight1.5 lbs (680.4g)	Power - Max	40 VA
Size / Dimension92.46mm L x 59.44mm WHeight - Seated (Max)56.39mmVoltage - Isolation1500VACWeight1.5 lbs (680.4g)	Mounting Type	Chassis Mount
Height - Seated (Max)56.39mmVoltage - Isolation1500VACWeight1.5 lbs (680.4g)	Termination Style	Solder, Quick Connect
Voltage - Isolation1500VACWeight1.5 lbs (680.4g)	Size / Dimension	92.46mm L x 59.44mm W
Weight 1.5 lbs (680.4g)	Height - Seated (Max)	56.39mm
	Voltage - Isolation	1500VAC
Report errors?	Weight	1.5 lbs (680.4g)
		Report errors?

#### **TCT40-08E07AB** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **TCT40-08E07AB** Payment Methods





If you have any question about TCT40-08E07AB, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com