

ТСТ50-05Е07АВ

TCT50-05E07AB Information



Part Number	TCT50-05E07AB	
Manufacturer	Triad Magnetics	
Category	Transformers Power Transformers	
Description	XFRMR LAMINATED 50VA CHAS MOUNT	
Package	-	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



TCT50-05E07AB Specifications

SeriesClass 2, TCTTypeLaminated CoreVoltage - Primary120V, 208V, 240VVoltage - Secondary (Full Load)24VCurrent - Output (Max)2.08APrimary Winding(s)Single, Multiple TapsSecondary Winding(s)SingleCenter TapNoPower - Max50 VA		
CategoryTransformersPackage-SeriesClass 2, TCTTypeLaminated CoreVoltage - Primary120V, 208V, 240VVoltage - Secondary (Full Load)24VCurrent - Output (Max)2.08APrimary Winding(s)Single, Multiple TapsSecondary Winding(s)SingleCenter TapNoPower - Max50 VAMounting TypeChassis MountSize / Dimension92.46mm L x 56.67mm WHeight - Seated (Max)57.40mmVoltage - Isolation1500VrmsWeight2 lbs (907.2g)	Manufacturer Part Number	TCT50-05E07AB
InterfactPower TransformersPackage-SeriesClass 2, TCTTypeLaminated CoreVoltage - Primary120V, 208V, 240VVoltage - Secondary (Full Load)24VCurrent - Output (Max)2.08APrimary Winding(s)Single, Multiple TapsSecondary Winding(s)SingleCenter TapNoPower - Max50 VAMounting TypeChasis MountSize / Dimension9.246mm L x 56.67mm WHeight - Seated (Max)57.40mmVoltage - Isolation1500VrmsWeight2 lbs (907.2g)	Manufacturer	Triad Magnetics
Package-SeriesClass 2, TCTTypeLaminated CoreVoltage - Primary120V, 208V, 240VVoltage - Secondary (Full Load)24VCurrent - Output (Max)2.08APrimary Winding(s)Single, Multiple TapsSecondary Winding(s)SingleCenter TapNoPower - Max50 VAMounting TypeChasis MountTermination StyleSolder, Quick ConnectSize / Dimension9.246mm L x 56.67mm WHeight - Seated (Max)57.40mmWotage - Isolation1500 VrmsWeight2.185 (07.2g)	Category	Transformers
SeriesClass 2, TCTTypeLaminated CoreVoltage - Primary120V, 208V, 240VVoltage - Secondary (Full Load)24VCurrent - Output (Max)2.08APrimary Winding(s)Single, Multiple TapsSecondary Winding(s)SinglePower - Max50 VAPower - MaxChassis MountMounting TypeSolder, Quick ConnectSize / Dimension92.46mm L x 56.67mm WHeight - Seated (Max)57.40mmWotage - Isolation1500VrmsWeight2 lbs (907.2g)		Power Transformers
TypeLaminated CoreVoltage - Primary120V, 208V, 240VVoltage - Secondary (Full Load)24VCurrent - Output (Max)2.08APrimary Winding(s)Single, Multiple TapsSecondary Winding(s)SinglePower - MaxNoPower - MaxChassis MountTermination StyleSolder, Quick ConnectSize / Dimension9.246mm L x 56.67mm WNotage - Isolation5.740mmWeightSingle Multiple TapsWeightSingle Multiple Taps	Package	-
Yoltage - Primary120V, 208V, 240VVoltage - Secondary (Full Load)24VCurrent - Output (Max)2.08APrimary Winding(s)Single, Multiple TapsSecondary Winding(s)SingleCenter TapNoPower - Max50 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension92.46mm L x 56.67mm WHeight - Seated (Max)57.40mmVoltage - Isolation1500VrmsWeight2 lbs (907.2g)	Series	Class 2, TCT
Voltage - Secondary (Full Load)24VCurrent - Output (Max)2.08APrimary Winding(s)Single, Multiple TapsSecondary Winding(s)SingleCenter TapNoPower - Max50 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension92.46mm L x 56.67mm WHeight - Seated (Max)57.40mmVoltage - Isolation1500VrmsWeight2 lbs (907.2g)	Туре	Laminated Core
Current - Output (Max)2.08APrimary Winding(s)Single, Multiple TapsSecondary Winding(s)SingleCenter TapNoPower - Max50 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension92.46mm L x 56.67mm WHeight - Seated (Max)57.40mmVoltage - Isolation1500VrmsWeight2 lbs (907.2g)	Voltage - Primary	120V, 208V, 240V
Primary Winding(s)Single, Multiple TapsSecondary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max50 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension92.46mm L x 56.67mm WHeight - Seated (Max)57.40mmVoltage - Isolation1500VrmsWeight2 lbs (907.2g)	Voltage - Secondary (Full Load)	24V
Secondary Winding(s)SingleCenter TapNoPower - Max50 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension92.46mm L x 56.67mm WHeight - Seated (Max)57.40mmVoltage - Isolation1500VrmsWeight2 lbs (907.2g)	Current - Output (Max)	2.08A
Center TapNoPower - Max50 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension92.46mm L x 56.67mm WHeight - Seated (Max)57.40mmVoltage - Isolation1500VrmsWeight21bs (907.2g)	Primary Winding(s)	Single, Multiple Taps
Power - Max50 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension92.46mm L x 56.67mm WHeight - Seated (Max)57.40mmVoltage - Isolation1500VrmsWeight2 lbs (907.2g)	Secondary Winding(s)	Single
Mounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension92.46mm L x 56.67mm WHeight - Seated (Max)57.40mmVoltage - Isolation1500VrmsWeight2 lbs (907.2g)	Center Tap	No
Termination StyleSolder, Quick ConnectSize / Dimension92.46mm L x 56.67mm WHeight - Seated (Max)57.40mmVoltage - Isolation1500VrmsWeight2 lbs (907.2g)	Power - Max	50 VA
Size / Dimension92.46mm L x 56.67mm WHeight - Seated (Max)57.40mmVoltage - Isolation1500VrmsWeight2 lbs (907.2g)	Mounting Type	Chassis Mount
Height - Seated (Max)57.40mmVoltage - Isolation1500VrmsWeight2 lbs (907.2g)	Termination Style	Solder, Quick Connect
Voltage - Isolation1500VrmsWeight2 lbs (907.2g)	Size / Dimension	92.46mm L x 56.67mm W
Weight 2 lbs (907.2g)	Height - Seated (Max)	57.40mm
	Voltage - Isolation	1500Vrms
Report errors?	Weight	2 lbs (907.2g)
		Report errors?

TCT50-05E07AB Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE UARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

TCT50-05E07AB Payment Methods





If you have any question about TCT50-05E07AB, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com