

TDC17-2-R Information

Heisener.com

Part Number TDC17-2-R
Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

DescriptionFUSE CARTRIDGEPackageCartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TDC17-2-R Specifications

Manufacturer Part Number Manufacturer Eaton Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series TDC17 Fuse Type Current Rating Voltage Rating - AC Voltage Rating - DC Response Time Applications Features Class Approvals Operating Temperature Breaking Capacity @ Rated Voltage Holder Eaton Circuit Protection Electrical, Specialty Fuses Cartridge Car	•	
Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series TDC17 Fuse Type Cartridge Current Rating 2A Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Circuit Protection Electrical, Specialty Fuses Cartridge Cartridge Cartridge Cartridge Cartridge 2A Page Cartridge Cartrid	Manufacturer Part Number	TDC17-2-R
Electrical, Specialty Fuses Package Cartridge, Non-Standard Series TDC17 Fuse Type Cartridge Current Rating 2A Voltage Rating - AC 250V Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage IELECTRICAL Specialty Fuses Cartridge Cartridge Cartridge Cartridge Cartridge Eattridge Cartridge Cartridge Cartridge Cartridge Electrical Features - Closs - Approvals - Operating Temperature O°C ~ 35°C Breaking Capacity @ Rated Voltage	Manufacturer	Eaton
Package Cartridge, Non-Standard Series TDC17 Fuse Type Cartridge Current Rating 2A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage 1kA	Category	Circuit Protection
Series TDC17 Fuse Type Cartridge Current Rating 2A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature 0°C ~ 35°C Breaking Capacity @ Rated Voltage 1kA		Electrical, Specialty Fuses
Fuse Type Current Rating 2A Voltage Rating - AC 250V Voltage Rating - DC Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Current Rating 2A 250V - Estor - Colemont	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage 2A 250V - Electrical, Industrial - Class - Approvals - Breaking Capacity @ Rated Voltage	Series	TDC17
Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage 250V - 0 0 0 - 1 0 1 1 250V - 1 0 0 1 1 1 1 1 1 1 1 1 1	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals Operating Temperature 0°C ~ 35°C Breaking Capacity @ Rated Voltage - Industrial Fast Approvals - Industrial Industrial - Industrial I	Current Rating	2A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Fast Fast Clouder Fast Clouder Fast O'C ~ 35°C Breaking Capacity @ Rated Voltage	Voltage Rating - AC	250V
Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature 0°C ~ 35°C Breaking Capacity @ Rated Voltage 1kA	Voltage Rating - DC	-
Features - Class - Approvals - Operating Temperature 0°C ~ 35°C Breaking Capacity @ Rated Voltage 1kA	Response Time	Fast
Class - Approvals - Operating Temperature 0°C ~ 35°C Breaking Capacity @ Rated Voltage 1kA	Applications	Electrical, Industrial
Approvals - Operating Temperature $0^{\circ}\text{C} \sim 35^{\circ}\text{C}$ Breaking Capacity @ Rated Voltage 1kA	Features	-
Operating Temperature 0°C ~ 35°C Breaking Capacity @ Rated Voltage 1kA	Class	-
Breaking Capacity @ Rated Voltage 1kA	Approvals	-
	Operating Temperature	0°C ~ 35°C
Mounting Type Holder	Breaking Capacity @ Rated Voltage	1kA
Troubing Type	Mounting Type	Holder
Package / Case Cartridge, Non-Standard	Package / Case	Cartridge, Non-Standard
Size / Dimension 0.210" Dia x 0.758" L (5.34mm x 19.25mm)	Size / Dimension	0.210" Dia x 0.758" L (5.34mm x 19.25mm)
Report errors?		Report errors?

TDC17-2-R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TDC17-2-R Payment Methods



















TDC17-2-R Shipping Methods













If you have any question about TDC17-2-R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com