



TE100B270RJ Information

Heisener.com

Part Number TE100B270RJ

Manufacturer TE Connectivity Passive Product

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 270 OHM 5% 100W

Package Radial, Tubular

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TE100B270RJ Specifications

Manufacturer Part Number TE100B270RJ Manufacturer TE Connectivity Passive Product Category Resistors Package Radial, Tubular Series TE, CGS Resistance 270 Ohms Tolerance ±5% Power (Watts) 100W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.102" Dia x 7.165" L (28.00mm x 182.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - Failure Rate -		
CategoryResistorsPackageRadial, TubularSeriesTE, CGSResistance270 OhmsTolerance±5%Power (Watts)100WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension1.102" Dia x 7.165" L (28.00mm x 182.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Manufacturer Part Number	TE100B270RJ
Chassis Mount Resistors Package Radial, Tubular TE, CGS Resistance 270 Ohms Tolerance ±5% Power (Watts) 100W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.102" Dia x 7.165" L (28.00mm x 182.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate	Manufacturer	TE Connectivity Passive Product
PackageRadial, TubularSeriesTE, CGSResistance270 OhmsTolerance±5%Power (Watts)100WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension1.102" Dia x 7.165" L (28.00mm x 182.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Category	Resistors
SeriesTE, CGSResistance270 OhmsTolerance±5%Power (Watts)100WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension1.102" Dia x 7.165" L (28.00mm x 182.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-		Chassis Mount Resistors
Resistance270 OhmsTolerance±5%Power (Watts)100WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension1.102" Dia x 7.165" L (28.00mm x 182.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Package	Radial, Tubular
Tolerance ±5% Power (Watts) 100W Composition Wirewound Temperature Coefficient ±440pm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.102" Dia x 7.165" L (28.00mm x 182.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Series	TE, CGS
Power (Watts) Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.102" Dia x 7.165" L (28.00mm x 182.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Resistance	270 Ohms
Composition Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.102" Dia x 7.165" L (28.00mm x 182.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate Wirewound ±440ppm/°C -25°C ~ 225°C Flame Proof, Safety Silicone Coated 1.102" Dia x 7.165" L (28.00mm x 182.00mm) - Radial, Tubular - Failure Rate	Tolerance	±5%
Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.102" Dia x 7.165" L (28.00mm x 182.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Power (Watts)	100W
Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.102" Dia x 7.165" L (28.00mm x 182.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Composition	Wirewound
Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.102" Dia x 7.165" L (28.00mm x 182.00mm) Height - Seated (Max) Lead Style Package / Case Radial, Tubular Failure Rate Flame Proof, Safety Silicone Coated Brackets Solder L(28.00mm x 182.00mm)	Temperature Coefficient	±440ppm/°C
Coating, Housing Type Silicone Coated Mounting Feature Brackets 1.102" Dia x 7.165" L (28.00mm x 182.00mm) Height - Seated (Max) Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate Silicone Coated Brackets 1.102" Dia x 7.165" L (28.00mm x 182.00mm)	Operating Temperature	-25°C ~ 225°C
Mounting Feature Size / Dimension 1.102" Dia x 7.165" L (28.00mm x 182.00mm) Height - Seated (Max) Lead Style Package / Case Radial, Tubular Failure Rate Brackets 1.102" Dia x 7.165" L (28.00mm x 182.00mm) - Radial, Tubular - Radial, Tubular	Features	Flame Proof, Safety
Size / Dimension 1.102" Dia x 7.165" L (28.00mm x 182.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Coating, Housing Type	Silicone Coated
Height - Seated (Max) Lead Style Package / Case Radial, Tubular Failure Rate -	Mounting Feature	Brackets
Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Size / Dimension	1.102" Dia x 7.165" L (28.00mm x 182.00mm)
Package / Case Radial, Tubular Failure Rate -	Height - Seated (Max)	-
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Radial, Tubular
Report errors?	Failure Rate	-
		Report errors?

TE100B270RJ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TE100B270RJ Payment Methods



















TE100B270RJ Shipping Methods













If you have any question about TE100B270RJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com